

Package: mlr3torch (via r-universe)

September 6, 2024

Title Deep Learning with 'mlr3'

Version 0.1.0

Description Deep Learning library that extends the mlr3 framework by building upon the 'torch' package. It allows to conveniently build, train, and evaluate deep learning models without having to worry about low level details. Custom architectures can be created using the graph language defined in 'mlr3pipelines'.

License LGPL (>= 3)

Depends mlr3 (>= 0.20.0), mlr3pipelines (>= 0.6.0), torch (>= 0.13.0), R (>= 3.5.0)

Imports backports, checkmate (>= 2.2.0), data.table, lgr, methods, mlr3misc (>= 0.14.0), paradox (>= 1.0.0), R6, withr

Suggests callr, future, ggplot2, igraph, jsonlite, knitr, magick, mlr3tuning (>= 1.0.0), progress, rmarkdown, rpart, viridis, visNetwork, testthat (>= 3.0.0), torchvision (>= 0.6.0), waldo

Config/testthat/edition 3

NeedsCompilation no

ByteCompile no

Encoding UTF-8

Roxygen list(markdown = TRUE, r6 = TRUE)

RoxygenNote 7.3.2

Collate 'CallbackSet.R' 'zzz.R' 'TorchCallback.R'
'CallbackSetCheckpoint.R' 'CallbackSetEarlyStopping.R'
'CallbackSetHistory.R' 'CallbackSetProgress.R' 'ContextTorch.R'
'DataBackendLazy.R' 'utils.R' 'DataDescriptor.R'
'LearnerTorch.R' 'LearnerTorchFeatureless.R'
'LearnerTorchImage.R' 'LearnerTorchMLP.R' 'task_dataset.R'
'shape.R' 'PipeOpTorchIngress.R' 'LearnerTorchModel.R'
'LearnerTorchTabResNet.R' 'LearnerTorchVision.R'
'ModelDescriptor.R' 'PipeOpModule.R' 'PipeOpTorch.R'
'PipeOpTaskPreprocTorch.R' 'PipeOpTorchActivation.R'
'PipeOpTorchAvgPool.R' 'PipeOpTorchBatchNorm.R'

'PipeOpTorchBlock.R' 'PipeOpTorchCallbacks.R'
 'PipeOpTorchConv.R' 'PipeOpTorchConvTranspose.R'
 'PipeOpTorchDropout.R' 'PipeOpTorchHead.R'
 'PipeOpTorchLayerNorm.R' 'PipeOpTorchLinear.R' 'TorchLoss.R'
 'PipeOpTorchLoss.R' 'PipeOpTorchMaxPool.R' 'PipeOpTorchMerge.R'
 'PipeOpTorchModel.R' 'PipeOpTorchOptimizer.R'
 'PipeOpTorchReshape.R' 'PipeOpTorchSoftmax.R'
 'TaskClassif_lazy_iris.R' 'TaskClassif_mnist.R'
 'TaskClassif_tiny_imagenet.R' 'TorchDescriptor.R'
 'TorchOptimizer.R' 'bibentries.R' 'cache.R' 'lazy_tensor.R'
 'learner_torch_methods.R' 'materialize.R' 'merge_graphs.R'
 'nn_graph.R' 'paramset_torchlearner.R' 'preprocess.R'
 'rd_info.R' 'with_torch_settings.R'

Repository <https://mlr-org.r-universe.dev>

RemoteUrl <https://github.com/mlr-org/mlr3torch>

RemoteRef v0.1.0

RemoteSha d37da4418cfc4d19801800da2e9a8b885ef5387

Contents

mlr3torch-package	5
assert_lazy_tensor	6
as_data_descriptor	6
as_lazy_tensor	7
as_torch_callback	8
as_torch_callbacks	9
as_torch_loss	10
as_torch_optimizer	10
auto_device	11
batchgetter_categ	11
batchgetter_num	12
callback_set	12
DataDescriptor	14
is_lazy_tensor	17
lazy_tensor	17
materialize	18
mlr3torch_callbacks	19
mlr3torch_losses	20
mlr3torch_optimizers	21
mlr_backends_lazy	21
mlr_callback_set	25
mlr_callback_set.checkpoint	28
mlr_callback_set.history	29
mlr_callback_set.progress	30
mlr_context_torch	32
mlr_learners.mlp	34

mlr_learners.tab_resnet	37
mlr_learners.torchvision	39
mlr_learners.torch_featureless	41
mlr_learners.torch	43
mlr_learners.torch_image	50
mlr_learners.torch_model	51
mlr_pipeops_module	54
mlr_pipeops_nn_avg_pool1d	57
mlr_pipeops_nn_avg_pool2d	59
mlr_pipeops_nn_avg_pool3d	61
mlr_pipeops_nn_batch_norm1d	63
mlr_pipeops_nn_batch_norm2d	65
mlr_pipeops_nn_batch_norm3d	67
mlr_pipeops_nn_block	69
mlr_pipeops_nn_celu	71
mlr_pipeops_nn_conv1d	73
mlr_pipeops_nn_conv2d	75
mlr_pipeops_nn_conv3d	77
mlr_pipeops_nn_conv_transpose1d	79
mlr_pipeops_nn_conv_transpose2d	81
mlr_pipeops_nn_conv_transpose3d	84
mlr_pipeops_nn_dropout	86
mlr_pipeops_nn_elu	88
mlr_pipeops_nn_flatten	90
mlr_pipeops_nn_gelu	91
mlr_pipeops_nn_glu	93
mlr_pipeops_nn_hardshrink	95
mlr_pipeops_nn_hardsigmoid	97
mlr_pipeops_nn_hardtanh	98
mlr_pipeops_nn_head	100
mlr_pipeops_nn_layer_norm	102
mlr_pipeops_nn_leaky_relu	104
mlr_pipeops_nn_linear	106
mlr_pipeops_nn_log_sigmoid	107
mlr_pipeops_nn_max_pool1d	109
mlr_pipeops_nn_max_pool2d	111
mlr_pipeops_nn_max_pool3d	114
mlr_pipeops_nn_merge	116
mlr_pipeops_nn_merge_cat	118
mlr_pipeops_nn_merge_prod	120
mlr_pipeops_nn_merge_sum	122
mlr_pipeops_nn_prelu	124
mlr_pipeops_nn_relu	126
mlr_pipeops_nn_relu6	128
mlr_pipeops_nn_reshape	129
mlr_pipeops_nn_rrelu	131
mlr_pipeops_nn_selu	133
mlr_pipeops_nn_sigmoid	135

mlr_pipeops_nn_softmax	137
mlr_pipeops_nn_softplus	138
mlr_pipeops_nn_softshrink	140
mlr_pipeops_nn_softsign	142
mlr_pipeops_nn_squeeze	144
mlr_pipeops_nn_tanh	147
mlr_pipeops_nn_tanhshrink	148
mlr_pipeops_nn_threshold	150
mlr_pipeops_preproc_torch	152
mlr_pipeops_preproc_torch.augment_center_crop	157
mlr_pipeops_preproc_torch.augment_color_jitter	157
mlr_pipeops_preproc_torch.augment_crop	158
mlr_pipeops_preproc_torch.augment_hflip	159
mlr_pipeops_preproc_torch.augment_random_affine	159
mlr_pipeops_preproc_torch.augment_random_choice	160
mlr_pipeops_preproc_torch.augment_random_crop	160
mlr_pipeops_preproc_torch.augment_random_horizontal_flip	161
mlr_pipeops_preproc_torch.augment_random_order	162
mlr_pipeops_preproc_torch.augment_random_resized_crop	162
mlr_pipeops_preproc_torch.augment_random_vertical_flip	163
mlr_pipeops_preproc_torch.augment_resized_crop	163
mlr_pipeops_preproc_torch.augment_rotate	164
mlr_pipeops_preproc_torch.augment_vflip	165
mlr_pipeops_preproc_torch.trafo_adjust_brightness	165
mlr_pipeops_preproc_torch.trafo_adjust_gamma	166
mlr_pipeops_preproc_torch.trafo_adjust_hue	166
mlr_pipeops_preproc_torch.trafo_adjust_saturation	167
mlr_pipeops_preproc_torch.trafo_grayscale	167
mlr_pipeops_preproc_torch.trafo_nop	168
mlr_pipeops_preproc_torch.trafo_normalize	168
mlr_pipeops_preproc_torch.trafo_pad	169
mlr_pipeops_preproc_torch.trafo_reshape	169
mlr_pipeops_preproc_torch.trafo_resize	170
mlr_pipeops_preproc_torch.trafo_rgb_to_grayscale	170
mlr_pipeops_torch	171
mlr_pipeops_torch_callbacks	177
mlr_pipeops_torch_ingress	178
mlr_pipeops_torch_ingress_categ	180
mlr_pipeops_torch_ingress_ltnsr	182
mlr_pipeops_torch_ingress_num	185
mlr_pipeops_torch_loss	187
mlr_pipeops_torch_model	189
mlr_pipeops_torch_model_classif	192
mlr_pipeops_torch_model_regr	194
mlr_pipeops_torch_optimizer	196
mlr_tasks_lazy_iris	197
mlr_tasks_mnist	198
mlr_tasks_tiny_imagenet	199

ModelDescriptor	200
model_descriptor_to_learner	202
model_descriptor_to_module	202
model_descriptor_union	203
nn_graph	204
nn_merge_cat	205
nn_merge_prod	206
nn_merge_sum	206
nn_reshape	206
nn_squeeze	207
nn_unsqueeze	207
pipeop_preproc_torch	208
task_dataset	209
TorchCallback	210
TorchDescriptor	212
TorchIngressToken	215
TorchLoss	216
TorchOptimizer	218
torch_callback	220
t_clbk	223
t_loss	224
t_opt	225

Index**227**

mlr3torch-package *mlr3torch: Deep Learning with 'mlr3'*

Description

Deep Learning library that extends the mlr3 framework by building upon the 'torch' package. It allows to conveniently build, train, and evaluate deep learning models without having to worry about low level details. Custom architectures can be created using the graph language defined in 'mlr3pipelines'.

Options

- `mlr3torch.cache`: Whether to cache the downloaded data (TRUE) or not (FALSE, default). This can also be set to a specific folder on the file system to be used as the cache directory.

Author(s)

Maintainer: Sebastian Fischer <sebf.fischer@gmail.com> ([ORCID](#))

Authors:

- Martin Binder <mlr.developer@mb706.com>

Other contributors:

- Bernd Bischl <bernd_bischl@gmx.net> ([ORCID](#)) [contributor]
- Lukas Burk <github@quantenbrot.de> ([ORCID](#)) [contributor]
- Florian Pfisterer <pfistererf@googlemail.com> ([ORCID](#)) [contributor]

assert_lazy_tensor *Assert Lazy Tensor*

Description

Asserts whether something is a lazy tensor.

Usage

```
assert_lazy_tensor(x)
```

Arguments

x	(any) Object to check.
---	---------------------------

as_data_descriptor *Convert to Data Descriptor*

Description

Converts the input to a [DataDescriptor](#).

Usage

```
as_data_descriptor(x, dataset_shapes, ...)
```

Arguments

x	(any) Object to convert.
dataset_shapes	(named list() of (integer() or NULL)) The shapes of the output. Names are the elements of the list returned by the dataset. If the shape is not NULL (unknown, e.g. for images of different sizes) the first dimension must be NA to indicate the batch dimension.
...	(any) Further arguments passed to the DataDescriptor constructor.

Examples

```

ds = dataset("example",
  initialize = function() self$iris = iris[, -5],
  .getitem = function(i) list(x = torch_tensor(as.numeric(self$iris[i, ]))),
  .length = function() nrow(self$iris)
)()
as_data_descriptor(ds, list(x = c(NA, 4L)))

# if the dataset has a .getbatch method, the shapes are inferred
ds2 = dataset("example",
  initialize = function() self$iris = iris[, -5],
  .getbatch = function(i) list(x = torch_tensor(as.matrix(self$iris[i, ]))),
  .length = function() nrow(self$iris)
)()
as_data_descriptor(ds2)

```

as_lazy_tensor	<i>Convert to Lazy Tensor</i>
----------------	-------------------------------

Description

Convert a object to a [lazy_tensor](#).

Usage

```

as_lazy_tensor(x, ...)

## S3 method for class 'dataset'
as_lazy_tensor(x, dataset_shapes = NULL, ids = NULL, ...)

```

Arguments

x	(any) Object to convert to a lazy_tensor
...	(any) Additional arguments passed to the method.
dataset_shapes	(named list() of (integer() or NULL)) The shapes of the output. Names are the elements of the list returned by the dataset. If the shape is not NULL (unknown, e.g. for images of different sizes) the first dimension must be NA to indicate the batch dimension.
ids	(integer()) Which ids to include in the lazy tensor.

Examples

```

iris_ds = dataset("iris",
  initialize = function() {
    self$iris = iris[, -5]
  },
  .getbatch = function(i) {
    list(x = torch_tensor(as.matrix(self$iris[i, ])))
  },
  .length = function() nrow(self$iris)
)()
# no need to specify the dataset shapes as they can be inferred from the .getbatch method
# only first 5 observations
as_lazy_tensor(iris_ds, ids = 1:5)
# all observations
head(as_lazy_tensor(iris_ds))

iris_ds2 = dataset("iris",
  initialize = function() self$iris = iris[, -5],
  .getitem = function(i) list(x = torch_tensor(as.numeric(self$iris[i, ]))),
  .length = function() nrow(self$iris)
)()
# if .getitem is implemented we cannot infer the shapes as they might vary,
# so we have to annotate them explicitly
as_lazy_tensor(iris_ds2, dataset_shapes = list(x = c(NA, 4L)))[1:5]

# Convert a matrix
lt = as_lazy_tensor(matrix(rnorm(100), nrow = 20))
materialize(lt[1:5], rbind = TRUE)

```

as_torch_callback *Convert to a TorchCallback*

Description

Converts an object to a [TorchCallback](#).

Usage

```
as_torch_callback(x, clone = FALSE, ...)
```

Arguments

x	(any) Object to be converted.
clone	(logical(1)) Whether to make a deep clone.
...	(any) Additional arguments

Value

[TorchCallback](#).

See Also

Other Callback: [TorchCallback](#), [as_torch_callbacks\(\)](#), [callback_set\(\)](#), [mlr3torch_callbacks](#), [mlr_callback_set](#), [mlr_callback_set.checkpoint](#), [mlr_callback_set.progress](#), [mlr_context_torch](#), [t_clbk\(\)](#), [torch_callback\(\)](#)

as_torch_callbacks *Convert to a list of Torch Callbacks*

Description

Converts an object to a list of [TorchCallback](#).

Usage

```
as_torch_callbacks(x, clone, ...)
```

Arguments

x	(any) Object to convert.
clone	(logical(1)) Whether to create a deep clone.
...	(any) Additional arguments.

Value

list() of [TorchCallbacks](#)

See Also

Other Callback: [TorchCallback](#), [as_torch_callback\(\)](#), [callback_set\(\)](#), [mlr3torch_callbacks](#), [mlr_callback_set](#), [mlr_callback_set.checkpoint](#), [mlr_callback_set.progress](#), [mlr_context_torch](#), [t_clbk\(\)](#), [torch_callback\(\)](#)

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as_torch_loss\(\)](#), [as_torch_optimizer\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_clbk\(\)](#), [t_loss\(\)](#), [t_opt\(\)](#)

as_torch_loss *Convert to TorchLoss*

Description

Converts an object to a [TorchLoss](#).

Usage

```
as_torch_loss(x, clone = FALSE, ...)
```

Arguments

x	(any) Object to convert to a TorchLoss .
clone	(logical(1)) Whether to make a deep clone.
...	(any) Additional arguments. Currently used to pass additional constructor arguments to TorchLoss for objects of type nn_loss.

Value

[TorchLoss](#).

See Also

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as_torch_callbacks\(\)](#), [as_torch_optimizer\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_clbk\(\)](#), [t_loss\(\)](#), [t_opt\(\)](#)

as_torch_optimizer *Convert to TorchOptimizer*

Description

Converts an object to a [TorchOptimizer](#).

Usage

```
as_torch_optimizer(x, clone = FALSE, ...)
```

Arguments

x	(any) Object to convert to a TorchOptimizer .
clone	(logical(1)) Whether to make a deep clone. Default is FALSE.
...	(any) Additional arguments. Currently used to pass additional constructor arguments to TorchOptimizer for objects of type torch_optimizer_generator.

Value

[TorchOptimizer](#)

See Also

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as_torch_callbacks\(\)](#), [as_torch_loss\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_clbk\(\)](#), [t_loss\(\)](#), [t_opt\(\)](#)

auto_device	<i>Auto Device</i>
-------------	--------------------

Description

First tries cuda, then cpu.

Usage

```
auto_device(device = NULL)
```

Arguments

device	(character(1)) The device. If not NULL, is returned as is.
--------	---

batchgetter_categ	<i>Batchgetter for Categorical data</i>
-------------------	---

Description

Converts a data frame of categorical data into a long tensor by converting the data to integers. No input checks are performed.

Usage

```
batchgetter_categ(data, device, ...)
```

Arguments

data	(data.table) data.table to be converted to a tensor.
device	(character(1)) The device.
...	(any) Unused.

batchgetter_num	<i>Batchgetter for Numeric Data</i>
-----------------	-------------------------------------

Description

Converts a data frame of numeric data into a float tensor by calling `as.matrix()`. No input checks are performed

Usage

```
batchgetter_num(data, device, ...)
```

Arguments

data	(data.table()) data.table to be converted to a tensor.
device	(character(1)) The device on which the tensor should be created.
...	(any) Unused.

callback_set	<i>Create a Set of Callbacks for Torch</i>
--------------	--

Description

Creates an R6ClassGenerator inheriting from [CallbackSet](#). Additionally performs checks such as that the stages are not accidentally misspelled. To create a [TorchCallback](#) use `torch_callback()`.

In order for the resulting class to be cloneable, the private method `$deep_clone()` must be provided.

Usage

```

callback_set(
  classname,
  on_begin = NULL,
  on_end = NULL,
  on_exit = NULL,
  on_epoch_begin = NULL,
  on_before_valid = NULL,
  on_epoch_end = NULL,
  on_batch_begin = NULL,
  on_batch_end = NULL,
  on_after_backward = NULL,
  on_batch_valid_begin = NULL,
  on_batch_valid_end = NULL,
  on_valid_end = NULL,
  state_dict = NULL,
  load_state_dict = NULL,
  initialize = NULL,
  public = NULL,
  private = NULL,
  active = NULL,
  parent_env = parent.frame(),
  inherit = CallbackSet,
  lock_objects = FALSE
)

```

Arguments

classname	(character(1)) The class name.
on_begin, on_epoch_end, on_batch_valid_begin, on_batch_valid_end, on_valid_end, on_end, on_epoch_begin, on_batch_begin, on_batch_end, on_after_backward, on_exit	(function) Function to execute at the given stage, see section <i>Stages</i> .
state_dict	(function()) The function that retrieves the state dict from the callback. This is what will be available in the learner after training.
load_state_dict	(function(state_dict)) Function that loads a callback state.
initialize	(function()) The initialization method of the callback.
public, private, active	(list()) Additional public, private, and active fields to add to the callback.
parent_env	(environment()) The parent environment for the R6Class .

<code>inherit</code>	(R6ClassGenerator) From which class to inherit. This class must either be <code>CallbackSet</code> (default) or inherit from it.
<code>lock_objects</code>	(logical(1)) Whether to lock the objects of the resulting <code>R6Class</code> . If FALSE (default), values can be freely assigned to self without declaring them in the class definition.

Value`CallbackSet`**See Also**

Other Callback: `TorchCallback`, `as_torch_callback()`, `as_torch_callbacks()`, `mlr3torch_callbacks`, `mlr_callback_set`, `mlr_callback_set.checkpoint`, `mlr_callback_set.progress`, `mlr_context_torch`, `t_clbk()`, `torch_callback()`

`DataDescriptor`*Data Descriptor*

Description

A data descriptor is a rather internal data structure used in the `lazy_tensor` data type. In essence it is an annotated `torch::dataset` and a preprocessing graph (consisting mostly of `PipeOpModule` operators). The additional meta data (e.g. pointer, shapes) allows to preprocess `lazy_tensors` in an `mlr3pipelines::Graph` just like any (non-lazy) data types. The preprocessing is applied when `materialize()` is called on the `lazy_tensor`.

To create a data descriptor, you can also use the `as_data_descriptor()` function.

Details

While it would be more natural to define this as an S3 class, we opted for an R6 class to avoid the usual trouble of serializing S3 objects. If each row contained a `DataDescriptor` as an S3 class, this would copy the object when serializing.

Public fields`dataset` (`torch::dataset`)

The dataset.

`graph` (`Graph`)

The preprocessing graph.

`dataset_shapes` (named `list()` of (`integer()` or `NULL`))

The shapes of the output.

`input_map` (`character()`)

The input map from the dataset to the preprocessing graph.

`pointer` (`character(2)`)
 The output pointer.

`pointer_shape` (`integer()` | `NULL`)
 The shape of the output indicated by pointer.

`dataset_hash` (`character(1)`)
 Hash for the wrapped dataset.

`hash` (`character(1)`)
 Hash for the data descriptor.

`graph_input` (`character()`)
 The input channels of the preprocessing graph (cached to save time).

`pointer_shape_predict` (`integer()` or `NULL`)
 Internal use only.

Methods

Public methods:

- [DataDescriptor\\$new\(\)](#)
- [DataDescriptor\\$print\(\)](#)
- [DataDescriptor\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```

DataDescriptor$new(
  dataset,
  dataset_shapes = NULL,
  graph = NULL,
  input_map = NULL,
  pointer = NULL,
  pointer_shape = NULL,
  pointer_shape_predict = NULL,
  clone_graph = TRUE
)

```

Arguments:

`dataset` ([torch::dataset](#))

The torch dataset. It should return a named `list()` of [torch_tensor](#) objects.

`dataset_shapes` (named `list()` of (`integer()` or `NULL`))

The shapes of the output. Names are the elements of the list returned by the dataset. If the shape is not `NULL` (unknown, e.g. for images of different sizes) the first dimension must be `NA` to indicate the batch dimension.

`graph` ([Graph](#))

The preprocessing graph. If left `NULL`, no preprocessing is applied to the data and `input_map`, `pointer`, `pointer_shape`, and `pointer_shape_predict` are inferred in case the dataset returns only one element.

`input_map` (`character()`)

Character vector that must have the same length as the input of the graph. Specifies how the data from the dataset is fed into the preprocessing graph.

`pointer` (character(2) | NULL)
 Points to an output channel within graph: Element 1 is the PipeOp's id and element 2 is that PipeOp's output channel.

`pointer_shape` (integer() | NULL)
 Shape of the output indicated by pointer.

`pointer_shape_predict` (integer() or NULL)
 Internal use only. Used in a [Graph](#) to anticipate possible mismatches between train and predict shapes.

`clone_graph` (logical(1))
 Whether to clone the preprocessing graph.

Method `print()`: Prints the object

Usage:

```
DataDescriptor$print(...)
```

Arguments:

... (any)
 Unused

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
DataDescriptor$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

ModelDescriptor, lazy_tensor

Examples

```
# Create a dataset
ds = dataset(
  initialize = function() self$x = torch_randn(10, 3, 3),
  .getitem = function(i) list(x = self$x[i, ]),
  .length = function() nrow(self$x)
)()
dd = DataDescriptor$new(ds, list(x = c(NA, 3, 3)))
dd
# is the same as using the converter:
as_data_descriptor(ds, list(x = c(NA, 3, 3)))
```

is_lazy_tensor	<i>Check for lazy tensor</i>
----------------	------------------------------

Description

Checks whether an object is a lazy tensor.

Usage

```
is_lazy_tensor(x)
```

Arguments

x	(any) Object to check.
---	---------------------------

lazy_tensor	<i>Create a lazy tensor</i>
-------------	-----------------------------

Description

Create a lazy tensor.

Usage

```
lazy_tensor(data_descriptor = NULL, ids = NULL)
```

Arguments

data_descriptor	(DataDescriptor or NULL) The data descriptor or NULL for a lazy tensor of length 0.
ids	(integer()) The elements of the data_descriptor to be included in the lazy tensor.

Examples

```
ds = dataset("example",
  initialize = function() self$iris = iris[, -5],
  .getitem = function(i) list(x = torch_tensor(as.numeric(self$iris[i, ]))),
  .length = function() nrow(self$iris)
)()
dd = as_data_descriptor(ds, list(x = c(NA, 4L)))
lt = as_lazy_tensor(dd)
```

 materialize

Materialize Lazy Tensor Columns

Description

This will materialize a `lazy_tensor()` or a `data.frame() / list()` containing – among other things – `lazy_tensor()` columns. I.e. the data described in the underlying `DataDescriptors` is loaded for the indices in the `lazy_tensor()`, is preprocessed and then put unto the specified device. Because not all elements in a lazy tensor must have the same shape, a list of tensors is returned by default. If all elements have the same shape, these tensors can also be rbinded into a single tensor (parameter `rbind`).

Usage

```
materialize(x, device = "cpu", rbind = FALSE, ...)

## S3 method for class 'list'
materialize(x, device = "cpu", rbind = FALSE, cache = "auto", ...)
```

Arguments

<code>x</code>	(any) The object to materialize. Either a <code>lazy_tensor</code> or a <code>list()</code> / <code>data.frame()</code> containing <code>lazy_tensor</code> columns.
<code>device</code>	(character(1)) The torch device.
<code>rbind</code>	(logical(1)) Whether to rbind the lazy tensor columns (TRUE) or return them as a list of tensors (FALSE). In the second case, there is no batch dimension.
<code>...</code>	(any) Additional arguments.
<code>cache</code>	(character(1) or environment() or NULL) Optional cache for (intermediate) materialization results. Per default, caching will be enabled when the same dataset or data descriptor (with different output pointer) is used for more than one lazy tensor column.

Details

Materializing a lazy tensor consists of:

1. Loading the data from the internal dataset of the `DataDescriptor`.
2. Processing these batches in the preprocessing `Graphs`.
3. Returning the result of the `PipeOp` pointed to by the `DataDescriptor` (pointer).

With multiple `lazy_tensor` columns we can benefit from caching because: a) Output(s) from the dataset might be input to multiple graphs. b) Different lazy tensors might be outputs from the same graph.

For this reason it is possible to provide a cache environment. The hash key for a) is the hash of the indices and the dataset. The hash key for b) is the hash of the indices, dataset and preprocessing graph.

Value

(list() of `lazy_tensors` or a `lazy_tensor`)

Examples

```
lt1 = as_lazy_tensor(torch_randn(10, 3))
materialize(lt1, rbind = TRUE)
materialize(lt1, rbind = FALSE)
lt2 = as_lazy_tensor(torch_randn(10, 4))
d = data.table::data.table(lt1 = lt1, lt2 = lt2)
materialize(d, rbind = TRUE)
materialize(d, rbind = FALSE)
```

mlr3torch_callbacks *Dictionary of Torch Callbacks*

Description

A `mlr3misc::Dictionary` of torch callbacks. Use `t_clbk()` to conveniently retrieve callbacks. Can be converted to a `data.table` using `as.data.table`.

Usage

```
mlr3torch_callbacks
```

Format

An object of class `DictionaryMlr3torchCallbacks` (inherits from `Dictionary`, R6) of length 13.

See Also

Other Callback: `TorchCallback`, `as_torch_callback()`, `as_torch_callbacks()`, `callback_set()`, `mlr_callback_set`, `mlr_callback_set.checkpoint`, `mlr_callback_set.progress`, `mlr_context_torch`, `t_clbk()`, `torch_callback()`

Other Dictionary: `mlr3torch_losses`, `mlr3torch_optimizers`, `t_opt()`

Examples

```
mlr3torch_callbacks$get("checkpoint")  
# is the same as  
t_clbk("checkpoint")  
# convert to a data.table  
as.data.table(mlr3torch_callbacks)
```

mlr3torch_losses	<i>Loss Functions</i>
------------------	-----------------------

Description

Dictionary of torch loss descriptors. See `t_loss()` for conveniently retrieving a loss function. Can be converted to a `data.table` using `as.data.table`.

Usage

```
mlr3torch_losses
```

Format

An object of class `DictionaryMlr3torchLosses` (inherits from `Dictionary`, R6) of length 13.

Available Loss Functions

```
cross_entropy, l1, mse
```

See Also

Other Torch Descriptor: `TorchCallback`, `TorchDescriptor`, `TorchLoss`, `TorchOptimizer`, `as_torch_callbacks()`, `as_torch_loss()`, `as_torch_optimizer()`, `mlr3torch_optimizers`, `t_clbk()`, `t_loss()`, `t_opt()`

Other Dictionary: `mlr3torch_callbacks`, `mlr3torch_optimizers`, `t_opt()`

Examples

```
mlr3torch_losses$get("mse")  
# is equivalent to  
t_loss("mse")  
# convert to a data.table  
as.data.table(mlr3torch_losses)
```

mlr3torch_optimizers *Optimizers*

Description

Dictionary of torch optimizers. Use `t_opt` for conveniently retrieving optimizers. Can be converted to a `data.table` using `as.data.table`.

Usage

```
mlr3torch_optimizers
```

Format

An object of class `DictionaryMlr3torchOptimizers` (inherits from `Dictionary`, R6) of length 13.

Available Optimizers

adadelta, adagrad, adam, asgd, rmsprop, rprop, sgd

See Also

Other Torch Descriptor: `TorchCallback`, `TorchDescriptor`, `TorchLoss`, `TorchOptimizer`, `as_torch_callbacks()`, `as_torch_loss()`, `as_torch_optimizer()`, `mlr3torch_losses`, `t_clbk()`, `t_loss()`, `t_opt()`

Other Dictionary: `mlr3torch_callbacks`, `mlr3torch_losses`, `t_opt()`

Examples

```
mlr3torch_optimizers$get("adam")  
# is equivalent to  
t_opt("adam")  
# convert to a data.table  
as.data.table(mlr3torch_optimizers)
```

mlr_backends_lazy *Lazy Data Backend*

Description

This lazy data backend wraps a constructor that lazily creates another backend, e.g. by downloading (and caching) some data from the internet. This backend should be used, when some metadata of the backend is known in advance and should be accessible before downloading the actual data. When the backend is first constructed, it is verified that the provided metadata was correct, otherwise an informative error message is thrown. After the construction of the lazily constructed backend, calls like `$data()`, `$missings()`, `$distinct()`, or `$hash()` are redirected to it.

Information that is available before the backend is constructed is:

- `nrow` - The number of rows (set as the length of the rownames).
- `ncol` - The number of columns (provided via the `id` column of `col_info`).
- `colnames` - The column names.
- `rownames` - The row names.
- `col_info` - The column information, which can be obtained via `mlr3::col_info()`.

Beware that accessing the backend's hash also constructs the backend.

Note that while in most cases the data contains `lazy_tensor` columns, this is not necessary and the naming of this class has nothing to do with the `lazy_tensor` data type.

Important

When the constructor generates `factor()` variables it is important that the ordering of the levels in data corresponds to the ordering of the levels in the `col_info` argument.

Super class

`mlr3::DataBackend` -> `DataBackendLazy`

Active bindings

`backend` (`DataBackend`)

The wrapped backend that is lazily constructed when first accessed.

`nrow` (`integer(1)`)

Number of rows (observations).

`ncol` (`integer(1)`)

Number of columns (variables), including the primary key column.

`rownames` (`integer()`)

Returns vector of all distinct row identifiers, i.e. the contents of the primary key column.

`colnames` (`character()`)

Returns vector of all column names, including the primary key column.

`is_constructed` (`logical(1)`)

Whether the backend has already been constructed.

Methods

Public methods:

- [DataBackendLazy\\$new\(\)](#)
- [DataBackendLazy\\$data\(\)](#)
- [DataBackendLazy\\$head\(\)](#)
- [DataBackendLazy\\$distinct\(\)](#)
- [DataBackendLazy\\$missings\(\)](#)
- [DataBackendLazy\\$print\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
DataBackendLazy$new(constructor, rownames, col_info, primary_key, data_formats)
```

Arguments:

`constructor` (function)

A function with argument `backend` (the lazy backend), whose return value must be the actual backend. This function is called the first time the field `$backend` is accessed.

`rownames` (integer())

The row names. Must be a permutation of the rownames of the lazily constructed backend.

`col_info` ([data.table::data.table\(\)](#))

A `data.table` with columns `id`, `type` and `levels` containing the column `id`, `type` and `levels`. Note that the levels must be provided in the correct order.

`primary_key` (character(1))

Name of the primary key column.

`data_formats` (character())

Set of supported data formats. E.g. `"data.table"`. These must be a subset of the data formats of the lazily constructed backend.

Method `data()`: Returns a slice of the data in the specified format. The rows must be addressed as vector of primary key values, columns must be referred to via column names. Queries for rows with no matching row `id` and queries for columns with no matching column name are silently ignored. Rows are guaranteed to be returned in the same order as rows, columns may be returned in an arbitrary order. Duplicated row `ids` result in duplicated rows, duplicated column names lead to an exception.

Accessing the data triggers the construction of the backend.

Usage:

```
DataBackendLazy$data(rows, cols, data_format = "data.table")
```

Arguments:

`rows` (integer())

Row indices.

`cols` (character())

Column names.

`data_format` (character(1))

Desired data format, e.g. `"data.table"` or `"Matrix"`.

Method `head()`: Retrieve the first `n` rows. This triggers the construction of the backend.

Usage:

```
DataBackendLazy$head(n = 6L)
```

Arguments:

`n` (`integer(1)`)
Number of rows.

Returns: `data.table::data.table()` of the first `n` rows.

Method `distinct()`: Returns a named list of vectors of distinct values for each column specified. If `na_rm` is `TRUE`, missing values are removed from the returned vectors of distinct values. Non-existing rows and columns are silently ignored.

This triggers the construction of the backend.

Usage:

```
DataBackendLazy$distinct(rows, cols, na_rm = TRUE)
```

Arguments:

`rows` (`integer()`)
Row indices.
`cols` (`character()`)
Column names.
`na_rm` (`logical(1)`)
Whether to remove NAs or not.

Returns: Named `list()` of distinct values.

Method `missings()`: Returns the number of missing values per column in the specified slice of data. Non-existing rows and columns are silently ignored.

This triggers the construction of the backend.

Usage:

```
DataBackendLazy$missings(rows, cols)
```

Arguments:

`rows` (`integer()`)
Row indices.
`cols` (`character()`)
Column names.

Returns: Total of missing values per column (named `numeric()`).

Method `print()`: Printer.

Usage:

```
DataBackendLazy$print()
```

Examples

```
# We first define a backend constructor
constructor = function(backend) {
  cat("Data is constructed!\n")
  DataBackendDataTable$new(
```

```

    data.table(x = rnorm(10), y = rnorm(10), row_id = 1:10),
    primary_key = "row_id"
  )
}

# to wrap this backend constructor in a lazy backend, we need to provide the correct metadata for it
column_info = data.table(
  id = c("x", "y", "row_id"),
  type = c("numeric", "numeric", "integer"),
  levels = list(NULL, NULL, NULL)
)
backend_lazy = DataBackendLazy$new(
  constructor = constructor,
  rownames = 1:10,
  col_info = column_info,
  data_formats = "data.table",
  primary_key = "row_id"
)

# Note that the constructor is not called for the calls below
# as they can be read from the metadata
backend_lazy$nrow
backend_lazy$rownames
backend_lazy$ncol
backend_lazy$colnames
col_info(backend_lazy)

# Only now the backend is constructed
backend_lazy$data(1, "x")
# Is the same as:
backend_lazy$backend$data(1, "x")

```

mlr_callback_set

Base Class for Callbacks

Description

Base class from which callbacks should inherit (see section *Inheriting*). A callback set is a collection of functions that are executed at different stages of the training loop. They can be used to gain more control over the training process of a neural network without having to write everything from scratch.

When used in a torch learner, the `CallbackSet` is wrapped in a `TorchCallback`. The latter's parameter set represents the arguments of the `CallbackSet`'s `$initialize()` method.

Inheriting

For each available stage (see section *Stages*) a public method `$on_<stage>()` can be defined. The evaluation context (a `ContextTorch`) can be accessed via `self$ctx`, which contains the current

state of the training loop. This context is assigned at the beginning of the training loop and removed afterwards. Different stages of a callback can communicate with each other by assigning values to `$self`.

State: To be able to store information in the `$model` slot of a `LearnerTorch`, callbacks support a state API. You can overload the `$state_dict()` public method to define what will be stored in `learner$model$callbacks$<id>` after training finishes. This then also requires to implement a `$load_state_dict(state_dict)` method that defines how to load a previously saved callback state into a different callback. Note that the `$state_dict()` should not include the parameter values that were used to initialize the callback.

For creating custom callbacks, the function `torch_callback()` is recommended, which creates a `CallbackSet` and then wraps it in a `TorchCallback`. To create a `CallbackSet` the convenience function `callback_set()` can be used. These functions perform checks such as that the stages are not accidentally misspelled.

Stages

- `begin` :: Run before the training loop begins.
- `epoch_begin` :: Run he beginning of each epoch.
- `batch_begin` :: Run before the forward call.
- `after_backward` :: Run after the backward call.
- `batch_end` :: Run after the optimizer step.
- `batch_valid_begin` :: Run before the forward call in the validation loop.
- `batch_valid_end` :: Run after the forward call in the validation loop.
- `valid_end` :: Run at the end of validation.
- `epoch_end` :: Run at the end of each epoch.
- `end` :: Run after last epoch.
- `exit` :: Run at last, using `on.exit()`.

Terminate Training

If training is to be stopped, it is possible to set the field `$terminate` of `ContextTorch`. At the end of every epoch this field is checked and if it is `TRUE`, training stops. This can for example be used to implement custom early stopping.

Public fields

`ctx` (`ContextTorch` or `NULL`)

The evaluation context for the callback. This field should always be `NULL` except during the `$train()` call of the torch learner.

Active bindings

`stages` (`character()`)

The active stages of this callback set.

Methods

Public methods:

- [CallbackSet#print\(\)](#)
- [CallbackSet\\$state_dict\(\)](#)
- [CallbackSet\\$load_state_dict\(\)](#)
- [CallbackSet\\$clone\(\)](#)

Method `print()`: Prints the object.

Usage:

```
CallbackSet#print(...)
```

Arguments:

... (any)
Currently unused.

Method `state_dict()`: Returns information that is kept in the the [LearnerTorch](#)'s state after training. This information should be loadable into the callback using `$load_state_dict()` to be able to continue training. This returns NULL by default.

Usage:

```
CallbackSet$state_dict()
```

Method `load_state_dict()`: Loads the state dict into the callback to continue training.

Usage:

```
CallbackSet$load_state_dict(state_dict)
```

Arguments:

state_dict (any)
The state dict as retrieved via `$state_dict()`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CallbackSet$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Callback: [TorchCallback](#), [as_torch_callback\(\)](#), [as_torch_callbacks\(\)](#), [callback_set\(\)](#), [mlr3torch_callbacks](#), [mlr_callback_set.checkpoint](#), [mlr_callback_set.progress](#), [mlr_context_torch](#), [t_clbk\(\)](#), [torch_callback\(\)](#)

```
mlr_callback_set.checkpoint
Checkpoint Callback
```

Description

Saves the optimizer and network states during training. The final network and optimizer are always stored.

Details

Saving the learner itself in the callback with a trained model is impossible, as the model slot is set *after* the last callback step is executed.

Super class

```
mlr3torch::CallbackSet -> CallbackSetCheckpoint
```

Methods

Public methods:

- [CallbackSetCheckpoint\\$new\(\)](#)
- [CallbackSetCheckpoint\\$on_epoch_end\(\)](#)
- [CallbackSetCheckpoint\\$on_batch_end\(\)](#)
- [CallbackSetCheckpoint\\$on_exit\(\)](#)
- [CallbackSetCheckpoint\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
CallbackSetCheckpoint$new(path, freq, freq_type = "epoch")
```

Arguments:

`path` (character(1))

The path to a folder where the models are saved.

`freq` (integer(1))

The frequency how often the model is saved. Frequency is either per step or epoch, which can be configured through the `freq_type` parameter.

`freq_type` (character(1))

Can be either "epoch" (default) or "step".

Method `on_epoch_end()`: Saves the network and optimizer state dict. Does nothing if `freq_type` or `freq` are not met.

Usage:

```
CallbackSetCheckpoint$on_epoch_end()
```

Method `on_batch_end()`: Saves the selected objects defined in `save`. Does nothing if `freq_type` or `freq` are not met.

Usage:

`CallbackSetCheckpoint$on_batch_end()`

Method `on_exit()`: Saves the learner.

Usage:

`CallbackSetCheckpoint$on_exit()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`CallbackSetCheckpoint$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Callback: [TorchCallback](#), [as_torch_callback\(\)](#), [as_torch_callbacks\(\)](#), [callback_set\(\)](#), [mlr3torch_callbacks](#), [mlr_callback_set](#), [mlr_callback_set.progress](#), [mlr_context_torch](#), [t_clbk\(\)](#), [torch_callback\(\)](#)

mlr_callback_set.history

History Callback

Description

Saves the training and validation history during training. The history is saved as a `data.table` in the `$train` and `$valid` slots. The first column is always `epoch`.

Super class

`mlr3torch::CallbackSet` -> `CallbackSetHistory`

Methods

Public methods:

- `CallbackSetHistory$on_begin()`
- `CallbackSetHistory$state_dict()`
- `CallbackSetHistory$load_state_dict()`
- `CallbackSetHistory$on_before_valid()`
- `CallbackSetHistory$on_epoch_end()`
- `CallbackSetHistory$clone()`

Method `on_begin()`: Initializes lists where the train and validation metrics are stored.

Usage:

CallbackSetHistory\$on_begin()

Method state_dict(): Converts the lists to data.tables.

Usage:

CallbackSetHistory\$state_dict()

Method load_state_dict(): Sets the field \$train and \$valid to those contained in the state dict.

Usage:

CallbackSetHistory\$load_state_dict(state_dict)

Arguments:

state_dict (callback_state_history)
The state dict as retrieved via \$state_dict().

Method on_before_valid(): Add the latest training scores to the history.

Usage:

CallbackSetHistory\$on_before_valid()

Method on_epoch_end(): Add the latest validation scores to the history.

Usage:

CallbackSetHistory\$on_epoch_end()

Method clone(): The objects of this class are cloneable with this method.

Usage:

CallbackSetHistory\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

mlr_callback_set.progress

Progress Callback

Description

Prints a progress bar and the metrics for training and validation.

Super class

[mlr3torch::CallbackSet](#) -> CallbackSetProgress

Methods

Public methods:

- [CallbackSetProgress\\$on_epoch_begin\(\)](#)
- [CallbackSetProgress\\$on_batch_end\(\)](#)
- [CallbackSetProgress\\$on_before_valid\(\)](#)
- [CallbackSetProgress\\$on_batch_valid_end\(\)](#)
- [CallbackSetProgress\\$on_epoch_end\(\)](#)
- [CallbackSetProgress\\$clone\(\)](#)

Method `on_epoch_begin()`: Initializes the progress bar for training.

Usage:

```
CallbackSetProgress$on_epoch_begin()
```

Method `on_batch_end()`: Increments the training progress bar.

Usage:

```
CallbackSetProgress$on_batch_end()
```

Method `on_before_valid()`: Creates the progress bar for validation.

Usage:

```
CallbackSetProgress$on_before_valid()
```

Method `on_batch_valid_end()`: Increments the validation progress bar.

Usage:

```
CallbackSetProgress$on_batch_valid_end()
```

Method `on_epoch_end()`: Prints a summary of the training and validation process.

Usage:

```
CallbackSetProgress$on_epoch_end()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
CallbackSetProgress$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Callback: [TorchCallback](#), [as_torch_callback\(\)](#), [as_torch_callbacks\(\)](#), [callback_set\(\)](#), [mlr3torch_callbacks](#), [mlr_callback_set](#), [mlr_callback_set.checkpoint](#), [mlr_context_torch](#), [t_clbk\(\)](#), [torch_callback\(\)](#)

mlr_context_torch *Context for Torch Learner*

Description

Context for training a torch learner. This is the - mostly read-only - information callbacks have access to through the argument ctx. For more information on callbacks, see [CallbackSet](#).

Public fields

- learner ([Learner](#))
The torch learner.
- task_train ([Task](#))
The training task.
- task_valid ([Task](#) or NULL)
The validation task.
- loader_train ([torch::data_loader](#))
The data loader for training.
- loader_valid ([torch::data_loader](#))
The data loader for validation.
- measures_train (list() of [Measures](#))
Measures used for training.
- measures_valid (list() of [Measures](#))
Measures used for validation.
- network ([torch::nn_module](#))
The torch network.
- optimizer ([torch::optimizer](#))
The optimizer.
- loss_fn ([torch::nn_module](#))
The loss function.
- total_epochs (integer(1))
The total number of epochs the learner is trained for.
- last_scores_train (named list() or NULL)
The scores from the last training batch. Names are the ids of the training measures. If [LearnerTorch](#) sets eval_freq different from 1, this is NULL in all epochs that don't evaluate the model.
- last_scores_valid (list())
The scores from the last validation batch. Names are the ids of the validation measures. If [LearnerTorch](#) sets eval_freq different from 1, this is NULL in all epochs that don't evaluate the model.
- epoch (integer(1))
The current epoch.

`step` (integer(1))
 The current iteration.

`prediction_encoder` (function())
 The learner's prediction encoder.

`batch` (named list() of torch_tensors)
 The current batch.

`terminate` (logical(1))
 If this field is set to TRUE at the end of an epoch, training stops.

Methods

Public methods:

- [ContextTorch\\$new\(\)](#)
- [ContextTorch\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
ContextTorch$new(
  learner,
  task_train,
  task_valid = NULL,
  loader_train,
  loader_valid = NULL,
  measures_train = NULL,
  measures_valid = NULL,
  network,
  optimizer,
  loss_fn,
  total_epochs,
  prediction_encoder,
  eval_freq = 1L
)
```

Arguments:

`learner` ([Learner](#))
 The torch learner.

`task_train` ([Task](#))
 The training task.

`task_valid` ([Task](#) or NULL)
 The validation task.

`loader_train` ([torch::data_loader](#))
 The data loader for training.

`loader_valid` ([torch::data_loader](#) or NULL)
 The data loader for validation.

`measures_train` (list() of [Measures](#) or NULL)
 Measures used for training. Default is NULL.

`measures_valid` (list() of [Measures](#) or NULL)
 Measures used for validation.
`network` ([torch::nn_module](#))
 The torch network.
`optimizer` ([torch::optimizer](#))
 The optimizer.
`loss_fn` ([torch::nn_module](#))
 The loss function.
`total_epochs` ([integer\(1\)](#))
 The total number of epochs the learner is trained for.
`prediction_encoder` ([function\(\)](#))
 The learner's prediction encoder.
`eval_freq` ([integer\(1\)](#))
 The evaluation frequency.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
ContextTorch$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Callback: [TorchCallback](#), [as_torch_callback\(\)](#), [as_torch_callbacks\(\)](#), [callback_set\(\)](#), [mlr3torch_callbacks](#), [mlr_callback_set](#), [mlr_callback_set.checkpoint](#), [mlr_callback_set.progress](#), [t_clbk\(\)](#), [torch_callback\(\)](#)

mlr_learners.mlp

My Little Pony

Description

Fully connected feed forward network with dropout after each activation function. The features can either be a single [lazy_tensor](#) or one or more numeric columns (but not both).

Dictionary

This [Learner](#) can be instantiated using the sugar function [lrn\(\)](#):

```
lrn("classif.mlp", ...)
lrn("regr.mlp", ...)
```

Properties

- Supported task types: 'classif', 'regr'
- Predict Types:
 - classif: 'response', 'prob'
 - regr: 'response'
- Feature Types: "integer", "numeric", "lazy_tensor"
- Required Packages: **mlr3**, **mlr3torch**, **torch**

Parameters

Parameters from [LearnerTorch](#), as well as:

- `activation` :: [nn_module]
The activation function. Is initialized to `nn_relu`.
- `activation_args` :: named list()
A named list with initialization arguments for the activation function. This is initialized to an empty list.
- `neurons` :: integer()
The number of neurons per hidden layer. By default there is no hidden layer. Setting this to `c(10, 20)` would have a the first hidden layer with 10 neurons and the second with 20.
- `p` :: numeric(1)
The dropout probability. Is initialized to 0.5.
- `shape` :: integer() or NULL
The input shape of length 2, e.g. `c(NA, 5)`. Only needs to be present when there is a lazy tensor input with unknown shape (NULL). Otherwise the input shape is inferred from the number of numeric features.

Super classes

`mlr3::Learner` -> `mlr3torch::LearnerTorch` -> `LearnerTorchMLP`

Methods

Public methods:

- `LearnerTorchMLP$new()`
- `LearnerTorchMLP$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerTorchMLP$new(
  task_type,
  optimizer = NULL,
  loss = NULL,
  callbacks = list()
)
```

Arguments:

task_type (character(1))

The task type, either "classif" or "regr".

optimizer ([TorchOptimizer](#))

The optimizer to use for training. Per default, *adam* is used.

loss ([TorchLoss](#))

The loss used to train the network. Per default, *mse* is used for regression and *cross_entropy* for classification.

callbacks (list() of [TorchCallbacks](#))

The callbacks. Must have unique ids.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
LearnerTorchMLP$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Learner: [mlr_learners.tab_resnet](#), [mlr_learners.torch_featureless](#), [mlr_learners_torch](#), [mlr_learners_torch_image](#), [mlr_learners_torch_model](#)

Examples

```
# Define the Learner and set parameter values
learner = lrn("classif.mlp")
learner$param_set$set_values(
  epochs = 1, batch_size = 16, device = "cpu",
  neurons = 10
)

# Define a Task
task = tsk("iris")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners.tab_resnet
Tabular ResNet

Description

Tabular resnet.

Dictionary

This [Learner](#) can be instantiated using the sugar function `lrn()`:

```
lrn("classif.tab_resnet", ...)  
lrn("regr.tab_resnet", ...)
```

Properties

- Supported task types: 'classif', 'regr'
- Predict Types:
 - classif: 'response', 'prob'
 - regr: 'response'
- Feature Types: "integer", "numeric"
- Required Packages: **mlr3**, **mlr3torch**, **torch**

Parameters

Parameters from [LearnerTorch](#), as well as:

- `n_blocks :: integer(1)`
The number of blocks.
- `d_block :: integer(1)`
The input and output dimension of a block.
- `d_hidden :: integer(1)`
The latent dimension of a block.
- `d_hidden_multiplier :: integer(1)`
Alternative way to specify the latent dimension as `d_block * d_hidden_multiplier`.
- `dropout1 :: numeric(1)`
First dropout ratio.
- `dropout2 :: numeric(1)`
Second dropout ratio.

Super classes

```
mlr3::Learner -> mlr3torch::LearnerTorch -> LearnerTorchTabResNet
```

Methods

Public methods:

- [LearnerTorchTabResNet\\$new\(\)](#)
- [LearnerTorchTabResNet\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerTorchTabResNet$new(
  task_type,
  optimizer = NULL,
  loss = NULL,
  callbacks = list()
)
```

Arguments:

`task_type` (character(1))

The task type, either "classif" or "regr".

`optimizer` ([TorchOptimizer](#))

The optimizer to use for training. Per default, *adam* is used.

`loss` ([TorchLoss](#))

The loss used to train the network. Per default, *mse* is used for regression and *cross_entropy* for classification.

`callbacks` (list() of [TorchCallbacks](#))

The callbacks. Must have unique ids.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerTorchTabResNet$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

References

Gorishniy Y, Rubachev I, Khrukov V, Babenko A (2021). "Revisiting Deep Learning for Tabular Data." *arXiv*, **2106.11959**.

See Also

Other Learner: [mlr_learners.mlp](#), [mlr_learners.torch_featureless](#), [mlr_learners_torch](#), [mlr_learners_torch_image](#), [mlr_learners_torch_model](#)

Examples

```
# Define the Learner and set parameter values
learner = lrn("classif.tab_resnet")
learner$param_set$set_values(
  epochs = 1, batch_size = 16, device = "cpu",
```

```
n_blocks = 2, d_block = 10, d_hidden = 20, dropout1 = 0.3, dropout2 = 0.3
)

# Define a Task
task = tsk("iris")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)

# Score the predictions
predictions$score()
```

mlr_learners.torchvision

AlexNet Image Classifier

Description

Classic image classification networks from torchvision.

Parameters

Parameters from [LearnerTorchImage](#) and

- `pretrained` :: `logical(1)`
Whether to use the pretrained model. The final linear layer will be replaced with a new `nn_linear` with the number of classes inferred from the [Task](#).

Properties

- Supported task types: "classif"
- Predict Types: "response" and "prob"
- Feature Types: "lazy_tensor"
- Required packages: "mlr3torch", "torch", "torchvision"

Super classes

[mlr3::Learner](#) -> [mlr3torch::LearnerTorch](#) -> [mlr3torch::LearnerTorchImage](#) -> [LearnerTorchVision](#)

Methods

Public methods:

- [LearnerTorchVision\\$new\(\)](#)
- [LearnerTorchVision\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerTorchVision$new(
  name,
  module_generator,
  label,
  optimizer = NULL,
  loss = NULL,
  callbacks = list()
)
```

Arguments:

`name` (`character(1)`)

The name of the network.

`module_generator` (`function(pretrained, num_classes)`)

Function that generates the network.

`label` (`character(1)`)

The label of the network. #' @references Krizhevsky, Alex, Sutskever, Ilya, Hinton, E. G (2017). "Imagenet classification with deep convolutional neural networks." *Communications of the ACM*, **60**(6), 84–90. Sandler, Mark, Howard, Andrew, Zhu, Menglong, Zhmoginov, Andrey, Chen, Liang-Chieh (2018). "Mobilenetv2: Inverted residuals and linear bottlenecks." In *Proceedings of the IEEE conference on computer vision and pattern recognition*, 4510–4520. He, Kaiming, Zhang, Xiangyu, Ren, Shaoqing, Sun, Jian (2016). "Deep residual learning for image recognition ." In *Proceedings of the IEEE conference on computer vision and pattern recognition* , 770–778 . Simonyan, Karen, Zisserman, Andrew (2014). "Very deep convolutional networks for large-scale image recognition." *arXiv preprint arXiv:1409.1556*.

`optimizer` ([TorchOptimizer](#))

The optimizer to use for training. Per default, *adam* is used.

`loss` ([TorchLoss](#))

The loss used to train the network. Per default, *mse* is used for regression and *cross_entropy* for classification.

`callbacks` (`list()` of [TorchCallbacks](#))

The callbacks. Must have unique ids.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerTorchVision$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

mlr_learners.torch_featureless
Featureless Torch Learner

Description

Featureless torch learner. Output is a constant weight that is learned during training. For classification, this should (asymptotically) result in a majority class prediction when using the standard cross-entropy loss. For regression, this should result in the median for L1 loss and in the mean for L2 loss.

Dictionary

This [Learner](#) can be instantiated using the sugar function `lrn()`:

```
lrn("classif.torch_featureless", ...)  
lrn("regr.torch_featureless", ...)
```

Properties

- Supported task types: 'classif', 'regr'
- Predict Types:
 - classif: 'response', 'prob'
 - regr: 'response'
- Feature Types: "logical", "integer", "numeric", "character", "factor", "ordered", "POSIXct", "lazy_tensor"
- Required Packages: **mlr3**, **mlr3torch**, **torch**

Parameters

Only those from [LearnerTorch](#).

Super classes

```
mlr3::Learner -> mlr3torch::LearnerTorch -> LearnerTorchFeatureless
```

Methods

Public methods:

- [LearnerTorchFeatureless\\$new\(\)](#)
- [LearnerTorchFeatureless\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerTorchFeatureless$new(
  task_type,
  optimizer = NULL,
  loss = NULL,
  callbacks = list()
)
```

Arguments:

task_type (character(1))

The task type, either "classif" or "regr".

optimizer ([TorchOptimizer](#))

The optimizer to use for training. Per default, *adam* is used.

loss ([TorchLoss](#))

The loss used to train the network. Per default, *mse* is used for regression and *cross_entropy* for classification.

callbacks (list() of [TorchCallbacks](#))

The callbacks. Must have unique ids.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
LearnerTorchFeatureless$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Learner: [mlr_learners.mlp](#), [mlr_learners.tab_resnet](#), [mlr_learners.torch](#), [mlr_learners.torch_image](#), [mlr_learners.torch_model](#)

Examples

```
# Define the Learner and set parameter values
learner = lrn("classif.torch_featureless")
learner$param_set$set_values(
  epochs = 1, batch_size = 16, device = "cpu"
)

# Define a Task
task = tsk("iris")

# Create train and test set
ids = partition(task)

# Train the learner on the training ids
learner$train(task, row_ids = ids$train)

# Make predictions for the test rows
predictions = learner$predict(task, row_ids = ids$test)
```

```
# Score the predictions
predictions$score()
```

mlr_learners_torch *Base Class for Torch Learners*

Description

This base class provides the basic functionality for training and prediction of a neural network. All torch learners should inherit from this class.

Validation

To specify the validation data, you can set the `$validate` field of the Learner, which can be set to:

- `NULL`: no validation
- `ratio`: only proportion `1 - ratio` of the task is used for training and `ratio` is used for validation.
- `"test"` means that the `"test"` task of a resampling is used and is not possible when calling `$train()` manually.
- `"predefined"`: This will use the predefined `$internal_valid_task` of a `mlr3::Task`, which can e.g. be created using the `$divide()` method of `Task`.

This validation data can also be used for early stopping, see the description of the Learner's parameters.

Saving a Learner

In order to save a `LearnerTorch` for later usage, it is necessary to call the `$marshal()` method on the Learner before writing it to disk, as the object will otherwise not be saved correctly. After loading a marshaled `LearnerTorch` into R again, you then need to call `$unmarshal()` to transform it into a useable state.

Early Stopping and Tuning

In order to prevent overfitting, the `LearnerTorch` class allows to use early stopping via the `patience` and `min_delta` parameters, see the Learner's parameters. When tuning a `LearnerTorch` it is also possible to combine the explicit tuning via `mlr3tuning` and the `LearnerTorch`'s internal tuning of the epochs via early stopping. To do so, you just need to include `epochs = to_tune(upper = <upper>, internal = TRUE)` in the search space, where `<upper>` is the maximally allowed number of epochs, and configure the early stopping.

Model

The Model is a list of class "learner_torch_model" with the following elements:

- network :: The trained [network](#).
- optimizer :: The `$state_dict()` [optimizer](#) used to train the network.
- loss_fn :: The `$state_dict()` of the [loss](#) used to train the network.
- callbacks :: The [callbacks](#) used to train the network.
- seed :: The seed that was / is used for training and prediction.
- epochs :: How many epochs the model was trained for (early stopping).
- task_col_info :: A `data.table()` containing information about the train-task.

Parameters

General:

The parameters of the optimizer, loss and callbacks, prefixed with "opt.", "loss." and "cb.<callback id>." respectively, as well as:

- epochs :: `integer(1)`
The number of epochs.
- device :: `character(1)`
The device. One of "auto", "cpu", or "cuda" or other values defined in `mlr_reflections$torch$devices`. The value is initialized to "auto", which will select "cuda" if possible, then try "mps" and otherwise fall back to "cpu".
- num_threads :: `integer(1)`
The number of threads for intraop parallelization (if device is "cpu"). This value is initialized to 1.
- seed :: `integer(1)` or "random"
The seed that is used during training and prediction. This value is initialized to "random", which means that a random seed will be sampled at the beginning of the training phase. This seed (either set or randomly sampled) is available via `$model$seed` after training and used during prediction. Note that by setting the seed during the training phase this will mean that by default (i.e. when seed is "random"), clones of the learner will use a different seed.

Evaluation:

- measures_train :: [Measure](#) or `list()` of [Measures](#).
Measures to be evaluated during training.
- measures_valid :: [Measure](#) or `list()` of [Measures](#).
Measures to be evaluated during validation.
- eval_freq :: `integer(1)`
How often the train / validation predictions are evaluated using `measures_train` / `measures_valid`. This is initialized to 1. Note that the final model is always evaluated.

Early Stopping:

- `patience :: integer(1)`
This activates early stopping using the validation scores. If the performance of a model does not improve for `patience` evaluation steps, training is ended. Note that the final model is stored in the learner, not the best model. This is initialized to `0`, which means no early stopping. The first entry from `measures_valid` is used as the metric. This also requires to specify the `svalidate` field of the Learner, as well as `measures_valid`.
- `min_delta :: double(1)`
The minimum improvement threshold (`>`) for early stopping. Is initialized to `0`.

Dataloader:

- `batch_size :: integer(1)`
The batch size (required).
- `shuffle :: logical(1)`
Whether to shuffle the instances in the dataset. Default is `FALSE`. This does not impact validation.
- `sampler :: torch::sampler`
Object that defines how the dataloader draw samples.
- `batch_sampler :: torch::sampler`
Object that defines how the dataloader draws batches.
- `num_workers :: integer(1)`
The number of workers for data loading (batches are loaded in parallel). The default is `0`, which means that data will be loaded in the main process.
- `collate_fn :: function`
How to merge a list of samples to form a batch.
- `pin_memory :: logical(1)`
Whether the dataloader copies tensors into CUDA pinned memory before returning them.
- `drop_last :: logical(1)`
Whether to drop the last training batch in each epoch during training. Default is `FALSE`.
- `timeout :: numeric(1)`
The timeout value for collecting a batch from workers. Negative values mean no timeout and the default is `-1`.
- `worker_init_fn :: function(id)`
A function that receives the worker id (in `[1, num_workers]`) and is executed after seeding on the worker but before data loading.
- `worker_globals :: list() | character()`
When loading data in parallel, this allows to export globals to the workers. If this is a character vector, the objects in the global environment with those names are copied to the workers.
- `worker_packages :: character()`
Which packages to load on the workers.

Also see `torch::dataloader` for more information.

Inheriting

There are no separate classes for classification and regression to inherit from. Instead, the `task_type` must be specified as a construction argument. Currently, only classification and regression are supported.

When inheriting from this class, one should overload two private methods:

- `.network(task, param_vals)`
(`Task`, `list()`) -> `nn_module`
Construct a `torch::nn_module` object for the given task and parameter values, i.e. the neural network that is trained by the learner. For classification, the output of this network are expected to be the scores before the application of the final softmax layer.
- `.dataset(task, param_vals)`
(`Task`, `list()`) -> `torch::dataset`
Create the dataset for the task. Must respect the parameter value of the device. Moreover, one needs to pay attention respect the row ids of the provided task.

It is also possible to overwrite the private `.dataloader()` method instead of the `.dataset()` method. Per default, a dataloader is constructed using the output from the `.dataset()` method. However, this should respect the dataloader parameters from the `ParamSet`.

- `.dataloader(task, param_vals)`
(`Task`, `list()`) -> `torch::dataloader`
Create a dataloader from the task. Needs to respect at least `batch_size` and `shuffle` (otherwise predictions can be permuted).

To change the predict types, the private `.encode_prediction()` method can be overwritten:

- `.encode_prediction(predict_tensor, task, param_vals)`
(`torch_tensor`, `Task`, `list()`) -> `list()`
Take in the raw predictions from `self$network` (`predict_tensor`) and encode them into a format that can be converted to valid `mlr3` predictions using `mlr3::as_prediction_data()`. This method must take `self$predict_type` into account.

While it is possible to add parameters by specifying the `param_set` construction argument, it is currently not possible to remove existing parameters, i.e. those listed in section *Parameters*. None of the parameters provided in `param_set` can have an id that starts with "loss.", "opt.", or "cb.", as these are preserved for the dynamically constructed parameters of the optimizer, the loss function, and the callbacks.

To perform additional input checks on the task, the private `.verify_train_task(task, param_vals)` and `.verify_predict_task(task, param_vals)` can be overwritten.

For learners that have other construction arguments that should change the hash of a learner, it is required to implement the private `$.additional_phash_input()`.

Super class

`mlr3::Learner` -> `LearnerTorch`

Active bindings

- `validate` How to construct the internal validation data. This parameter can be either `NULL`, a ratio in $(0, 1)$, "test", or "predefined".
- `loss` ([TorchLoss](#))
The torch loss.
- `optimizer` ([TorchOptimizer](#))
The torch optimizer.
- `callbacks` (`list()` of [TorchCallbacks](#))
List of torch callbacks. The ids will be set as the names.
- `internal_valid_scores` Retrieves the internal validation scores as a named `list()`. Specify the `$validate` field and the `measures_valid` parameter to configure this. Returns `NULL` if learner is not trained yet.
- `internal_tuned_values` When early stopping is activate, this returns a named list with the early-stopped epochs, otherwise an empty list is returned. Returns `NULL` if learner is not trained yet.
- `marshaled` (`logical(1)`)
Whether the learner is marshaled.
- `network` ([nn_module\(\)](#))
Shortcut for `learner$model$network`.
- `param_set` ([ParamSet](#))
The parameter set
- `hash` (`character(1)`)
Hash (unique identifier) for this object.
- `phash` (`character(1)`)
Hash (unique identifier) for this partial object, excluding some components which are varied systematically during tuning (parameter values).

Methods**Public methods:**

- [LearnerTorch\\$new\(\)](#)
- [LearnerTorch\\$format\(\)](#)
- [LearnerTorch\\$print\(\)](#)
- [LearnerTorch\\$marshal\(\)](#)
- [LearnerTorch\\$unmarshal\(\)](#)
- [LearnerTorch\\$dataset\(\)](#)
- [LearnerTorch\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerTorch$new(
  id,
  task_type,
  param_set,
```

```

properties,
man,
label,
feature_types,
optimizer = NULL,
loss = NULL,
packages = character(),
predict_types = NULL,
callbacks = list()
)

```

Arguments:

id (character(1))

The id for of the new object.

task_type (character(1))

The task type.

param_set ([ParamSet](#) or `alist()`)

Either a parameter set, or an `alist()` containing different values of self, e.g. `alist(private$.param_set1, private$.param_set2)`, from which a [ParamSet](#) collection should be created.

properties (character())

The properties of the object. See [mlr_reflections\\$learner_properties](#) for available values.

man (character(1))

String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

label (character(1))

Label for the new instance.

feature_types (character())

The feature types. See [mlr_reflections\\$task_feature_types](#) for available values, Additionally, "lazy_tensor" is supported.

optimizer (NULL or [TorchOptimizer](#))

The optimizer to use for training. Defaults to adam.

loss (NULL or [TorchLoss](#))

The loss to use for training. Defaults to MSE for regression and cross entropy for classification.

packages (character())

The R packages this object depends on.

predict_types (character())

The predict types. See [mlr_reflections\\$learner_predict_types](#) for available values.

For regression, the default is "response". For classification, this defaults to "response" and "prob". To deviate from the defaults, it is necessary to overwrite the private `$.encode_prediction()` method, see section *Inheriting*.

callbacks (`list()` of [TorchCallbacks](#))

The callbacks to use for training. Defaults to an empty `list()`, i.e. no callbacks.

Method `format()`: Helper for print outputs.

Usage:

LearnerTorch\$format(...)

Arguments:

... (ignored).

Method print(): Prints the object.

Usage:

LearnerTorch\$print(...)

Arguments:

... (any)

Currently unused.

Method marshal(): Marshal the learner.

Usage:

LearnerTorch\$marshal(...)

Arguments:

... (any)

Additional parameters.

Returns: self

Method unmarshal(): Unmarshal the learner.

Usage:

LearnerTorch\$unmarshal(...)

Arguments:

... (any)

Additional parameters.

Returns: self

Method dataset(): Create the dataset for a task.

Usage:

LearnerTorch\$dataset(task)

Arguments:

task [Task](#)

The task

Returns: [dataset](#)

Method clone(): The objects of this class are cloneable with this method.

Usage:

LearnerTorch\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

See Also

Other Learner: [mlr_learners.mlp](#), [mlr_learners.tab_resnet](#), [mlr_learners.torch_featureless](#), [mlr_learners_torch_image](#), [mlr_learners_torch_model](#)

```
mlr_learners_torch_image
  Image Learner
```

Description

Base Class for Image Learners. The features are assumed to be a single [lazy_tensor](#) column in RGB format.

Parameters

Parameters include those inherited from [LearnerTorch](#) and the `param_set` construction argument.

Super classes

[mlr3::Learner](#) -> [mlr3torch::LearnerTorch](#) -> [LearnerTorchImage](#)

Methods

Public methods:

- [LearnerTorchImage\\$new\(\)](#)
- [LearnerTorchImage\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerTorchImage$new(
  id,
  task_type,
  param_set = ps(),
  label,
  optimizer = NULL,
  loss = NULL,
  callbacks = list(),
  packages = c("torchvision", "magick"),
  man,
  properties = NULL,
  predict_types = NULL
)
```

Arguments:

`id` (`character(1)`)
The id for of the new object.

`task_type` (`character(1)`)
The task type.

`param_set` ([ParamSet](#))
The parameter set.

label (character(1))
 Label for the new instance.

optimizer ([TorchOptimizer](#))
 The torch optimizer.

loss ([TorchLoss](#))
 The loss to use for training.

callbacks (list() of [TorchCallbacks](#))
 The callbacks used during training. Must have unique ids. They are executed in the order in which they are provided

packages (character())
 The R packages this object depends on.

man (character(1))
 String in the format [pkg]::[topic] pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

properties (character())
 The properties of the object. See [mlr_reflections\\$learner_properties](#) for available values.

predict_types (character())
 The predict types. See [mlr_reflections\\$learner_predict_types](#) for available values.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerTorchImage$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Learner: [mlr_learners.mlp](#), [mlr_learners.tab_resnet](#), [mlr_learners.torch_featureless](#), [mlr_learners_torch](#), [mlr_learners_torch_model](#)

mlr_learners_torch_model

Learner Torch Model

Description

Create a torch learner from an instantiated `nn_module()`. For classification, the output of the network must be the scores (before the softmax).

Parameters

See [LearnerTorch](#)

Super classes

`mlr3::Learner` -> `mlr3torch::LearnerTorch` -> `LearnerTorchModel`

Active bindings

`network_stored` (`nn_module` or `NULL`)

The network that will be trained. After calling `$train()`, this is `NULL`.

`ingress_tokens` (named `list()` with `TorchIngressToken` or `NULL`)

The ingress tokens. Must be non-`NULL` when calling `$train()`.

Methods**Public methods:**

- `LearnerTorchModel$new()`
- `LearnerTorchModel$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerTorchModel$new(
  network = NULL,
  ingress_tokens = NULL,
  task_type,
  properties = NULL,
  optimizer = NULL,
  loss = NULL,
  callbacks = list(),
  packages = character(0),
  feature_types = NULL
)
```

Arguments:

`network` (`nn_module`)

An instantiated `nn_module`. Is not cloned during construction. For classification, outputs must be the scores (before the softmax).

`ingress_tokens` (`list()` of `TorchIngressToken()`)

A list with ingress tokens that defines how the dataloader will be defined.

`task_type` (`character(1)`)

The task type.

`properties` (`NULL` or `character()`)

The properties of the learner. Defaults to all available properties for the given task type.

`optimizer` (`TorchOptimizer`)

The torch optimizer.

`loss` (`TorchLoss`)

The loss to use for training.

`callbacks` (`list()` of `TorchCallbacks`)

The callbacks used during training. Must have unique ids. They are executed in the order in which they are provided

packages (character())

The R packages this object depends on.

feature_types (NULL or character())

The feature types. Defaults to all available feature types.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
LearnerTorchModel$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Learner: [mlr_learners.mlp](#), [mlr_learners.tab_resnet](#), [mlr_learners.torch_featureless](#), [mlr_learners_torch](#), [mlr_learners_torch_image](#)

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr_pipeops_module](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [model_descriptor_to_learner\(\)](#), [model_descriptor_to_module\(\)](#), [model_descriptor_union\(\)](#), [nn_graph\(\)](#)

Examples

```
# We show the learner using a classification task

# The iris task has 4 features and 3 classes
network = nn_linear(4, 3)
task = tsk("iris")

# This defines the dataloader.
# It loads all 4 features, which are also numeric.
# The shape is (NA, 4) because the batch dimension is generally NA
ingress_tokens = list(
  input = TorchIngressToken(task$feature_names, batchgetter_num, c(NA, 4))
)

# Creating the learner and setting required parameters
learner = lrn("classif.torch_model",
  network = network,
  ingress_tokens = ingress_tokens,
  batch_size = 16,
  epochs = 1,
  device = "cpu"
)

# A simple train-predict
ids = partition(task)
learner$train(task, ids$train)
learner$predict(task, ids$test)
```

mlr_pipeops_module *Class for Torch Module Wrappers*

Description

PipeOpModule wraps an `nn_module` or function that is being called during the train phase of this `mlr3pipelines::PipeOp`. By doing so, this allows to assemble PipeOpModules in a computational `mlr3pipelines::Graph` that represents either a neural network or a preprocessing graph of a `lazy_tensor`. In most cases it is easier to create such a network by creating a graph that generates this graph.

In most cases it is easier to create such a network by creating a structurally related graph consisting of nodes of class `PipeOpTorchIngress` and `PipeOpTorch`. This graph will then generate the graph consisting of PipeOpModules as part of the `ModelDescriptor`.

Input and Output Channels

The number and names of the input and output channels can be set during construction. They input and output "torch_tensor" during training, and NULL during prediction as the prediction phase currently serves no meaningful purpose.

State

The state is the value calculated by the public method `shapes_out()`.

Parameters

No parameters.

Internals

During training, the wrapped `nn_module` / function is called with the provided inputs in the order in which the channels are defined. Arguments are **not** matched by name.

Super class

`mlr3pipelines::PipeOp` -> PipeOpModule

Public fields

module (`nn_module`)

The torch module that is called during the training phase.

Methods**Public methods:**

- [PipeOpModule\\$new\(\)](#)
- [PipeOpModule\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PipeOpModule$new(
  id = "module",
  module = nn_identity(),
  inname = "input",
  outname = "output",
  param_vals = list(),
  packages = character(0)
)
```

Arguments:

`id` (`character(1)`)

The id for of the new object.

`module` ([nn_module](#) or `function()`)

The torch module or function that is being wrapped.

`inname` (`character()`)

The names of the input channels.

`outname` (`character()`)

The names of the output channels. If this parameter has length 1, the parameter [module](#) must return a [tensor](#). Otherwise it must return a `list()` of tensors of corresponding length.

`param_vals` (`named list()`)

Parameter values to be set after construction.

`packages` (`character()`)

The R packages this object depends on.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpModule$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr_learners_torch_model](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_num](#), [model_descriptor_to_learner\(\)](#), [model_descriptor_to_module\(\)](#), [model_descriptor_union\(\)](#), [nn_graph\(\)](#)

Other PipeOp: [mlr_pipeops_torch_callbacks](#), [mlr_pipeops_torch_optimizer](#)

Examples

```

## creating an PipeOpModule manually

# one input and output channel
po_module = po("module",
  id = "linear",
  module = torch::nn_linear(10, 20),
  inname = "input",
  outname = "output"
)
x = torch::torch_randn(16, 10)
# This calls the forward function of the wrapped module.
y = po_module$train(list(input = x))
str(y)

# multiple input and output channels
nn_custom = torch::nn_module("nn_custom",
  initialize = function(in_features, out_features) {
    self$lin1 = torch::nn_linear(in_features, out_features)
    self$lin2 = torch::nn_linear(in_features, out_features)
  },
  forward = function(x, z) {
    list(out1 = self$lin1(x), out2 = torch::nnf_relu(self$lin2(z)))
  }
)

module = nn_custom(3, 2)
po_module = po("module",
  id = "custom",
  module = module,
  inname = c("x", "z"),
  outname = c("out1", "out2")
)
x = torch::torch_randn(1, 3)
z = torch::torch_randn(1, 3)
out = po_module$train(list(x = x, z = z))
str(out)

# How such a PipeOpModule is usually generated
graph = po("torch_ingress_num") %>>% po("nn_linear", out_features = 10L)
result = graph$train(tsk("iris"))
# The PipeOpTorchLinear generates a PipeOpModule and adds it to a new (module) graph
result[[1]]$graph
linear_module = result[[1L]]$graph$pipeops$nn_linear
linear_module
formalArgs(linear_module$module)
linear_module$input$name

# Constructing a PipeOpModule using a simple function
po_add1 = po("module",
  id = "add_one",
  module = function(x) x + 1

```

```

)
input = list(torch_tensor(1))
po_add1$train(input)$output

```

```
mlr_pipeops_nn_avg_pool1d
```

1D Average Pooling

Description

Applies a 1D adaptive average pooling over an input signal composed of several input planes.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `kernel_size :: integer()`
The size of the window. Can be a single number or a vector.
- `stride :: integer()`
The stride of the window. Can be a single number or a vector. Default: `kernel_size`.
- `padding :: integer()`
Implicit zero paddings on both sides of the input. Can be a single number or a vector. Default: 0.
- `ceil_mode :: integer()`
When TRUE, will use ceil instead of floor to compute the output shape. Default: FALSE.
- `count_include_pad :: logical(1)`
When TRUE, will include the zero-padding in the averaging calculation. Default: TRUE.
- `divisor_override :: logical(1)`
If specified, it will be used as divisor, otherwise size of the pooling region will be used. Default: NULL. Only available for dimension greater than 1.

Internals

Calls `nn_avg_pool1d()` during training.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchAvgPool -
> PipeOpTorchAvgPool1D
```

Methods**Public methods:**

- [PipeOpTorchAvgPool1D\\$new\(\)](#)
- [PipeOpTorchAvgPool1D\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchAvgPool1D$new(id = "nn_avg_pool1d", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchAvgPool1D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_avg_pool1d")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_avg_pool2d
      2D Average Pooling
```

Description

Applies a 2D adaptive average pooling over an input signal composed of several input planes.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls `nn_avg_pool2d()` during training.

Parameters

- `kernel_size :: integer()`
The size of the window. Can be a single number or a vector.
- `stride :: integer()`
The stride of the window. Can be a single number or a vector. Default: `kernel_size`.
- `padding :: integer()`
Implicit zero paddings on both sides of the input. Can be a single number or a vector. Default: 0.
- `ceil_mode :: integer()`
When TRUE, will use ceil instead of floor to compute the output shape. Default: FALSE.
- `count_include_pad :: logical(1)`
When TRUE, will include the zero-padding in the averaging calculation. Default: TRUE.

- `divisor_override` :: `logical(1)`
If specified, it will be used as divisor, otherwise size of the pooling region will be used. Default: `NULL`. Only available for dimension greater than 1.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchAvgPool -
> PipeOpTorchAvgPool2D
```

Methods

Public methods:

- `PipeOpTorchAvgPool2D$new()`
- `PipeOpTorchAvgPool2D$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchAvgPool2D$new(id = "nn_avg_pool2d", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchAvgPool2D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_avg_pool2d")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_avg_pool3d
      3D Average Pooling
```

Description

Applies a 3D adaptive average pooling over an input signal composed of several input planes.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls `nn_avg_pool3d()` during training.

Parameters

- `kernel_size :: integer()`
The size of the window. Can be a single number or a vector.
- `stride :: integer()`
The stride of the window. Can be a single number or a vector. Default: `kernel_size`.
- `padding :: integer()`
Implicit zero paddings on both sides of the input. Can be a single number or a vector. Default: 0.
- `ceil_mode :: integer()`
When TRUE, will use ceil instead of floor to compute the output shape. Default: FALSE.
- `count_include_pad :: logical(1)`
When TRUE, will include the zero-padding in the averaging calculation. Default: TRUE.

- `divisor_override` :: `logical(1)`
If specified, it will be used as divisor, otherwise size of the pooling region will be used. Default: `NULL`. Only available for dimension greater than 1.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchAvgPool -
> PipeOpTorchAvgPool3D
```

Methods

Public methods:

- `PipeOpTorchAvgPool3D$new()`
- `PipeOpTorchAvgPool3D$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchAvgPool3D$new(id = "nn_avg_pool3d", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchAvgPool3D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_avg_pool3d")
pipeop
# The available parameters
pipeop$params
```

```
mlr_pipeops_nn_batch_norm1d
  1D Batch Normalization
```

Description

Applies Batch Normalization for each channel across a batch of data.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `eps :: numeric(1)`
A value added to the denominator for numerical stability. Default: `1e-5`.
- `momentum :: numeric(1)`
The value used for the `running_mean` and `running_var` computation. Can be set to `NULL` for cumulative moving average (i.e. simple average). Default: `0.1`
- `affine :: logical(1)`
a boolean value that when set to `TRUE`, this module has learnable affine parameters. Default: `TRUE`
- `track_running_stats :: logical(1)`
a boolean value that when set to `TRUE`, this module tracks the running mean and variance, and when set to `FALSE`, this module does not track such statistics and always uses batch statistics in both training and eval modes. Default: `TRUE`

Internals

Calls `torch::nn_batch_norm1d()`. The parameter `num_features` is inferred as the second dimension of the input shape.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchBatchNorm
-> PipeOpTorchBatchNorm1D
```

Methods**Public methods:**

- [PipeOpTorchBatchNorm1D\\$new\(\)](#)
- [PipeOpTorchBatchNorm1D\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchBatchNorm1D$new(id = "nn_batch_norm1d", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchBatchNorm1D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_lt](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_batch_norm1d")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_batch_norm2d
      2D Batch Normalization
```

Description

Applies Batch Normalization for each channel across a batch of data.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls `torch::nn_batch_norm2d()`. The parameter `num_features` is inferred as the second dimension of the input shape.

Parameters

- `eps :: numeric(1)`
A value added to the denominator for numerical stability. Default: `1e-5`.
- `momentum :: numeric(1)`
The value used for the `running_mean` and `running_var` computation. Can be set to `NULL` for cumulative moving average (i.e. simple average). Default: `0.1`
- `affine :: logical(1)`
a boolean value that when set to `TRUE`, this module has learnable affine parameters. Default: `TRUE`
- `track_running_stats :: logical(1)`
a boolean value that when set to `TRUE`, this module tracks the running mean and variance, and when set to `FALSE`, this module does not track such statistics and always uses batch statistics in both training and eval modes. Default: `TRUE`

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchBatchNorm
-> PipeOpTorchBatchNorm2D
```

Methods**Public methods:**

- [PipeOpTorchBatchNorm2D\\$new\(\)](#)
- [PipeOpTorchBatchNorm2D\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchBatchNorm2D$new(id = "nn_batch_norm2d", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchBatchNorm2D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_lt](#), [mlr_pipeops_torch_ingress_ltmsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_batch_norm2d")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_batch_norm3d
      3D Batch Normalization
```

Description

Applies Batch Normalization for each channel across a batch of data.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls `torch::nn_batch_norm3d()`. The parameter `num_features` is inferred as the second dimension of the input shape.

Parameters

- `eps :: numeric(1)`
A value added to the denominator for numerical stability. Default: `1e-5`.
- `momentum :: numeric(1)`
The value used for the `running_mean` and `running_var` computation. Can be set to `NULL` for cumulative moving average (i.e. simple average). Default: `0.1`
- `affine :: logical(1)`
a boolean value that when set to `TRUE`, this module has learnable affine parameters. Default: `TRUE`
- `track_running_stats :: logical(1)`
a boolean value that when set to `TRUE`, this module tracks the running mean and variance, and when set to `FALSE`, this module does not track such statistics and always uses batch statistics in both training and eval modes. Default: `TRUE`

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchBatchNorm
-> PipeOpTorchBatchNorm3D
```

Methods**Public methods:**

- [PipeOpTorchBatchNorm3D\\$new\(\)](#)
- [PipeOpTorchBatchNorm3D\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchBatchNorm3D$new(id = "nn_batch_norm3d", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchBatchNorm3D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_lt](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_batch_norm3d")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_block *Block Repetition*

Description

Repeat a block `n_blocks` times.

Parameters

The parameters available for the block itself, as well as

- `n_blocks :: integer(1)`
How often to repeat the block.

Input and Output Channels

The PipeOp sets its input and output channels to those from the block (Graph) it received during construction.

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchBlock
```

Active bindings

`block` ([Graph](#))
The neural network segment that is repeated by this PipeOp.

Methods

Public methods:

- [PipeOpTorchBlock\\$new\(\)](#)
- [PipeOpTorchBlock\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchBlock$new(block, id = "nn_block", param_vals = list())
```

Arguments:

`block` ([Graph](#))

A graph consisting primarily of [PipeOpTorch](#) objects that is to be repeated.

`id` (`character(1)`)

The id for of the new object.

`param_vals` (`named list()`)

Parameter values to be set after construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchBlock$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
block = po("nn_linear") %>>% po("nn_relu")
po_block = po("nn_block", block,
nn_linear.out_features = 10L, n_blocks = 3)
```

```

network = po("torch_ingress_num") %>>%
po_block %>>%
po("nn_head") %>>%
po("torch_loss", t_loss("cross_entropy")) %>>%
po("torch_optimizer", t_opt("adam")) %>>%
po("torch_model_classif",
  batch_size = 50,
  epochs = 3)

task = tsk("iris")
network$train(task)

```

mlr_pipeops_nn_celu *CELU Activation Function*

Description

Applies element-wise, $CELU(x) = \max(0, x) + \min(0, \alpha * (\exp(x\alpha) - 1))$.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `alpha` :: numeric(1)
The alpha value for the ELU formulation. Default: 1.0
- `inplace` :: logical(1)
Whether to do the operation in-place. Default: FALSE.

Internals

Calls `torch::nn_celu()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchCELU`

Methods

Public methods:

- [PipeOpTorchCELU\\$new\(\)](#)
- [PipeOpTorchCELU\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchCELU$new(id = "nn_celu", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchCELU$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_celu")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_conv1d *1D Convolution*

Description

Applies a 1D convolution over an input signal composed of several input planes.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `out_channels :: integer(1)`
Number of channels produced by the convolution.
- `kernel_size :: integer()`
Size of the convolving kernel.
- `stride :: integer()`
Stride of the convolution. The default is 1.
- `padding :: integer()`
'dilation * (kernel_size - 1) - padding' zero-padding will be added to both sides of the input. Default: 0.
- `groups :: integer()`
Number of blocked connections from input channels to output channels. Default: 1
- `bias :: logical(1)`
If 'TRUE', adds a learnable bias to the output. Default: 'TRUE'.
- `dilation :: integer()`
Spacing between kernel elements. Default: 1.
- `padding_mode :: character(1)`
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

Internals

Calls `torch::nn_conv1d()` when trained. The parameter `in_channels` is inferred from the second dimension of the input tensor.

Super classes

mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchConv -> PipeOpTorchConv1D

Methods**Public methods:**

- [PipeOpTorchConv1D\\$new\(\)](#)
- [PipeOpTorchConv1D\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchConv1D$new(id = "nn_conv1d", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchConv1D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_conv1d", kernel_size = 10, out_channels = 1)
pipeop
# The available parameters
pipeop$params
```

mlr_pipeops_nn_conv2d *2D Convolution*

Description

Applies a 2D convolution over an input image composed of several input planes.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls `torch::nn_conv2d()` when trained. The parameter `in_channels` is inferred from the second dimension of the input tensor.

Parameters

- `out_channels :: integer(1)`
Number of channels produced by the convolution.
- `kernel_size :: integer()`
Size of the convolving kernel.
- `stride :: integer()`
Stride of the convolution. The default is 1.
- `padding :: integer()`
'dilation * (kernel_size - 1) - padding' zero-padding will be added to both sides of the input.
Default: 0.
- `groups :: integer()`
Number of blocked connections from input channels to output channels. Default: 1

- `bias :: logical(1)`
If 'TRUE', adds a learnable bias to the output. Default: 'TRUE'.
- `dilation :: integer()`
Spacing between kernel elements. Default: 1.
- `padding_mode :: character(1)`
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `mlr3torch::PipeOpTorchConv` -> `PipeOpTorchConv2D`

Methods

Public methods:

- `PipeOpTorchConv2D$new()`
- `PipeOpTorchConv2D$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchConv2D$new(id = "nn_conv2d", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchConv2D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`,

```
mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid,
mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign,
mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold,
mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr,
mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss, mlr_pipeops_torch_model, mlr_pipeops_torch_model_regr,
mlr_pipeops_torch_model_regr
```

Examples

```
# Construct the PipeOp
pipeop = po("nn_conv2d", kernel_size = 10, out_channels = 1)
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_conv3d *3D Convolution*

Description

Applies a 3D convolution over an input image composed of several input planes.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls `torch::nn_conv3d()` when trained. The parameter `in_channels` is inferred from the second dimension of the input tensor.

Parameters

- `out_channels :: integer(1)`
Number of channels produced by the convolution.
- `kernel_size :: integer()`
Size of the convolving kernel.

- `stride :: integer()`
Stride of the convolution. The default is 1.
- `padding :: integer()`
'dilation * (kernel_size - 1) - padding' zero-padding will be added to both sides of the input. Default: 0.
- `groups :: integer()`
Number of blocked connections from input channels to output channels. Default: 1
- `bias :: logical(1)`
If 'TRUE', adds a learnable bias to the output. Default: 'TRUE'.
- `dilation :: integer()`
Spacing between kernel elements. Default: 1.
- `padding_mode :: character(1)`
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `mlr3torch::PipeOpTorchConv` -> `PipeOpTorchConv3D`

Methods

Public methods:

- `PipeOpTorchConv3D$new()`
- `PipeOpTorchConv3D$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchConv3D$new(id = "nn_conv3d", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchConv3D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_conv3d", kernel_size = 10, out_channels = 1)
pipeop
# The available parameters
pipeop$param_set
```

`mlr_pipeops_nn_conv_transpose1d`

Transpose 1D Convolution

Description

Transpose 1D Convolution

Transpose 1D Convolution

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

Parameters

- `out_channels :: integer(1)`
Number of output channels produce by the convolution.
- `kernel_size :: integer()`
Size of the convolving kernel.
- `stride :: integer()`
Stride of the convolution. Default: 1.
- `padding :: integer()`
'dilation * (kernel_size - 1) - padding' zero-padding will be added to both sides of the input. Default: 0.
- `output_padding :: integer()`
Additional size added to one side of the output shape. Default: 0.
- `groups :: integer()`
Number of blocked connections from input channels to output channels. Default: 1
- `bias :: logical(1)`
If 'True', adds a learnable bias to the output. Default: 'TRUE'.
- `dilation :: integer()`
Spacing between kernel elements. Default: 1.
- `padding_mode :: character(1)`
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

Internals

Calls `nn_conv_transpose1d`. The parameter `in_channels` is inferred as the second dimension of the input tensor.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchConvTranspose
-> PipeOpTorchConvTranspose1D
```

Methods**Public methods:**

- `PipeOpTorchConvTranspose1D$new()`
- `PipeOpTorchConvTranspose1D$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchConvTranspose1D$new(id = "nn_conv_transpose1d", param_vals = list())
```

Arguments:

```
id (character(1))
  Identifier of the resulting object.
```

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchConvTranspose1D$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_conv_transpose1d", kernel_size = 3, out_channels = 2)
pipeop
# The available parameters
pipeop$param_set
```

`mlr_pipeops_nn_conv_transpose2d`

Transpose 2D Convolution

Description

Applies a 2D transposed convolution operator over an input image composed of several input planes, sometimes also called "deconvolution".

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls [nn_conv_transpose2d](#). The parameter `in_channels` is inferred as the second dimension of the input tensor.

Parameters

- `out_channels :: integer(1)`
Number of output channels produce by the convolution.
- `kernel_size :: integer()`
Size of the convolving kernel.
- `stride :: integer()`
Stride of the convolution. Default: 1.
- `padding :: integer()`
'dilation * (kernel_size - 1) - padding' zero-padding will be added to both sides of the input. Default: 0.
- `output_padding :: integer()`
Additional size added to one side of the output shape. Default: 0.
- `groups :: integer()`
Number of blocked connections from input channels to output channels. Default: 1
- `bias :: logical(1)`
If 'True', adds a learnable bias to the output. Default: 'TRUE'.
- `dilation :: integer()`
Spacing between kernel elements. Default: 1.
- `padding_mode :: character(1)`
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchConvTranspose
-> PipeOpTorchConvTranspose2D
```

Methods**Public methods:**

- `PipeOpTorchConvTranspose2D$new()`
- `PipeOpTorchConvTranspose2D$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchConvTranspose2D$new(id = "nn_conv_transpose2d", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchConvTranspose2D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_conv_transpose2d", kernel_size = 3, out_channels = 2)
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_conv_transpose3d
Transpose 3D Convolution

Description

Applies a 3D transposed convolution operator over an input image composed of several input planes, sometimes also called "deconvolution"

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls `nn_conv_transpose3d`. The parameter `in_channels` is inferred as the second dimension of the input tensor.

Parameters

- `out_channels :: integer(1)`
Number of output channels produce by the convolution.
- `kernel_size :: integer()`
Size of the convolving kernel.
- `stride :: integer()`
Stride of the convolution. Default: 1.
- `padding :: integer()`
'dilation * (kernel_size - 1) - padding' zero-padding will be added to both sides of the input. Default: 0.
- `output_padding :: integer()`
Additional size added to one side of the output shape. Default: 0.
- `groups :: integer()`
Number of blocked connections from input channels to output channels. Default: 1
- `bias :: logical(1)`
If 'True', adds a learnable bias to the output. Default: 'TRUE'.
- `dilation :: integer()`
Spacing between kernel elements. Default: 1.

- padding_mode :: character(1)
The padding mode. One of "zeros", "reflect", "replicate", or "circular". Default is "zeros".

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchConvTranspose
-> PipeOpTorchConvTranspose3D
```

Methods

Public methods:

- PipeOpTorchConvTranspose3D\$new()
- PipeOpTorchConvTranspose3D\$clone()

Method new(): Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchConvTranspose3D$new(id = "nn_conv_transpose3d", param_vals = list())
```

Arguments:

id (character(1))

Identifier of the resulting object.

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchConvTranspose3D$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_conv_transpose3d", kernel_size = 3, out_channels = 2)
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_dropout
      Dropout
```

Description

During training, randomly zeroes some of the elements of the input tensor with probability p using samples from a Bernoulli distribution.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `p` :: numeric(1)
Probability of an element to be zeroed. Default: 0.5 inplace
- `inplace` :: logical(1)
If set to TRUE, will do this operation in-place. Default: FALSE.

Internals

Calls `torch::nn_dropout()` when trained.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchDropout
```

Methods**Public methods:**

- [PipeOpTorchDropout\\$new\(\)](#)
- [PipeOpTorchDropout\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchDropout$new(id = "nn_dropout", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchDropout$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_dropout")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_elu *ELU Activation Function*

Description

Applies element-wise,

$$ELU(x) = \max(0, x) + \min(0, \alpha * (\exp(x) - 1))$$

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `alpha :: numeric(1)`
The alpha value for the ELU formulation. Default: 1.0
- `inplace :: logical(1)`
Whether to do the operation in-place. Default: FALSE.

Internals

Calls `torch::nn_elu()` when trained.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchELU`

Methods

Public methods:

- `PipeOpTorchELU$new()`
- `PipeOpTorchELU$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchELU$new(id = "nn_elu", param_vals = list())
```

Arguments:

id (character(1))

Identifier of the resulting object.

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchELU$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_elu")
pipeop
# The available parameters
pipeop$param_set
```

 mlr_pipeops_nn_flatten

Flattens a Tensor

Description

For use with [nn_sequential](#).

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

`start_dim` :: integer(1)

At wich dimension to start flattening. Default is 2. `end_dim` :: integer(1)

At wich dimension to stop flattening. Default is -1.

Internals

Calls `torch::nn_flatten()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchFlatten`

Methods

Public methods:

- `PipeOpTorchFlatten$new()`
- `PipeOpTorchFlatten$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchFlatten$new(id = "nn_flatten", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

```
param_vals (list())
```

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchFlatten$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_flatten")
pipeop
# The available parameters
pipeop$param_set
```

`mlr_pipeops_nn_gelu` *GELU Activation Function*

Description

Gelu

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `approximate :: character(1)`
Whether to use an approximation algorithm. Default is "none".

Internals

Calls `torch::nn_gelu()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchGELU`

Methods**Public methods:**

- `PipeOpTorchGELU$new()`
- `PipeOpTorchGELU$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchGELU$new(id = "nn_gelu", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchGELU$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_glu")
pipeop
# The available parameters
pipeop$params
```

`mlr_pipeops_nn_glu` *GLU Activation Function*

Description

The gated linear unit. Computes:

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `dim :: integer(1)`
Dimension on which to split the input. Default: -1

Internals

Calls `torch::nn_glu()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchGLU`

Methods**Public methods:**

- `PipeOpTorchGLU$new()`
- `PipeOpTorchGLU$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchGLU$new(id = "nn_glu", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchGLU$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`,

```
mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid,
mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign,
mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold,
mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr,
mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss, mlr_pipeops_torch_model, mlr_pipeops_torch_model_regr
```

Examples

```
# Construct the PipeOp
pipeop = po("nn_glu")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_hardshrink
      Hard Shrink Activation Function
```

Description

Applies the hard shrinkage function element-wise

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `lambda :: numeric(1)`
The lambda value for the Hardshrink formulation formulation. Default 0.5.

Internals

Calls `torch::nn_hardshrink()` when trained.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchHardShrink
```

Methods

Public methods:

- `PipeOpTorchHardShrink$new()`
- `PipeOpTorchHardShrink$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchHardShrink$new(id = "nn_hardshrink", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchHardShrink$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_hardshrink")
pipeop
# The available parameters
pipeop$param_set
```

`mlr_pipeops_nn_hardsigmoid`*Hard Sigmoid Activation Function*

Description

Applies the element-wise function $\text{Hardsigmoid}(x) = \frac{\text{ReLU}_6(x+3)}{6}$

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

No parameters.

Internals

Calls `torch::nn_hardsigmoid()` when trained.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchHardSigmoid`

Methods

Public methods:

- `PipeOpTorchHardSigmoid$new()`
- `PipeOpTorchHardSigmoid$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchHardSigmoid$new(id = "nn_hardsigmoid", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchHardSigmoid$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_hardsigmoid")
pipeop
# The available parameters
pipeop$param_set
```

`mlr_pipeops_nn_hardtanh`

Hard Tanh Activation Function

Description

Applies the HardTanh function element-wise.

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `min_val` :: `numeric(1)`
Minimum value of the linear region range. Default: -1.
- `max_val` :: `numeric(1)`
Maximum value of the linear region range. Default: 1.
- `inplace` :: `logical(1)`
Can optionally do the operation in-place. Default: FALSE.

Internals

Calls `torch::nn_hardtanh()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchHardTanh`

Methods**Public methods:**

- `PipeOpTorchHardTanh$new()`
- `PipeOpTorchHardTanh$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchHardTanh$new(id = "nn_hardtanh", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchHardTanh$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_hardtanh")
pipeop
# The available parameters
pipeop$param_set
```

`mlr_pipeops_nn_head` *Output Head*

Description

Output head for classification and regression.

NOTE Because the method `$shapes_out()` does not have access to the task, it returns `c(NA, NA)`. When this [PipeOp](#) is trained however, the model descriptor has the correct output shape.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `bias :: logical(1)`
Whether to use a bias. Default is TRUE.

Internals

Calls `torch::nn_linear()` with the input and output features inferred from the input shape / task.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchHead`

Methods**Public methods:**

- `PipeOpTorchHead$new()`
- `PipeOpTorchHead$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchHead$new(id = "nn_head", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchHead$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`,

```
mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid,
mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign,
mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold,
mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr,
mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss, mlr_pipeops_torch_model, mlr_pipeops_torch_model_regr,
mlr_pipeops_torch_model_regr
```

Examples

```
# Construct the PipeOp
pipeop = po("nn_head")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_layer_norm
      Layer Normalization
```

Description

Applies Layer Normalization for last certain number of dimensions.

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

Parameters

- `dims :: integer(1)`
The number of dimensions over which will be normalized (starting from the last dimension).
- `elementwise_affine :: logical(1)`
Whether to learn affine-linear parameters initialized to 1 for weights and to 0 for biases. The default is TRUE.
- `eps :: numeric(1)`
A value added to the denominator for numerical stability.

Internals

Calls `torch::nn_layer_norm()` when trained. The parameter `normalized_shape` is inferred as the dimensions of the last `dims` dimensions of the input shape.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchLayerNorm`

Methods**Public methods:**

- `PipeOpTorchLayerNorm$new()`
- `PipeOpTorchLayerNorm$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchLayerNorm$new(id = "nn_layer_norm", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchLayerNorm$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_layer_norm", dims = 1)
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_leaky_relu

Leaky ReLU Activation Function

Description

Applies element-wise, $LeakyReLU(x) = \max(0, x) + negative_slope * \min(0, x)$

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `negative_slope :: numeric(1)`
Controls the angle of the negative slope. Default: 1e-2.
- `inplace :: logical(1)`
Can optionally do the operation in-place. Default: 'FALSE'.

Internals

Calls `torch::nn_hardswish()` when trained.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchLeakyReLU`

Methods**Public methods:**

- `PipeOpTorchLeakyReLU$new()`
- `PipeOpTorchLeakyReLU$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchLeakyReLU$new(id = "nn_leaky_relu", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchLeakyReLU$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_leaky_relu")
pipeop
# The available parameters
pipeop$param_set
```

 mlr_pipeops_nn_linear *Linear Layer*

Description

Applies a linear transformation to the incoming data: $y = xA^T + b$.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `out_features :: integer(1)`
The output features of the linear layer.
- `bias :: logical(1)`
Whether to use a bias. Default is TRUE.

Internals

Calls `torch::nn_linear()` when trained where the parameter `in_features` is inferred as the second to last dimension of the input tensor.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchLinear`

Methods

Public methods:

- `PipeOpTorchLinear$new()`
- `PipeOpTorchLinear$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchLinear$new(id = "nn_linear", param_vals = list())
```

Arguments:

id (character(1))
 Identifier of the resulting object.

param_vals (list())
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchLinear$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_linear", out_features = 10)
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_log_sigmoid

Log Sigmoid Activation Function

Description

Applies element-wise $\text{LogSigmoid}(x_i) = \log\left(\frac{1}{1+\exp(-x_i)}\right)$

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

No parameters.

Internals

Calls `torch::nn_log_sigmoid()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchLogSigmoid`

Methods**Public methods:**

- `PipeOpTorchLogSigmoid$new()`
- `PipeOpTorchLogSigmoid$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchLogSigmoid$new(id = "nn_log_sigmoid", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchLogSigmoid$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_log_sigmoid")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_max_pool1d
```

1D Max Pooling

Description

Applies a 1D max pooling over an input signal composed of several input planes.

Input and Output Channels

If `return_indices` is `FALSE` during construction, there is one input channel 'input' and one output channel 'output'. If `return_indices` is `TRUE`, there are two output channels 'output' and 'indices'. For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `kernel_size :: integer()`
The size of the window. Can be single number or a vector.
- `stride :: (integer(1))`
The stride of the window. Can be a single number or a vector. Default: `kernel_size`
- `padding :: integer()`
Implicit zero paddings on both sides of the input. Can be a single number or a tuple (`padW,`). Default: 0
- `dilation :: integer()`
Controls the spacing between the kernel points; also known as the `à trous` algorithm. Default: 1
- `ceil_mode :: logical(1)`
When True, will use `ceil` instead of `floor` to compute the output shape. Default: FALSE

Internals

Calls `torch::nn_max_pool1d()` during training.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMaxPool -
> PipeOpTorchMaxPool1D
```

Methods

Public methods:

- `PipeOpTorchMaxPool1D$new()`
- `PipeOpTorchMaxPool1D$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchMaxPool1D$new(
  id = "nn_max_pool1d",
  return_indices = FALSE,
  param_vals = list()
)
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`return_indices` (`logical(1)`)

Whether to return the indices. If this is TRUE, there are two output channels "output" and "indices".

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchMaxPool1D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_max_pool1d")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_max_pool2d
      2D Max Pooling
```

Description

Applies a 2D max pooling over an input signal composed of several input planes.

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls `torch::nn_max_pool2d()` during training.

Input and Output Channels

If `return_indices` is `FALSE` during construction, there is one input channel 'input' and one output channel 'output'. If `return_indices` is `TRUE`, there are two output channels 'output' and 'indices'. For an explanation see [PipeOpTorch](#).

Parameters

- `kernel_size :: integer()`
The size of the window. Can be single number or a vector.
- `stride :: (integer(1))`
The stride of the window. Can be a single number or a vector. Default: `kernel_size`
- `padding :: integer()`
Implicit zero paddings on both sides of the input. Can be a single number or a tuple (`padW`). Default: 0
- `dilation :: integer()`
Controls the spacing between the kernel points; also known as the *à trous* algorithm. Default: 1
- `ceil_mode :: logical(1)`
When True, will use `ceil` instead of `floor` to compute the output shape. Default: `FALSE`

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMaxPool -
> PipeOpTorchMaxPool2D
```

Methods**Public methods:**

- [PipeOpTorchMaxPool2D\\$new\(\)](#)
- [PipeOpTorchMaxPool2D\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchMaxPool2D$new(
  id = "nn_max_pool2d",
  return_indices = FALSE,
  param_vals = list()
)
```

Arguments:

id (character(1))
 Identifier of the resulting object.

return_indices (logical(1))
 Whether to return the indices. If this is TRUE, there are two output channels "output" and "indices".

param_vals (list())
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchMaxPool2D$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_max_pool2d")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_max_pool3d
3D Max Pooling

Description

Applies a 3D max pooling over an input signal composed of several input planes.

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Internals

Calls `torch::nn_max_pool3d()` during training.

Input and Output Channels

If `return_indices` is `FALSE` during construction, there is one input channel 'input' and one output channel 'output'. If `return_indices` is `TRUE`, there are two output channels 'output' and 'indices'. For an explanation see [PipeOpTorch](#).

Parameters

- `kernel_size :: integer()`
The size of the window. Can be single number or a vector.
- `stride :: (integer(1))`
The stride of the window. Can be a single number or a vector. Default: `kernel_size`
- `padding :: integer()`
Implicit zero paddings on both sides of the input. Can be a single number or a tuple (`padW,`). Default: `0`
- `dilation :: integer()`
Controls the spacing between the kernel points; also known as the *à trous* algorithm. Default: `1`
- `ceil_mode :: logical(1)`
When `True`, will use `ceil` instead of `floor` to compute the output shape. Default: `FALSE`

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMaxPool -> PipeOpTorchMaxPool3D
```

Methods**Public methods:**

- [PipeOpTorchMaxPool3D\\$new\(\)](#)
- [PipeOpTorchMaxPool3D\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchMaxPool3D$new(
  id = "nn_max_pool3d",
  return_indices = FALSE,
  param_vals = list()
)
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`return_indices` (logical(1))

Whether to return the indices. If this is TRUE, there are two output channels "output" and "indices".

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchMaxPool3D$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_max_pool3d")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_merge *Merge Operation*

Description

Base class for merge operations such as addition ([PipeOpTorchMergeSum](#)), multiplication ([PipeOpTorchMergeProd](#)) or concatenation ([PipeOpTorchMergeCat](#)).

State

The state is the value calculated by the public method `shapes_out()`.

Input and Output Channels

`PipeOpTorchMerges` has either a *vararg* input channel if the constructor argument `innum` is not set, or input channels "input1", ..., "input<innum>". There is one output channel "output". For an explanation see [PipeOpTorch](#).

Parameters

See the respective child class.

Internals

Per default, the `private$.shapes_out()` method outputs the broadcasted tensors. There are two things to be aware:

1. NAs are assumed to batch (this should almost always be the batch size in the first dimension).
2. Tensors are expected to have the same number of dimensions, i.e. missing dimensions are not filled with 1s. The reason is that again that the first dimension should be the batch dimension. This private method can be overwritten by [PipeOpTorchs](#) inheriting from this class.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchMerge
```

Methods**Public methods:**

- [PipeOpTorchMerge\\$new\(\)](#)
- [PipeOpTorchMerge\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchMerge$new(
  id,
  module_generator,
  param_set = ps(),
  innum = 0,
  param_vals = list()
)
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`module_generator` (`nn_module_generator`)

The torch module generator.

`param_set` (`ParamSet`)

The parameter set.

`innum` (`integer(1)`)

The number of inputs. Default is 0 which means there is one *vararg* input channel.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchMerge$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#),

```
mlr_pipeops_nn_rrelu,mlr_pipeops_nn_selu,mlr_pipeops_nn_sigmoid,mlr_pipeops_nn_softmax,
mlr_pipeops_nn_softplus,mlr_pipeops_nn_softshrink,mlr_pipeops_nn_softsign,mlr_pipeops_nn_squeeze,
mlr_pipeops_nn_tanh,mlr_pipeops_nn_tanhshrink,mlr_pipeops_nn_threshold,mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_categ,mlr_pipeops_torch_ingress_ltnsr,mlr_pipeops_torch_ingress_num,
mlr_pipeops_torch_loss,mlr_pipeops_torch_model,mlr_pipeops_torch_model_classif,
mlr_pipeops_torch_model_regr
```

```
mlr_pipeops_nn_merge_cat
```

Merge by Concatenation

Description

Concatenates multiple tensors on a given dimension. No broadcasting rules are applied here, you must reshape the tensors before to have the same shape.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

PipeOpTorchMerges has either a *vararg* input channel if the constructor argument `innum` is not set, or input channels "input1", ..., "input<innum>". There is one output channel "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `dim :: integer(1)`
The dimension along which to concatenate the tensors.

Internals

Calls `nn_merge_cat()` when trained.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMerge ->
PipeOpTorchMergeCat
```

Methods**Public methods:**

- [PipeOpTorchMergeCat\\$new\(\)](#)
- [PipeOpTorchMergeCat\\$speak\(\)](#)
- [PipeOpTorchMergeCat\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchMergeCat$new(id = "nn_merge_cat", innum = 0, param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`innum` (integer(1))

The number of inputs. Default is 0 which means there is one *vararg* input channel.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `speak()`: What does the cat say?

Usage:

```
PipeOpTorchMergeCat$speak()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchMergeCat$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_merge_cat")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_merge_prod
      Merge by Product
```

Description

Calculates the product of all input tensors.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

PipeOpTorchMerges has either a *vararg* input channel if the constructor argument `innum` is not set, or input channels "input1", ..., "input<innum>". There is one output channel "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

No parameters.

Internals

Calls `nn_merge_prod()` when trained.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMerge ->
PipeOpTorchMergeProd
```

Methods**Public methods:**

- [PipeOpTorchMergeProd\\$new\(\)](#)
- [PipeOpTorchMergeProd\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchMergeProd$new(id = "nn_merge_prod", innum = 0, param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`innum` (`integer(1)`)

The number of inputs. Default is 0 which means there is one *vararg* input channel.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchMergeProd$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
# Construct the PipeOp
pipeop = po("nn_merge_prod")
```

```
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_merge_sum
```

Merge by Summation

Description

Calculates the sum of all input tensors.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

PipeOpTorchMerges has either a *vararg* input channel if the constructor argument `innum` is not set, or input channels "input1", ..., "input<innum>". There is one output channel "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

No parameters.

Internals

Calls `nn_merge_sum()` when trained.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> mlr3torch::PipeOpTorchMerge ->
PipeOpTorchMergeSum
```

Methods**Public methods:**

- [PipeOpTorchMergeSum\\$new\(\)](#)
- [PipeOpTorchMergeSum\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchMergeSum$new(id = "nn_merge_sum", innum = 0, param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`innum` (integer(1))

The number of inputs. Default is 0 which means there is one *vararg* input channel.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchMergeSum$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#),

```
mlr_pipeops_nn_conv_transpose3d,mlr_pipeops_nn_dropout,mlr_pipeops_nn_elu,mlr_pipeops_nn_flatten,
mlr_pipeops_nn_gelu,mlr_pipeops_nn_glu,mlr_pipeops_nn_hardshrink,mlr_pipeops_nn_hardsigmoid,
mlr_pipeops_nn_hardtanh,mlr_pipeops_nn_head,mlr_pipeops_nn_layer_norm,mlr_pipeops_nn_leaky_relu,
mlr_pipeops_nn_linear,mlr_pipeops_nn_log_sigmoid,mlr_pipeops_nn_max_pool1d,mlr_pipeops_nn_max_pool2d,
mlr_pipeops_nn_max_pool3d,mlr_pipeops_nn_merge,mlr_pipeops_nn_merge_cat,mlr_pipeops_nn_merge_prod,
mlr_pipeops_nn_prelu,mlr_pipeops_nn_relu,mlr_pipeops_nn_relu6,mlr_pipeops_nn_reshape,
mlr_pipeops_nn_rrelu,mlr_pipeops_nn_selu,mlr_pipeops_nn_sigmoid,mlr_pipeops_nn_softmax,
mlr_pipeops_nn_softplus,mlr_pipeops_nn_softshrink,mlr_pipeops_nn_softsign,mlr_pipeops_nn_squeeze,
mlr_pipeops_nn_tanh,mlr_pipeops_nn_tanhshrink,mlr_pipeops_nn_threshold,mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_categ,mlr_pipeops_torch_ingress_ltnsr,mlr_pipeops_torch_ingress_num,
mlr_pipeops_torch_loss,mlr_pipeops_torch_model,mlr_pipeops_torch_model_classif,
mlr_pipeops_torch_model_regr
```

Examples

```
# Construct the PipeOp
pipeop = po("nn_merge_sum")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_prelu *PReLU Activation Function*

Description

Applies element-wise the function $PReLU(x) = \max(0, x) + weight * \min(0, x)$ where *weight* is a learnable parameter.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `num_parameters` :: `integer(1)`: Number of a to learn. Although it takes an int as input, there is only two values are legitimate: 1, or the number of channels at input. Default: 1.
- `init` :: `numeric(1)`
T The initial value of a. Default: 0.25.

Internals

Calls `torch::nn_prelu()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchPReLU`

Methods**Public methods:**

- `PipeOpTorchPReLU$new()`
- `PipeOpTorchPReLU$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchPReLU$new(id = "nn_prelu", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchPReLU$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_prelu")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_relu *ReLU Activation Function*

Description

Applies the rectified linear unit function element-wise.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `inplace :: logical(1)`
Whether to do the operation in-place. Default: FALSE.

Internals

Calls `torch::nn_relu()` when trained.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchReLU`

Methods**Public methods:**

- `PipeOpTorchReLU$new()`
- `PipeOpTorchReLU$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchReLU$new(id = "nn_relu", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchReLU$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_relu")
pipeop
# The available parameters
pipeop$param_set
```

 mlr_pipeops_nn_relu6 *ReLU6 Activation Function*

Description

Applies the element-wise function $ReLU6(x) = \min(\max(0, x), 6)$.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `inplace :: logical(1)`
Whether to do the operation in-place. Default: FALSE.

Internals

Calls `torch::nn_relu6()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchReLU6`

Methods

Public methods:

- `PipeOpTorchReLU6$new()`
- `PipeOpTorchReLU6$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchReLU6$new(id = "nn_relu6", param_vals = list())
```

Arguments:

`id` (`character(1)`)
Identifier of the resulting object.

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchReLU6$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_relu6")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_reshape

Reshape a Tensor

Description

Reshape a tensor to the given shape.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `shape :: integer(1)`
The desired output shape. Unknown dimension (one at most) can either be specified as -1 or NA.

Internals

Calls `nn_reshape()` when trained. This internally calls `torch::torch_reshape()` with the given shape.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchReshape`

Methods

Public methods:

- `PipeOpTorchReshape$new()`
- `PipeOpTorchReshape$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchReshape$new(id = "nn_reshape", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchReshape$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_reshape")
pipeop
# The available parameters
pipeop$params
```

`mlr_pipeops_nn_rrelu` *RReLU Activation Function*

Description

Randomized leaky ReLU.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `lower:: numeric(1)`
Lower bound of the uniform distribution. Default: 1/8.
- `upper:: numeric(1)`
Upper bound of the uniform distribution. Default: 1/3.
- `inplace :: logical(1)`
Whether to do the operation in-place. Default: FALSE.

Internals

Calls `torch::nn_rrelu()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchRReLU`

Methods**Public methods:**

- `PipeOpTorchRReLU$new()`
- `PipeOpTorchRReLU$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchRReLU$new(id = "nn_rrelu", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchRReLU$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`,

```
mlr_pipeops_nn_hardtanh, mlr_pipeops_nn_head, mlr_pipeops_nn_layer_norm, mlr_pipeops_nn_leaky_relu,
mlr_pipeops_nn_linear, mlr_pipeops_nn_log_sigmoid, mlr_pipeops_nn_max_pool1d, mlr_pipeops_nn_max_pool2d,
mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat, mlr_pipeops_nn_merge_prod,
mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_relu, mlr_pipeops_nn_relu6,
mlr_pipeops_nn_reshape, mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid, mlr_pipeops_nn_softmax,
mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze,
mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold, mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num,
mlr_pipeops_torch_loss, mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif,
mlr_pipeops_torch_model_regr
```

Examples

```
# Construct the PipeOp
pipeop = po("nn_rrelu")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_selu *SELU Activation Function*

Description

Applies element-wise,

$$SELU(x) = scale * (max(0, x) + min(0, \alpha * (exp(x) - 1)))$$

, with $\alpha = 1.6732632423543772848170429916717$ and $scale = 1.0507009873554804934193349852946$.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `inplace :: logical(1)`
Whether to do the operation in-place. Default: FALSE.

Internals

Calls `torch::nn_selu()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchSELU`

Methods**Public methods:**

- `PipeOpTorchSELU$new()`
- `PipeOpTorchSELU$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchSELU$new(id = "nn_selu", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchSELU$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_selu")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_sigmoid

Sigmoid Activation Function

Description

Applies element-wise $Sigmoid(x_i) = \frac{1}{1+exp(-x_i)}$

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

No parameters.

Internals

Calls `torch::nn_sigmoid()` when trained.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSigmoid`

Methods**Public methods:**

- `PipeOpTorchSigmoid$new()`
- `PipeOpTorchSigmoid$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchSigmoid$new(id = "nn_sigmoid", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchSigmoid$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_sigmoid")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_softmax
Softmax

Description

Applies a softmax function.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `dim :: integer(1)`
A dimension along which Softmax will be computed (so every slice along dim will sum to 1).

Internals

Calls `torch::nn_softmax()` when trained.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSoftmax`

Methods

Public methods:

- `PipeOpTorchSoftmax$new()`
- `PipeOpTorchSoftmax$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchSoftmax$new(id = "nn_softmax", param_vals = list())
```

Arguments:

`id` (`character(1)`)
Identifier of the resulting object.

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchSoftmax$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_softmax")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_softplus

SoftPlus Activation Function

Description

Applies element-wise, the function $Softplus(x) = 1/\beta * \log(1 + \exp(\beta * x))$.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `beta :: numeric(1)`
The beta value for the Softplus formulation. Default: 1
- `threshold :: numeric(1)`
Values above this revert to a linear function. Default: 20

Internals

Calls `torch::nn_softplus()` when trained.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSoftPlus`

Methods**Public methods:**

- `PipeOpTorchSoftPlus$new()`
- `PipeOpTorchSoftPlus$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchSoftPlus$new(id = "nn_softplus", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchSoftPlus$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_softplus")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_softshrink
```

Soft Shrink Activation Function

Description

Applies the soft shrinkage function elementwise

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `lamd` :: numeric(1)
The lambda (must be no less than zero) value for the Softshrink formulation. Default: 0.5

Internals

Calls `torch::nn_softshrink()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchSoftShrink`

Methods**Public methods:**

- `PipeOpTorchSoftShrink$new()`
- `PipeOpTorchSoftShrink$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchSoftShrink$new(id = "nn_softshrink", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchSoftShrink$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`,

```
mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid,
mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softsign, mlr_pipeops_nn_squeeze,
mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold, mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num,
mlr_pipeops_torch_loss, mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif,
mlr_pipeops_torch_model_regr
```

Examples

```
# Construct the PipeOp
pipeop = po("nn_softshrink")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_softsign
```

SoftSign Activation Function

Description

Applies element-wise, the function $SoftSign(x) = x/(1 + |x|)$

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

No parameters.

Internals

Calls `torch::nn_softsign()` when trained.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSoftSign
```

Methods**Public methods:**

- `PipeOpTorchSoftSign$new()`
- `PipeOpTorchSoftSign$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchSoftSign$new(id = "nn_softsign", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchSoftSign$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_softsign")
pipeop
# The available parameters
pipeop$param_set
```

`mlr_pipeops_nn_squeeze`*Squeeze a Tensor*

Description

Squeezes a tensor by calling `torch::torch_squeeze()` with the given dimension `dim`.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `dim :: integer(1)`
The dimension to squeeze. If NULL, all dimensions of size 1 will be squeezed. Negative values are interpreted downwards from the last dimension.
- `dim :: integer(1)`
The dimension which to unsqueeze. Negative values are interpreted downwards from the last dimension.

Internals

Calls `nn_squeeze()` when trained.

Calls `nn_unsqueeze()` when trained. This internally calls `torch::torch_unsqueeze()`.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchSqueeze`

Methods**Public methods:**

- [PipeOpTorchSqueeze\\$new\(\)](#)
- [PipeOpTorchSqueeze\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PipeOpTorchSqueeze$new(id = "nn_squeeze", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchSqueeze$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchUnsqueeze
```

Methods**Public methods:**

- [PipeOpTorchUnsqueeze\\$new\(\)](#)
- [PipeOpTorchUnsqueeze\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PipeOpTorchUnsqueeze$new(id = "nn_unsqueeze", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchUnsqueeze$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_squeeze")
pipeop
# The available parameters
pipeop$param_set
```

```
# Construct the PipeOp
pipeop = po("nn_squeeze")
pipeop
# The available parameters
pipeop$param_set
```

mlr_pipeops_nn_tanh *Tanh Activation Function*

Description

Applies the element-wise function:

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

No parameters.

Internals

Calls `torch::nn_tanh()` when trained.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchTanh`

Methods

Public methods:

- `PipeOpTorchTanh$new()`
- `PipeOpTorchTanh$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchTanh$new(id = "nn_tanh", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchTanh$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_tanh")
pipeop
# The available parameters
pipeop$param_set
```

`mlr_pipeops_nn_tanhshrink`

Tanh Shrink Activation Function

Description

Applies element-wise, $Tanhshrink(x) = x - Tanh(x)$

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

No parameters.

Internals

Calls `torch::nn_tanhshrink()` when trained.

Super classes

```
mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorch -> PipeOpTorchTanhShrink
```

Methods**Public methods:**

- `PipeOpTorchTanhShrink$new()`
- `PipeOpTorchTanhShrink$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchTanhShrink$new(id = "nn_tanhshrink", param_vals = list())
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchTanhShrink$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Examples

```
# Construct the PipeOp
pipeop = po("nn_tanhshrink")
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_nn_threshold
```

Threshold Activation Function

Description

Thresholds each element of the input Tensor.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `$shapes_out()`.

Credit

Part of this documentation have been copied or adapted from the documentation of **torch**.

Parameters

- `threshold :: numeric(1)`
The value to threshold at.
- `value :: numeric(1)`
The value to replace with.
- `inplace :: logical(1)`
Can optionally do the operation in-place. Default: 'FALSE'.

Internals

Calls `torch::nn_threshold()` when trained.

Super classes

`mlr3pipelines::PipeOp` -> `mlr3torch::PipeOpTorch` -> `PipeOpTorchThreshold`

Methods**Public methods:**

- `PipeOpTorchThreshold$new()`
- `PipeOpTorchThreshold$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchThreshold$new(id = "nn_threshold", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchThreshold$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`,

```
mlr_pipeops_nn_hardtanh, mlr_pipeops_nn_head, mlr_pipeops_nn_layer_norm, mlr_pipeops_nn_leaky_relu,
mlr_pipeops_nn_linear, mlr_pipeops_nn_log_sigmoid, mlr_pipeops_nn_max_pool1d, mlr_pipeops_nn_max_pool2d,
mlr_pipeops_nn_max_pool3d, mlr_pipeops_nn_merge, mlr_pipeops_nn_merge_cat, mlr_pipeops_nn_merge_prod,
mlr_pipeops_nn_merge_sum, mlr_pipeops_nn_prelu, mlr_pipeops_nn_relu, mlr_pipeops_nn_relu6,
mlr_pipeops_nn_reshape, mlr_pipeops_nn_rrelu, mlr_pipeops_nn_selu, mlr_pipeops_nn_sigmoid,
mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign,
mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink, mlr_pipeops_torch_ingress,
mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr, mlr_pipeops_torch_ingress_num,
mlr_pipeops_torch_loss, mlr_pipeops_torch_model, mlr_pipeops_torch_model_classif,
mlr_pipeops_torch_model_regr
```

Examples

```
# Construct the PipeOp
pipeop = po("nn_threshold", threshold = 1, value = 2)
pipeop
# The available parameters
pipeop$param_set
```

```
mlr_pipeops_preproc_torch
```

Base Class for Lazy Tensor Preprocessing

Description

This PipeOp can be used to preprocess (one or more) [lazy_tensor](#) columns contained in an [mlr3::Task](#). The preprocessing function is specified as construction argument `fn` and additional arguments to this function can be defined through the PipeOp's parameter set. The preprocessing is done per column, i.e. the number of lazy tensor output columns is equal to the number of lazy tensor input columns.

To create custom preprocessing PipeOps you can use [pipeop_preproc_torch](#).

Inheriting

In addition to specifying the construction arguments, you can overwrite the private `.shapes_out()` method. If you don't overwrite it, the output shapes are assumed to be unknown (NULL).

- `.shapes_out(shapes_in, param_vals, task)`
`(list(), list(), TaskorNULL) -> list()\n` This private method calculates the output shapes of the lazy tensor columns. This private method only has the responsibility to calculate the output shapes for one input column, i.e. the input `shapes_in` can be assumed to have exactly one shape vector for which it must calculate the output shapes and return it as a `list()` of length 1. It can also be assumed that the shape is not NULL (i.e. unknown). Also, the first dimension can be NA, i.e. is unknown (as for the batch dimension).

Input and Output Channels

See [PipeOpTaskPreproc](#).

State

In addition to state elements from [PipeOpTaskPreprocSimple](#), the state also contains the `$param_vals` that were set during training.

Parameters

In addition to the parameters inherited from [PipeOpTaskPreproc](#) as well as those specified during construction as the argument `param_set` there are the following parameters:

- `stages :: character(1)`
The stages during which to apply the preprocessing. Can be one of "train", "predict" or "both". The initial value of this parameter is set to "train" when the PipeOp's id starts with "augment_" and to "both" otherwise. Note that the preprocessing that is applied during `$predict()` uses the parameters that were set during `$train()` and not those that are set when performing the prediction.

Internals

During `$train()` / `$predict()`, a [PipeOpModule](#) with one input and one output channel is created. The pipeop applies the function `fn` to the input tensor while additionally passing the parameter values (minus `stages` and `affect_columns`) to `fn`. The preprocessing graph of the lazy tensor columns is shallowly cloned and the [PipeOpModule](#) is added. This is done to avoid modifying user input and means that identical [PipeOpModules](#) can be part of different preprocessing graphs. This is only possible, because the created [PipeOpModule](#) is stateless.

At a later point in the graph, preprocessing graphs will be merged if possible to avoid unnecessary computation. This is best illustrated by example: One lazy tensor column's preprocessing graph is `A -> B`. Then, two branches are created `B -> C` and `B -> D`, creating two preprocessing graphs `A -> B -> C` and `A -> B -> D`. When loading the data, we want to run the preprocessing only once, i.e. we don't want to run the `A -> B` part twice. For this reason, [task_dataset\(\)](#) will try to merge graphs and cache results from graphs. However, only graphs using the same dataset can currently be merged.

Also, the shapes created during `$train()` and `$predict()` might differ. To avoid the creation of graphs where the predict shapes are incompatible with the train shapes, the hypothetical predict shapes are already calculated during `$train()` (this is why the parameters that are set during train are also used during predict) and the [PipeOpTorchModel](#) will check the train and predict shapes for compatibility before starting the training.

Otherwise, this mechanism is very similar to the [ModelDescriptor](#) construct.

Super classes

`mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpTaskPreproc -> PipeOpTaskPreprocTorch`

Active bindings

`fn` The preprocessing function.

`rowwise` Whether the preprocessing is applied rowwise.

Methods

Public methods:

- [PipeOpTaskPreprocTorch\\$new\(\)](#)
- [PipeOpTaskPreprocTorch\\$shapes_out\(\)](#)
- [PipeOpTaskPreprocTorch\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTaskPreprocTorch$new(
  fn,
  id = "preproc_torch",
  param_vals = list(),
  param_set = ps(),
  packages = character(0),
  rowwise = FALSE,
  stages_init = NULL,
  tags = NULL
)
```

Arguments:

`fn` (function or character(2))

The preprocessing function. Must not modify its input in-place. If it is a character(2), the first element should be the namespace and the second element the name. When the preprocessing function is applied to the tensor, the tensor will be passed by position as the first argument. If the `param_set` is inferred (left as NULL) it is assumed that the first argument is the `torch_tensor`.

`id` (character(1))

The id for of the new object.

`param_vals` (named list())

Parameter values to be set after construction.

`param_set` ([ParamSet](#))

In case the function `fn` takes additional parameter besides a `torch_tensor` they can be specified as parameters. None of the parameters can have the "predict" tag. All tags should include "train".

`packages` (character())

The packages the preprocessing function depends on.

`rowwise` (logical(1))

Whether the preprocessing function is applied rowwise (and then concatenated by row) or directly to the whole tensor. In the first case there is no batch dimension.

`stages_init` (character(1))

Initial value for the stages parameter.

`tags` (character())

Tags for the pipeop.

Method `shapes_out()`: Calculates the output shapes that would result in applying the preprocessing to one or more lazy tensor columns with the provided shape. Names are ignored and only order matters. It uses the parameter values that are currently set.

Usage:

```
PipeOpTaskPreprocTorch$shapes_out(shapes_in, stage = NULL, task = NULL)
```

Arguments:

shapes_in (list() of integer() or NULL)

The input input shapes of the lazy tensors. NULL indicates that the shape is unknown. First dimension must be NA (if it is not NULL).

stage (character(1))

The stage: either "train" or "predict".

task (Task or NULL)

The task, which is very rarely needed.

Returns: list() of integer() or NULL)

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTaskPreprocTorch$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
# Creating a simple task
d = data.table(
  x1 = as_lazy_tensor(rnorm(10)),
  x2 = as_lazy_tensor(rnorm(10)),
  x3 = as_lazy_tensor(as.double(1:10)),
  y = rnorm(10)
)

taskin = as_task_regr(d, target = "y")

# Creating a simple preprocessing pipeop
po_simple = po("preproc_torch",
  # get rid of environment baggage
  fn = mlr3misc::crate(function(x, a) x + a),
  param_set = paradox::ps(a = paradox::p_int(tags = c("train", "required")))
)

po_simple$param_set$set_values(
  a = 100,
  affect_columns = selector_name(c("x1", "x2")),
  stages = "both" # use during train and predict
)

taskout_train = po_simple$train(list(taskin))[[1L]]
materialize(taskout_train$data(cols = c("x1", "x2")), rbind = TRUE)

taskout_predict_noaug = po_simple$predict(list(taskin))[[1L]]
materialize(taskout_predict_noaug$data(cols = c("x1", "x2")), rbind = TRUE)
```

```

po_simple$param_set$set_values(
  stages = "train"
)

# transformation is not applied
taskout_predict_aug = po_simple$predict(list(taskin))[[1L]]
materialize(taskout_predict_aug$data(cols = c("x1", "x2")), rbind = TRUE)

# Creating a more complex preprocessing PipeOp
PipeOpPreprocTorchPoly = R6::R6Class("PipeOpPreprocTorchPoly",
  inherit = PipeOpTaskPreprocTorch,
  public = list(
    initialize = function(id = "preproc_poly", param_vals = list()) {
      param_set = paradox::ps(
        n_degree = paradox::p_int(lower = 1L, tags = c("train", "required"))
      )
      param_set$set_values(
        n_degree = 1L
      )
      fn = mlr3misc::crate(function(x, n_degree) {
        torch::torch_cat(
          lapply(seq_len(n_degree), function(d) torch_pow(x, d)),
          dim = 2L
        )
      })
      super$initialize(
        fn = fn,
        id = id,
        packages = character(0),
        param_vals = param_vals,
        param_set = param_set,
        stages_init = "both"
      )
    },
    private = list(
      .shapes_out = function(shapes_in, param_vals, task) {
        # shapes_in is a list of length 1 containing the shapes
        checkmate::assert_true(length(shapes_in[[1L]]) == 2L)
        if (shapes_in[[1L]][2L] != 1L) {
          stop("Input shape must be (NA, 1)")
        }
        list(c(NA, param_vals$n_degree))
      }
    )
  )

po_poly = PipeOpPreprocTorchPoly$new(
  param_vals = list(n_degree = 3L, affect_columns = selector_name("x3"))
)

po_poly$shapes_out(list(c(NA, 1L)), stage = "train")

```

```
taskout = po_poly$train(list(taskin))[[1L]]
materialize(taskout$data(cols = "x3"), rbind = TRUE)
```

```
mlr_pipeops_preproc_torch.augment_center_crop
  PipeOpPreprocTorchAugmentCenterCrop
```

Description

Calls `torchvision::transform_center_crop`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels
size	untyped	-	
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

```
mlr_pipeops_preproc_torch.augment_color_jitter
  PipeOpPreprocTorchAugmentColorJitter
```

Description

Calls `torchvision::transform_color_jitter`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels	Range
brightness	numeric	0		$[0, \infty)$
contrast	numeric	0		$[0, \infty)$
saturation	numeric	0		$[0, \infty)$
hue	numeric	0		$[0, \infty)$
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

mlr_pipeops_preproc_torch.augment_crop

PipeOpPreprocTorchAugmentCrop

Description

Calls `torchvision::transform_crop`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels	Range
top	integer	-		$(-\infty, \infty)$
left	integer	-		$(-\infty, \infty)$
height	integer	-		$(-\infty, \infty)$
width	integer	-		$(-\infty, \infty)$
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

```
mlr_pipeops_preproc_torch.augment_hflip
  PipeOpPreprocTorchAugmentHflip
```

Description

Calls `torchvision::transform_hflip`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

```
mlr_pipeops_preproc_torch.augment_random_affine
  PipeOpPreprocTorchAugmentRandomAffine
```

Description

Calls `torchvision::transform_random_affine`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels	Range
degrees	untyped	-		-
translate	untyped	NULL		-
scale	untyped	NULL		-
resample	integer	0		$(-\infty, \infty)$
fillcolor	untyped	0		-
stages	character	-	train, predict, both	-

affect_columns untyped selector_all() -

mlr_pipeops_preproc_torch.augment_random_choice
PipeOpPreprocTorchAugmentRandomChoice

Description

Calls [torchvision::transform_random_choice](#), see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels
transforms	untyped	-	
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

mlr_pipeops_preproc_torch.augment_random_crop
PipeOpPreprocTorchAugmentRandomCrop

Description

Calls [torchvision::transform_random_crop](#), see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels
size	untyped	-	
padding	untyped	NULL	
pad_if_needed	logical	FALSE	TRUE, FALSE
fill	untyped	0L	
padding_mode	character	constant	constant, edge, reflect, symmetric
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

mlr_pipeops_preproc_torch.augment_random_horizontal_flip

PipeOpPreprocTorchAugmentRandomHorizontalFlip

Description

Calls [torchvision::transform_random_horizontal_flip](#), see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels	Range
p	numeric	0.5		[0, 1]
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

```
mlr_pipeops_preproc_torch.augment_random_order
      PipeOpPreprocTorchAugmentRandomOrder
```

Description

Calls `torchvision::transform_random_order`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels
transforms	untyped	-	
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

```
mlr_pipeops_preproc_torch.augment_random_resized_crop
      PipeOpPreprocTorchAugmentRandomResizedCrop
```

Description

Calls `torchvision::transform_random_resized_crop`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels	Range
size	untyped	-		-
scale	untyped	c(0.08, 1)		-
ratio	untyped	c(3/4, 4/3)		-
interpolation	integer	2		[0, 3]
stages	character	-	train, predict, both	-

affect_columns untyped selector_all() -

mlr_pipeops_preproc_torch.augment_random_vertical_flip
PipeOpPreprocTorchAugmentRandomVerticalFlip

Description

Calls `torchvision::transform_random_vertical_flip`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels	Range
p	numeric	0.5		[0, 1]
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

mlr_pipeops_preproc_torch.augment_resized_crop
PipeOpPreprocTorchAugmentResizedCrop

Description

Calls `torchvision::transform_resized_crop`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels	Range
top	integer	-		$(-\infty, \infty)$
left	integer	-		$(-\infty, \infty)$
height	integer	-		$(-\infty, \infty)$
width	integer	-		$(-\infty, \infty)$
size	untyped	-		-
interpolation	integer	2		[0, 3]
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

```
mlr_pipeops_preproc_torch.augment_rotate
```

```
PipeOpPreprocTorchAugmentRotate
```

Description

Calls `torchvision::transform_rotate`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels	Range
angle	untyped	-		-
resample	integer	0		$(-\infty, \infty)$
expand	logical	FALSE	TRUE, FALSE	-
center	untyped	NULL		-
fill	untyped	NULL		-
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

```
mlr_pipeops_preproc_torch.augment_vflip
  PipeOpPreprocTorchAugmentVflip
```

Description

Calls `torchvision::transform_vflip`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

```
mlr_pipeops_preproc_torch.trafo_adjust_brightness
  PipeOpPreprocTorchTrafoAdjustBrightness
```

Description

Calls `torchvision::transform_adjust_brightness`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels	Range
brightness_factor	numeric	-		$[0, \infty)$
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

```
mlr_pipeops_preproc_torch.trafo_adjust_gamma
      PipeOpPreprocTorchTrafoAdjustGamma
```

Description

Calls `torchvision::transform_adjust_gamma`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels	Range
gamma	numeric	-		$[0, \infty)$
gain	numeric	1		$(-\infty, \infty)$
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

```
mlr_pipeops_preproc_torch.trafo_adjust_hue
      PipeOpPreprocTorchTrafoAdjustHue
```

Description

Calls `torchvision::transform_adjust_hue`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels	Range
hue_factor	numeric	-		$[-0.5, 0.5]$
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

```
mlr_pipeops_preproc_torch.trafo_adjust_saturation
    PipeOpPreprocTorchTrafoAdjustSaturation
```

Description

Calls `torchvision::transform_adjust_saturation`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels	Range
saturation_factor	numeric	-		$(-\infty, \infty)$
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

```
mlr_pipeops_preproc_torch.trafo_grayscale
    PipeOpPreprocTorchTrafoGrayscale
```

Description

Calls `torchvision::transform_grayscale`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels	Range
num_output_channels	integer	-		[1, 3]
stages	character	-	train, predict, both	-
affect_columns	untyped	selector_all()		-

```
mlr_pipeops_preproc_torch.trafo_nop
      PipeOpPreprocTorchTrafoNop
```

Description

Does nothing.

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

```
mlr_pipeops_preproc_torch.trafo_normalize
      PipeOpPreprocTorchTrafoNormalize
```

Description

Calls [torchvision::transform_normalize](#), see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels
mean	untyped	-	
std	untyped	-	
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

```
mlr_pipeops_preproc_torch.trafo_pad
  PipeOpPreprocTorchTrafoPad
```

Description

Calls `torchvision::transform_pad`, see there for more information on the parameters. The pre-processing is applied row wise (no batch dimension).

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

Id	Type	Default	Levels
padding	untyped	-	
fill	untyped	0	
padding_mode	character	constant	constant, edge, reflect, symmetric
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

```
mlr_pipeops_preproc_torch.trafo_reshape
  PipeOpPreprocTorchTrafoReshape
```

Description

Reshapes the tensor according to the parameter shape, by calling `torch_reshape()`. This pre-processing function is applied batch-wise.

Format

`R6Class` inheriting from `PipeOpTaskPreprocTorch`.

Parameters

- `shape :: integer()`
The desired output shape. The first dimension is the batch dimension and should usually be -1.

mlr_pipeops_preproc_torch.trafo_resize
PipeOpPreprocTorchTrafoResize

Description

Calls `torchvision::transform_resize`, see there for more information on the parameters. The preprocessing is applied to the whole batch.

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels
size	untyped	-	
interpolation	character	2	Undefined, Bartlett, Blackman, Bohman, Box, Catrom, Cosine, Cubic, Gaussian
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

mlr_pipeops_preproc_torch.trafo_rgb_to_grayscale
PipeOpPreprocTorchTrafoRgbToGrayscale

Description

Calls `torchvision::transform_rgb_to_grayscale`, see there for more information on the parameters. The preprocessing is applied row wise (no batch dimension).

Format

[R6Class](#) inheriting from [PipeOpTaskPreprocTorch](#).

Parameters

Id	Type	Default	Levels
stages	character	-	train, predict, both
affect_columns	untyped	selector_all()	

Description

PipeOpTorch is the base class for all [PipeOps](#) that represent neural network layers in a [Graph](#). During **training**, it generates a [PipeOpModule](#) that wraps an [nn_module](#) and attaches it to the architecture, which is also represented as a [Graph](#) consisting mostly of [PipeOpModules](#) and [PipeOpNOPs](#).

While the former [Graph](#) operates on [ModelDescriptors](#), the latter operates on [tensors](#).

The relationship between a PipeOpTorch and a [PipeOpModule](#) is similar to the relationship between a [nn_module_generator](#) (like [nn_linear](#)) and a [nn_module](#) (like the output of `nn_linear(...)`). A crucial difference is that the PipeOpTorch infers auxiliary parameters (like `in_features` for `nn_linear`) automatically from the intermediate tensor shapes that are being communicated through the [ModelDescriptor](#).

During **prediction**, PipeOpTorch takes in a [Task](#) in each channel and outputs the same new [Task](#) resulting from their [feature union](#) in each channel. If there is only one input and output channel, the task is simply piped through.

Inheriting

When inheriting from this class, one should overload either the `private$.shapes_out()` and the `private$.shape_dependent_params()` methods, or overload `private$.make_module()`.

- `.make_module(shapes_in, param_vals, task)`
`(list(), list()) -> nn_module`
 This private method is called to generate the `nn_module` that is passed as argument `module` to [PipeOpModule](#). It must be overwritten, when no `module_generator` is provided. If left as is, it calls the provided `module_generator` with the arguments obtained by the private method `.shape_dependent_params()`.
- `.shapes_out(shapes_in, param_vals, task)`
`(list(), list(), Task or NULL) -> named list()`
 This private method gets a list of numeric vectors (`shapes_in`), the parameter values (`param_vals`), as well as an (optional) [Task](#). The `shapes_in` can be assumed to be in the same order as the input names of the PipeOp. The output shapes must be in the same order as the output names of the PipeOp. In case the output shapes depends on the task (as is the case for [PipeOpTorchHead](#)), the function should return valid output shapes (possibly containing NAs) if the task argument is provided or not.
- `.shape_dependent_params(shapes_in, param_vals, task)`
`(list(), list()) -> named list()`
 This private method has the same inputs as `.shapes_out`. If `.make_module()` is not overwritten, it constructs the arguments passed to `module_generator`. Usually this means that it must infer the auxiliary parameters that can be inferred from the input shapes and add it to the user-supplied parameter values (`param_vals`).

Input and Output Channels

During *training*, all inputs and outputs are of class `ModelDescriptor`. During *prediction*, all input and output channels are of class `Task`.

State

The state is the value calculated by the public method `shapes_out()`.

Parameters

The `ParamSet` is specified by the child class inheriting from `PipeOpTorch`. Usually the parameters are the arguments of the wrapped `nn_module` minus the auxiliary parameter that can be automatically inferred from the shapes of the input tensors.

Internals

During training, the `PipeOpTorch` creates a `PipeOpModule` for the given parameter specification and the input shapes from the incoming `ModelDescriptors` using the private method `.make_module()`. The input shapes are provided by the slot `pointer_shape` of the incoming `ModelDescriptors`. The channel names of this `PipeOpModule` are identical to the channel names of the generating `PipeOpTorch`.

A `model descriptor union` of all incoming `ModelDescriptors` is then created. Note that this modifies the `graph` of the first `ModelDescriptor` **in place** for efficiency. The `PipeOpModule` is added to the `graph` slot of this union and the edges that connect the sending `PipeOpModules` to the input channel of this `PipeOpModule` are added to the graph. This is possible because every incoming `ModelDescriptor` contains the information about the id and the channel name of the sending `PipeOp` in the slot `pointer`.

The new graph in the `model_descriptor_union` represents the current state of the neural network architecture. It is structurally similar to the subgraph that consists of all pipeops of class `PipeOpTorch` and `PipeOpTorchIngress` that are ancestors of this `PipeOpTorch`.

For the output, a shallow copy of the `ModelDescriptor` is created and the `pointer` and `pointer_shape` are updated accordingly. The shallow copy means that all `ModelDescriptors` point to the same `Graph` which allows the graph to be modified by-reference in different parts of the code.

Super class

```
mlr3pipelines::PipeOp -> PipeOpTorch
```

Public fields

`module_generator` (`nn_module_generator` or `NULL`)

The module generator wrapped by this `PipeOpTorch`. If `NULL`, the private method `private$.make_module(shapes_in, param_vals)` must be overwritten, see section 'Inheriting'. Do not change this after construction.

Methods

Public methods:

- `PipeOpTorch$new()`
- `PipeOpTorch$shapes_out()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorch$new(
  id,
  module_generator,
  param_set = ps(),
  param_vals = list(),
  inname = "input",
  outname = "output",
  packages = "torch",
  tags = NULL
)
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`module_generator` (`nn_module_generator`)

The torch module generator.

`param_set` (`ParamSet`)

The parameter set.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

`inname` (`character()`)

The names of the `PipeOp`'s input channels. These will be the input channels of the generated `PipeOpModule`. Unless the wrapped `module_generator`'s forward method (if present) has the argument `...`, `inname` must be identical to those argument names in order to avoid any ambiguity.

If the forward method has the argument `...`, the order of the input channels determines how the tensors will be passed to the wrapped `nn_module`.

If left as `NULL` (default), the argument `module_generator` must be given and the argument names of the `module_generator`'s forward function are set as `inname`.

`outname` (`character()`)

The names of the output channels channels. These will be the output channels of the generated `PipeOpModule` and therefore also the names of the list returned by its `$train()`. In case there is more than one output channel, the `nn_module` that is constructed by this `PipeOp` during training must return a named `list()`, where the names of the list are the names of the output channels. The default is "output".

`packages` (`character()`)

The R packages this object depends on.

`tags` (`character()`)

The tags of the `PipeOp`. The tag "torch" is always added.

Method `shapes_out()`: Calculates the output shapes for the given input shapes, parameters and task.

Usage:

```
PipeOpTorch$shapes_out(shapes_in, task = NULL)
```

Arguments:

`shapes_in` (`list()` of `integer()`)

The input input shapes, which must be in the same order as the input channel names of the PipeOp.

`task` (`Task` or `NULL`)

The task, which is very rarely used (default is `NULL`). An exception is `PipeOpTorchHead`.

Returns: A named `list()` containing the output shapes. The names are the names of the output channels of the PipeOp.

See Also

Other Graph Network: `ModelDescriptor()`, `TorchIngressToken()`, `mlr_learners_torch_model`, `mlr_pipeops_module`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_num`, `model_descriptor_to_learner()`, `model_descriptor_to_module()`, `model_descriptor_union()`, `nn_graph()`

Examples

```
## Creating a neural network
# In torch

task = tsk("iris")

network_generator = torch::nn_module(
  initialize = function(task, d_hidden) {
    d_in = length(task$feature_names)
    self$linear = torch::nn_linear(d_in, d_hidden)
    self$output = if (task$task_type == "regr") {
      torch::nn_linear(d_hidden, 1)
    } else if (task$task_type == "classif") {
      torch::nn_linear(d_hidden, length(task$class_names))
    }
  },
  forward = function(x) {
    x = self$linear(x)
    x = torch::nnf_relu(x)
    self$output(x)
  }
)

network = network_generator(task, d_hidden = 50)
x = torch::torch_tensor(as.matrix(task$data(1, task$feature_names)))
y = torch::with_no_grad(network(x))

# In mlr3torch
```

```

network_generator = po("torch_ingress_num") %>>%
  po("nn_linear", out_features = 50) %>>%
  po("nn_head")
md = network_generator$train(task)[[1L]]
network = model_descriptor_to_module(md)
y = torch::with_no_grad(network(torch_ingress_num.input = x))

## Implementing a custom PipeOpTorch

# defining a custom module
nn_custom = nn_module("nn_custom",
  initialize = function(d_in1, d_in2, d_out1, d_out2, bias = TRUE) {
    self$linear1 = nn_linear(d_in1, d_out1, bias)
    self$linear2 = nn_linear(d_in2, d_out2, bias)
  },
  forward = function(input1, input2) {
    output1 = self$linear1(input1)
    output2 = self$linear1(input2)

    list(output1 = output1, output2 = output2)
  }
)

# wrapping the module into a custom PipeOpTorch

library(paradox)

PipeOpTorchCustom = R6::R6Class("PipeOpTorchCustom",
  inherit = PipeOpTorch,
  public = list(
    initialize = function(id = "nn_custom", param_vals = list()) {
      param_set = ps(
        d_out1 = p_int(lower = 1, tags = c("required", "train")),
        d_out2 = p_int(lower = 1, tags = c("required", "train")),
        bias = p_lgl(default = TRUE, tags = "train")
      )
      super$initialize(
        id = id,
        param_vals = param_vals,
        param_set = param_set,
        inname = c("input1", "input2"),
        outname = c("output1", "output2"),
        module_generator = nn_custom
      )
    }
  ),
  private = list(
    .shape_dependent_params = function(shapes_in, param_vals, task) {
      c(param_vals,
        list(d_in1 = tail(shapes_in[["input1"]], 1), d_in2 = tail(shapes_in[["input2"]], 1)
        )
      )
    }
  )
)

```

```

    },
    .shapes_out = function(shapes_in, param_vals, task) {
      list(
        input1 = c(head(shapes_in[["input1"]], -1), param_vals$d_out1),
        input2 = c(head(shapes_in[["input2"]], -1), param_vals$d_out2)
      )
    }
  )
)

## Training

# generate input
task = tsk("iris")
task1 = task$clone()$select(paste0("Sepal.", c("Length", "Width")))
task2 = task$clone()$select(paste0("Petal.", c("Length", "Width")))
graph = gunion(list(po("torch_ingress_num_1"), po("torch_ingress_num_2")))
mds_in = graph$train(list(task1, task2), single_input = FALSE)

mds_in[[1L]][c("graph", "task", "ingress", "pointer", "pointer_shape")]
mds_in[[2L]][c("graph", "task", "ingress", "pointer", "pointer_shape")]

# creating the PipeOpTorch and training it
po_torch = PipeOpTorchCustom$new()
po_torch$param_set$values = list(d_out1 = 10, d_out2 = 20)
train_input = list(input1 = mds_in[[1L]], input2 = mds_in[[2L]])
mds_out = do.call(po_torch$train, args = list(input = train_input))
po_torch$state

# the new model descriptors

# the resulting graphs are identical
identical(mds_out[[1L]]$graph, mds_out[[2L]]$graph)
# not that as a side-effect, also one of the input graphs is modified in-place for efficiency
mds_in[[1L]]$graph$edges

# The new task has both Sepal and Petal features
identical(mds_out[[1L]]$task, mds_out[[2L]]$task)
mds_out[[2L]]$task

# The new ingress slot contains all ingressors
identical(mds_out[[1L]]$ingress, mds_out[[2L]]$ingress)
mds_out[[1L]]$ingress

# The pointer and pointer_shape slots are different
mds_out[[1L]]$pointer
mds_out[[2L]]$pointer

mds_out[[1L]]$pointer_shape
mds_out[[2L]]$pointer_shape

## Prediction
predict_input = list(input1 = task1, input2 = task2)

```

```
tasks_out = do.call(po_torch$predict, args = list(input = predict_input))
identical(tasks_out[[1L]], tasks_out[[2L]])
```

```
mlr_pipeops_torch_callbacks
      Callback Configuration
```

Description

Configures the callbacks of a deep learning model.

Input and Output Channels

There is one input channel "input" and one output channel "output". During *training*, the channels are of class [ModelDescriptor](#). During *prediction*, the channels are of class [Task](#).

State

The state is the value calculated by the public method `shapes_out()`.

Parameters

The parameters are defined dynamically from the callbacks, where the id of the respective callbacks is the respective set id.

Internals

During training the callbacks are cloned and added to the [ModelDescriptor](#).

Super class

```
mlr3pipelines::PipeOp -> PipeOpTorchCallbacks
```

Methods

Public methods:

- [PipeOpTorchCallbacks\\$new\(\)](#)
- [PipeOpTorchCallbacks\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PipeOpTorchCallbacks$new(
  callbacks = list(),
  id = "torch_callbacks",
  param_vals = list()
)
```

Arguments:

callbacks (list of [TorchCallbacks](#))

The callbacks (or something convertible via [as_torch_callbacks\(\)](#)). Must have unique ids. All callbacks are cloned during construction.

id (character(1))

Identifier of the resulting object.

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchCallbacks$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Model Configuration: [ModelDescriptor\(\)](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_optimizer](#), [model_descriptor_union\(\)](#)

Other PipeOp: [mlr_pipeops_module](#), [mlr_pipeops_torch_optimizer](#)

Examples

```
po_cb = po("torch_callbacks", "checkpoint")
po_cb$param_set
mdin = po("torch_ingress_num")$train(list(tsk("iris")))
mdin[[1L]]$callbacks
mdout = po_cb$train(mdin)[[1L]]
mdout$callbacks
# Can be called again
po_cb1 = po("torch_callbacks", t_clbk("progress"))
mdout1 = po_cb1$train(list(mdout))[[1L]]
mdout1$callbacks
```

mlr_pipeops_torch_ingress

Entrypoint to Torch Network

Description

Use this as entry-point to mlr3torch-networks. Unless you are an advanced user, you should not need to use this directly but [PipeOpTorchIngressNumeric](#), [PipeOpTorchIngressCategorical](#) or [PipeOpTorchIngressLazyTensor](#).

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is set to the input shape.

Parameters

Defined by the construction argument `param_set`.

Internals

Creates an object of class [TorchIngressToken](#) for the given task. The purpose of this is to store the information on how to construct the torch dataloader from the task for this entry point of the network.

Super class

`mlr3pipelines::PipeOp` -> `PipeOpTorchIngress`

Active bindings

`feature_types` (`character(1)`)

The features types that can be consumed by this `PipeOpTorchIngress`.

Methods**Public methods:**

- [PipeOpTorchIngress\\$new\(\)](#)
- [PipeOpTorchIngress\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PipeOpTorchIngress$new(
  id,
  param_set = ps(),
  param_vals = list(),
  packages = character(0),
  feature_types
)
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_set` ([ParamSet](#))

The parameter set.

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

packages (character())

The R packages this object depends on.

feature_types (character())

The feature types. See [mlr_reflections\\$task_feature_types](#) for available values. Additionally, "lazy_tensor" is supported.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchIngress$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr_learners_torch_model](#), [mlr_pipeops_module](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [model_descriptor_to_learner\(\)](#), [model_descriptor_to_module\(\)](#), [model_descriptor_union\(\)](#), [nn_graph\(\)](#)

mlr_pipeops_torch_ingress_categ

Torch Entry Point for Categorical Features

Description

Ingress PipeOp that represents a categorical (factor()), ordered() and logical()) entry point to a torch network.

Parameters

- `select :: logical(1)`
Whether PipeOp should selected the supported feature types. Otherwise it will err on receiving tasks with unsupported feature types.

Internals

Uses `batchgetter_categ()`.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is set to the input shape.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorchIngress -> PipeOpTorchIngressCategorical`

Methods**Public methods:**

- `PipeOpTorchIngressCategorical$new()`
- `PipeOpTorchIngressCategorical$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchIngressCategorical$new(
  id = "torch_ingress_categ",
  param_vals = list()
)
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchIngressCategorical$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Other Graph Network: `ModelDescriptor()`, `TorchIngressToken()`, `mlr_learners_torch_model`, `mlr_pipeops_module`, `mlr_pipeops_torch`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `model_descriptor_to_learner()`, `model_descriptor_to_module()`, `model_descriptor_union()`, `nn_graph()`

Examples

```
graph = po("select", selector = selector_type("factor")) %>>%
  po("torch_ingress_categ")
task = tsk("german_credit")
# The output is a model descriptor
md = graph$train(task)[[1L]]
ingress = md$ingress[[1L]]
ingress$batchgetter(task$data(1, ingress$features), "cpu")
```

```
mlr_pipeops_torch_ingress_ltnsr
```

Ingress for Lazy Tensor

Description

Ingress for a single `lazy_tensor` column.

Parameters

- `shape :: integer()`
The shape of the tensor, where the first dimension (batch) must be NA. When it is not specified, the lazy tensor input column needs to have a known shape.

Internals

The returned batchgetter materializes the lazy tensor column to a tensor.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is set to the input shape.

Super classes

`mlr3pipelines::PipeOp -> mlr3torch::PipeOpTorchIngress -> PipeOpTorchIngressLazyTensor`

Methods**Public methods:**

- `PipeOpTorchIngressLazyTensor$new()`
- `PipeOpTorchIngressLazyTensor$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchIngressLazyTensor$new(
  id = "torch_ingress_ltnsr",
  param_vals = list()
)
```

Arguments:

`id` (character(1))

Identifier of the resulting object.

`param_vals` (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchIngressLazyTensor$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model_classif`, `mlr_pipeops_torch_model_regr`

Other Graph Network: `ModelDescriptor()`, `TorchIngressToken()`, `mlr_learners_torch_model`, `mlr_pipeops_module`, `mlr_pipeops_torch`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_num`, `model_descriptor_to_learner()`, `model_descriptor_to_module()`, `model_descriptor_union()`, `nn_graph()`

Examples

```
po_ingress = po("torch_ingress_ltnsr")
task = tsk("lazy_iris")

md = po_ingress$train(list(task))[[1L]]

ingress = md$ingress
x_batch = ingress[[1L]]$batchgetter(data = task$data(1, "x"), device = "cpu", cache = NULL)
x_batch

# Now we try a lazy tensor with unknown shape, i.e. the shapes between the rows can differ

ds = dataset(
  initialize = function() self$x = list(torch_randn(3, 10, 10), torch_randn(3, 8, 8)),
  .getitem = function(i) list(x = self$x[[i]]),
  .length = function() 2)()

task_unknown = as_task_regr(data.table(
  x = as_lazy_tensor(ds, dataset_shapes = list(x = NULL)),
  y = rnorm(2)
), target = "y", id = "example2")

# this task (as it is) can NOT be processed by PipeOpTorchIngressLazyTensor
# It therefore needs to be preprocessed
po_resize = po("trafo_resize", size = c(6, 6))
task_unknown_resize = po_resize$train(list(task_unknown))[[1L]]
```

```

# printing the transformed column still shows unknown shapes,
# because the preprocessing pipeop cannot infer them,
# however we know that the shape is now (3, 10, 10) for all rows
task_unknown_resize$data(1:2, "x")
po_ingress$param_set$set_values(shape = c(NA, 3, 6, 6))

md2 = po_ingress$train(list(task_unknown_resize))[[1L]]

ingress2 = md2$ingress
x_batch2 = ingress2[[1L]]$batchgetter(
  data = task_unknown_resize$data(1:2, "x"),
  device = "cpu",
  cache = NULL
)

x_batch2

```

mlr_pipeops_torch_ingress_num

Torch Entry Point for Numeric Features

Description

Ingress PipeOp that represents a numeric (`integer()` and `numeric()`) entry point to a torch network.

Internals

Uses [batchgetter_num\(\)](#).

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is set to the input shape.

Super classes

[mlr3pipelines::PipeOp](#) -> [mlr3torch::PipeOpTorchIngress](#) -> [PipeOpTorchIngressNumeric](#)

Methods**Public methods:**

- [PipeOpTorchIngressNumeric\\$new\(\)](#)
- [PipeOpTorchIngressNumeric\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchIngressNumeric$new(id = "torch_ingress_num", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchIngressNumeric$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr_learners_torch_model](#), [mlr_pipeops_module](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [model_descriptor_to_learner\(\)](#), [model_descriptor_to_module\(\)](#), [model_descriptor_union\(\)](#), [nn_graph\(\)](#)

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Examples

```
graph = po("select", selector = selector_type(c("numeric", "integer"))) %>%
  po("torch_ingress_num")
task = tsk("german_credit")
# The output is a model descriptor
md = graph$train(task)[[1L]]
ingress = md$ingress[[1L]]
ingress$batchgetter(task$data(1:5, ingress$features), "cpu")
```

mlr_pipeops_torch_loss

Loss Configuration

Description

Configures the loss of a deep learning model.

Input and Output Channels

One input channel called "input" and one output channel called "output". For an explanation see [PipeOpTorch](#).

State

The state is the value calculated by the public method `shapes_out()`.

Parameters

The parameters are defined dynamically from the loss set during construction.

Internals

During training the loss is cloned and added to the [ModelDescriptor](#).

Super class

[mlr3pipelines::PipeOp](#) -> [PipeOpTorchLoss](#)

Methods**Public methods:**

- [PipeOpTorchLoss\\$new\(\)](#)
- [PipeOpTorchLoss\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PipeOpTorchLoss$new(loss, id = "torch_loss", param_vals = list())
```

Arguments:

loss ([TorchLoss](#) or character(1) or nn_loss)

The loss (or something convertible via [as_torch_loss\(\)](#)).

id (character(1))

Identifier of the resulting object.

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchLoss$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model_classif](#), [mlr_pipeops_torch_model_regr](#)

Other Model Configuration: [ModelDescriptor\(\)](#), [mlr_pipeops_torch_callbacks](#), [mlr_pipeops_torch_optimizer](#), [model_descriptor_union\(\)](#)

Examples

```
po_loss = po("torch_loss", loss = t_loss("cross_entropy"))
po_loss$param_set
mdin = po("torch_ingress_num")$train(list(tsk("iris")))
mdin[[1L]]$loss
mdout = po_loss$train(mdin)[[1L]]
mdout$loss
```

mlr_pipeops_torch_model

PipeOp Torch Model

Description

Builds a Torch Learner from a [ModelDescriptor](#) and trains it with the given parameter specification. The task type must be specified during construction.

Input and Output Channels

There is one input channel "input" that takes in [ModelDescriptor](#) during training and a [Task](#) of the specified task_type during prediction. The output is NULL during training and a [Prediction](#) of given task_type during prediction.

State

A trained [LearnerTorchModel](#).

Parameters

General:

The parameters of the optimizer, loss and callbacks, prefixed with "opt.", "loss." and "cb.<callback id>." respectively, as well as:

- epochs :: integer(1)
The number of epochs.
- device :: character(1)
The device. One of "auto", "cpu", or "cuda" or other values defined in `mlr_reflections$torch$devices`. The value is initialized to "auto", which will select "cuda" if possible, then try "mps" and otherwise fall back to "cpu".
- num_threads :: integer(1)
The number of threads for intraop parallelization (if device is "cpu"). This value is initialized to 1.
- seed :: integer(1) or "random"
The seed that is used during training and prediction. This value is initialized to "random", which means that a random seed will be sampled at the beginning of the training phase. This seed (either set or randomly sampled) is available via `$model$seed` after training and used during prediction. Note that by setting the seed during the training phase this will mean that by default (i.e. when seed is "random"), clones of the learner will use a different seed.

Evaluation:

- measures_train :: [Measure](#) or list() of [Measures](#).
Measures to be evaluated during training.
- measures_valid :: [Measure](#) or list() of [Measures](#).
Measures to be evaluated during validation.

- `eval_freq :: integer(1)`
How often the train / validation predictions are evaluated using `measures_train/measures_valid`. This is initialized to 1. Note that the final model is always evaluated.

Early Stopping:

- `patience :: integer(1)`
This activates early stopping using the validation scores. If the performance of a model does not improve for `patience` evaluation steps, training is ended. Note that the final model is stored in the learner, not the best model. This is initialized to 0, which means no early stopping. The first entry from `measures_valid` is used as the metric. This also requires to specify the `$validate` field of the Learner, as well as `measures_valid`.
- `min_delta :: double(1)`
The minimum improvement threshold (>) for early stopping. Is initialized to 0.

Dataloader:

- `batch_size :: integer(1)`
The batch size (required).
- `shuffle :: logical(1)`
Whether to shuffle the instances in the dataset. Default is FALSE. This does not impact validation.
- `sampler :: torch::sampler`
Object that defines how the dataloader draw samples.
- `batch_sampler :: torch::sampler`
Object that defines how the dataloader draws batches.
- `num_workers :: integer(1)`
The number of workers for data loading (batches are loaded in parallel). The default is 0, which means that data will be loaded in the main process.
- `collate_fn :: function`
How to merge a list of samples to form a batch.
- `pin_memory :: logical(1)`
Whether the dataloader copies tensors into CUDA pinned memory before returning them.
- `drop_last :: logical(1)`
Whether to drop the last training batch in each epoch during training. Default is FALSE.
- `timeout :: numeric(1)`
The timeout value for collecting a batch from workers. Negative values mean no timeout and the default is -1.
- `worker_init_fn :: function(id)`
A function that receives the worker id (in `[1, num_workers]`) and is executed after seeding on the worker but before data loading.
- `worker_globals :: list() | character()`
When loading data in parallel, this allows to export globals to the workers. If this is a character vector, the objects in the global environment with those names are copied to the workers.
- `worker_packages :: character()`
Which packages to load on the workers.

Also see `torch::dataloader` for more information.

Internals

A `LearnerTorchModel` is created by calling `model_descriptor_to_learner()` on the provided `ModelDescriptor` that is received through the input channel. Then the parameters are set according to the parameters specified in `PipeOpTorchModel` and its `'$train()` method is called on the `[Task][mlr3::Task]` stored

Super classes

```
mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpLearner -> PipeOpTorchModel
```

Methods

Public methods:

- `PipeOpTorchModel$new()`
- `PipeOpTorchModel$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchModel$new(task_type, id = "torch_model", param_vals = list())
```

Arguments:

`task_type` (`character(1)`)

The task type of the model.

`id` (`character(1)`)

Identifier of the resulting object.

`param_vals` (`list()`)

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchModel$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`,

```
mlr_pipeops_nn_softmax, mlr_pipeops_nn_softplus, mlr_pipeops_nn_softshrink, mlr_pipeops_nn_softsign,
mlr_pipeops_nn_squeeze, mlr_pipeops_nn_tanh, mlr_pipeops_nn_tanhshrink, mlr_pipeops_nn_threshold,
mlr_pipeops_torch_ingress, mlr_pipeops_torch_ingress_categ, mlr_pipeops_torch_ingress_ltnsr,
mlr_pipeops_torch_ingress_num, mlr_pipeops_torch_loss, mlr_pipeops_torch_model_classif,
mlr_pipeops_torch_model_regr
```

```
mlr_pipeops_torch_model_classif
  PipeOp Torch Classifier
```

Description

Builds a torch classifier and trains it.

Parameters

See [LearnerTorch](#)

Input and Output Channels

There is one input channel "input" that takes in `ModelDescriptor` during training and a `Task` of the specified `task_type` during prediction. The output is `NULL` during training and a `Prediction` of given `task_type` during prediction.

State

A trained [LearnerTorchModel](#).

Internals

A [LearnerTorchModel](#) is created by calling `model_descriptor_to_learner()` on the provided [ModelDescriptor](#) that is received through the input channel. Then the parameters are set according to the parameters specified in `PipeOpTorchModel` and its `'$train()` method is called on the `[Task][mlr3::Task]` stored

Super classes

```
mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpLearner -> mlr3torch::PipeOpTorchModel
-> PipeOpTorchModelClassif
```

Methods

Public methods:

- `PipeOpTorchModelClassif$new()`
- `PipeOpTorchModelClassif$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PipeOpTorchModelClassif$new(id = "torch_model_classif", param_vals = list())
```

Arguments:

```
id (character(1))
```

Identifier of the resulting object.

```
param_vals (list())
```

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchModelClassif$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOps: `mlr_pipeops_nn_avg_pool1d`, `mlr_pipeops_nn_avg_pool2d`, `mlr_pipeops_nn_avg_pool3d`, `mlr_pipeops_nn_batch_norm1d`, `mlr_pipeops_nn_batch_norm2d`, `mlr_pipeops_nn_batch_norm3d`, `mlr_pipeops_nn_block`, `mlr_pipeops_nn_celu`, `mlr_pipeops_nn_conv1d`, `mlr_pipeops_nn_conv2d`, `mlr_pipeops_nn_conv3d`, `mlr_pipeops_nn_conv_transpose1d`, `mlr_pipeops_nn_conv_transpose2d`, `mlr_pipeops_nn_conv_transpose3d`, `mlr_pipeops_nn_dropout`, `mlr_pipeops_nn_elu`, `mlr_pipeops_nn_flatten`, `mlr_pipeops_nn_gelu`, `mlr_pipeops_nn_glu`, `mlr_pipeops_nn_hardshrink`, `mlr_pipeops_nn_hardsigmoid`, `mlr_pipeops_nn_hardtanh`, `mlr_pipeops_nn_head`, `mlr_pipeops_nn_layer_norm`, `mlr_pipeops_nn_leaky_relu`, `mlr_pipeops_nn_linear`, `mlr_pipeops_nn_log_sigmoid`, `mlr_pipeops_nn_max_pool1d`, `mlr_pipeops_nn_max_pool2d`, `mlr_pipeops_nn_max_pool3d`, `mlr_pipeops_nn_merge`, `mlr_pipeops_nn_merge_cat`, `mlr_pipeops_nn_merge_prod`, `mlr_pipeops_nn_merge_sum`, `mlr_pipeops_nn_prelu`, `mlr_pipeops_nn_relu`, `mlr_pipeops_nn_relu6`, `mlr_pipeops_nn_reshape`, `mlr_pipeops_nn_rrelu`, `mlr_pipeops_nn_selu`, `mlr_pipeops_nn_sigmoid`, `mlr_pipeops_nn_softmax`, `mlr_pipeops_nn_softplus`, `mlr_pipeops_nn_softshrink`, `mlr_pipeops_nn_softsign`, `mlr_pipeops_nn_squeeze`, `mlr_pipeops_nn_tanh`, `mlr_pipeops_nn_tanhshrink`, `mlr_pipeops_nn_threshold`, `mlr_pipeops_torch_ingress`, `mlr_pipeops_torch_ingress_categ`, `mlr_pipeops_torch_ingress_ltnsr`, `mlr_pipeops_torch_ingress_num`, `mlr_pipeops_torch_loss`, `mlr_pipeops_torch_model`, `mlr_pipeops_torch_model`.

Examples

```
# simple logistic regression

# configure the model descriptor
md = as_graph(po("torch_ingress_num") %>>%
  po("nn_head") %>>%
  po("torch_loss", "cross_entropy") %>>%
  po("torch_optimizer", "adam"))$train(tsk("iris"))[[1L]]

print(md)

# build the learner from the model descriptor and train it
po_model = po("torch_model_classif", batch_size = 50, epochs = 1)
po_model$train(list(md))
po_model$state
```

mlr_pipeops_torch_model_regr
Torch Regression Model

Description

Builds a torch regression model and trains it.

Parameters

See [LearnerTorch](#)

Input and Output Channels

There is one input channel "input" that takes in `ModelDescriptor` during traing and a `Task` of the specified `task_type` during prediction. The output is `NULL` during training and a `Prediction` of given `task_type` during prediction.

State

A trained [LearnerTorchModel](#).

Internals

A [LearnerTorchModel](#) is created by calling `model_descriptor_to_learner()` on the provided [ModelDescriptor](#) that is received through the input channel. Then the parameters are set according to the parameters specified in `PipeOpTorchModel` and its `$train()` method is called on the `[Task][mlr3::Task]` stored

Super classes

```
mlr3pipelines::PipeOp -> mlr3pipelines::PipeOpLearner -> mlr3torch::PipeOpTorchModel
-> PipeOpTorchModelRegr
```

Methods

Public methods:

- [PipeOpTorchModelRegr\\$new\(\)](#)
- [PipeOpTorchModelRegr\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PipeOpTorchModelRegr$new(id = "torch_model_regr", param_vals = list())
```

Arguments:

`id` (`character(1)`)

Identifier of the resulting object.

param_vals (list())

List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method clone(): The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchModelRegr$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other PipeOps: [mlr_pipeops_nn_avg_pool1d](#), [mlr_pipeops_nn_avg_pool2d](#), [mlr_pipeops_nn_avg_pool3d](#), [mlr_pipeops_nn_batch_norm1d](#), [mlr_pipeops_nn_batch_norm2d](#), [mlr_pipeops_nn_batch_norm3d](#), [mlr_pipeops_nn_block](#), [mlr_pipeops_nn_celu](#), [mlr_pipeops_nn_conv1d](#), [mlr_pipeops_nn_conv2d](#), [mlr_pipeops_nn_conv3d](#), [mlr_pipeops_nn_conv_transpose1d](#), [mlr_pipeops_nn_conv_transpose2d](#), [mlr_pipeops_nn_conv_transpose3d](#), [mlr_pipeops_nn_dropout](#), [mlr_pipeops_nn_elu](#), [mlr_pipeops_nn_flatten](#), [mlr_pipeops_nn_gelu](#), [mlr_pipeops_nn_glu](#), [mlr_pipeops_nn_hardshrink](#), [mlr_pipeops_nn_hardsigmoid](#), [mlr_pipeops_nn_hardtanh](#), [mlr_pipeops_nn_head](#), [mlr_pipeops_nn_layer_norm](#), [mlr_pipeops_nn_leaky_relu](#), [mlr_pipeops_nn_linear](#), [mlr_pipeops_nn_log_sigmoid](#), [mlr_pipeops_nn_max_pool1d](#), [mlr_pipeops_nn_max_pool2d](#), [mlr_pipeops_nn_max_pool3d](#), [mlr_pipeops_nn_merge](#), [mlr_pipeops_nn_merge_cat](#), [mlr_pipeops_nn_merge_prod](#), [mlr_pipeops_nn_merge_sum](#), [mlr_pipeops_nn_prelu](#), [mlr_pipeops_nn_relu](#), [mlr_pipeops_nn_relu6](#), [mlr_pipeops_nn_reshape](#), [mlr_pipeops_nn_rrelu](#), [mlr_pipeops_nn_selu](#), [mlr_pipeops_nn_sigmoid](#), [mlr_pipeops_nn_softmax](#), [mlr_pipeops_nn_softplus](#), [mlr_pipeops_nn_softshrink](#), [mlr_pipeops_nn_softsign](#), [mlr_pipeops_nn_squeeze](#), [mlr_pipeops_nn_tanh](#), [mlr_pipeops_nn_tanhshrink](#), [mlr_pipeops_nn_threshold](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_model](#), [mlr_pipeops_torch_model](#)

Examples

```
# simple linear regression

# build the model descriptor
md = as_graph(po("torch_ingress_num") %>>%
  po("nn_head") %>>%
  po("torch_loss", "mse") %>>%
  po("torch_optimizer", "adam"))$train(tsk("mtcars"))[[1L]]

print(md)

# build the learner from the model descriptor and train it
po_model = po("torch_model_regr", batch_size = 20, epochs = 1)
po_model$train(list(md))
po_model$state
```

```
mlr_pipeops_torch_optimizer
  Optimizer Configuration
```

Description

Configures the optimizer of a deep learning model.

Input and Output Channels

There is one input channel "input" and one output channel "output". During *training*, the channels are of class `ModelDescriptor`. During *prediction*, the channels are of class `Task`.

State

The state is the value calculated by the public method `shapes_out()`.

Parameters

The parameters are defined dynamically from the optimizer that is set during construction.

Internals

During training, the optimizer is cloned and added to the `ModelDescriptor`. Note that the parameter set of the stored `TorchOptimizer` is reference-identical to the parameter set of the pipeop itself.

Super class

```
mlr3pipelines::PipeOp -> PipeOpTorchOptimizer
```

Methods

Public methods:

- `PipeOpTorchOptimizer$new()`
- `PipeOpTorchOptimizer$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
PipeOpTorchOptimizer$new(
  optimizer = t_opt("adam"),
  id = "torch_optimizer",
  param_vals = list()
)
```

Arguments:

`optimizer` (`TorchOptimizer` or `character(1)` or `torch_optimizer_generator`)
The optimizer (or something convertible via `as_torch_optimizer()`).

`id` (`character(1)`)
 Identifier of the resulting object.

`param_vals` (`list()`)
 List of hyperparameter settings, overwriting the hyperparameter settings that would otherwise be set during construction.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PipeOpTorchOptimizer$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other PipeOp: [mlr_pipeops_module](#), [mlr_pipeops_torch_callbacks](#)

Other Model Configuration: [ModelDescriptor\(\)](#), [mlr_pipeops_torch_callbacks](#), [mlr_pipeops_torch_loss](#), [model_descriptor_union\(\)](#)

Examples

```
po_opt = po("torch_optimizer", "sgd", lr = 0.01)
po_opt$param_set
mdin = po("torch_ingress_num")$train(list(tsk("iris")))
mdin[[1L]]$optimizer
mdout = po_opt$train(mdin)
mdout[[1L]]$optimizer
```

`mlr_tasks_lazy_iris` *Iris Classification Task*

Description

A classification task for the popular [datasets::iris](#) data set. Just like the iris task, but the features are represented as one lazy tensor column.

Format

[R6::R6Class](#) inheriting from [mlr3::TaskClassif](#).

Construction

```
tsk("lazy_iris")
```

Properties

- Task type: “classif”
- Properties: “multiclass”
- Has Missings: no
- Target: “Species”
- Features: “x”
- Data Dimension: 150x3

Source

https://en.wikipedia.org/wiki/Iris_flower_data_set

References

Anderson E (1936). “The Species Problem in Iris.” *Annals of the Missouri Botanical Garden*, **23**(3), 457. doi:10.2307/2394164.

Examples

```
task = tsk("lazy_iris")
task
df = task$data()
materialize(df$x[1:6], rbind = TRUE)
```

mlr_tasks_mnist

MNIST Image classification

Description

Classic MNIST image classification.

The underlying [DataBackend](#) contains columns "label", "image", "row_id", "split", where the last column indicates whether the row belongs to the train or test set.

The first 60000 rows belong to the training set, the last 10000 rows to the test set.

Construction

```
tsk("mnist")
```

Download

The `task`'s backend is a [DataBackendLazy](#) which will download the data once it is requested. Other meta-data is already available before that. You can cache these datasets by setting the `mlr3torch.cache` option to `TRUE` or to a specific path to be used as the cache directory.

Properties

- Task type: “classif”
- Properties: “multiclass”
- Has Missings: no
- Target: “label”
- Features: “image”
- Data Dimension: 70000x4

Source

https://torchvision.mlverse.org/reference/mnist_dataset.html

References

Lecun, Y., Bottou, L., Bengio, Y., Haffner, P. (1998). “Gradient-based learning applied to document recognition.” *Proceedings of the IEEE*, **86**(11), 2278-2324. doi:10.1109/5.726791.

Examples

```
task = tsk("mnist")
task
```

mlr_tasks_tiny_imagenet

Tiny ImageNet Classification Task

Description

Subset of the famous ImageNet dataset. The data is obtained from `torchvision::tiny_imagenet_dataset()`.

The underlying `DataBackend` contains columns "class", "image", "...row_id", "split", where the last column indicates whether the row belongs to the train, validation or test set that defined provided in torchvision.

There are no labels for the test rows, so by default, these observations are inactive, which means that the task uses only 110000 of the 120000 observations that are defined in the underlying data backend.

Construction

```
tsk("tiny_imagenet")
```

Download

The `task`'s backend is a `DataBackendLazy` which will download the data once it is requested. Other meta-data is already available before that. You can cache these datasets by setting the `mlr3torch.cache` option to `TRUE` or to a specific path to be used as the cache directory.

Properties

- Task type: “classif”
- Properties: “multiclass”
- Has Missings: no
- Target: “class”
- Features: “image”
- Data Dimension: 120000x4

References

Deng, Jia, Dong, Wei, Socher, Richard, Li, Li-Jia, Li, Kai, Fei-Fei, Li (2009). “Imagenet: A large-scale hierarchical image database.” In *2009 IEEE conference on computer vision and pattern recognition*, 248–255. IEEE.

Examples

```
task = tsk("tiny_imagenet")
task
```

ModelDescriptor

Represent a Model with Meta-Info

Description

Represents a *model*; possibly a complete model, possibly one in the process of being built up.

This model takes input tensors of shapes `shapes_in` and pipes them through `graph`. Input shapes get mapped to input channels of `graph`. Output shapes are named by the output channels of `graph`; it is also possible to represent no-ops on tensors, in which case names of input and output should be identical.

`ModelDescriptor` objects typically represent partial models being built up, in which case the `pointer` slot indicates a specific point in the `graph` that produces a tensor of shape `pointer_shape`, on which the `graph` should be extended. It is allowed for the `graph` in this structure to be modified by-reference in different parts of the code. However, these modifications may never add edges with elements of the `Graph` as destination. In particular, no element of `graph$input` may be removed by reference, e.g. by adding an edge to the `Graph` that has the input channel of a `PipeOp` that was previously without parent as its destination.

In most cases it is better to create a specific `ModelDescriptor` by training a `Graph` consisting (mostly) of operators `PipeOpTorchIngress`, `PipeOpTorch`, `PipeOpTorchLoss`, `PipeOpTorchOptimizer`, and `PipeOpTorchCallbacks`.

A `ModelDescriptor` can be converted to a `nn_graph` via `model_descriptor_to_module`.

Usage

```

ModelDescriptor(
  graph,
  ingress,
  task,
  optimizer = NULL,
  loss = NULL,
  callbacks = NULL,
  pointer = NULL,
  pointer_shape = NULL
)

```

Arguments

graph	(Graph) Graph of PipeOpModule and PipeOpNOP operators.
ingress	(uniquely named list of TorchIngressToken) List of inputs that go into graph. Names of this must be a subset of graph\$input\$name.
task	(Task) (Training)-Task for which the model is being built. May be necessary for for some aspects of what loss to use etc.
optimizer	(TorchOptimizer NULL) Additional info: what optimizer to use.
loss	(TorchLoss NULL) Additional info: what loss to use.
callbacks	(A list of CallbackSet or NULL) Additional info: what callbacks to use.
pointer	(character(2) NULL) Indicating an element on which a model is. Points to an output channel within graph: Element 1 is the PipeOp's id and element 2 is that PipeOp's output channel.
pointer_shape	(integer NULL) Shape of the output indicated by pointer.

Value

(ModelDescriptor)

See Also

Other Model Configuration: [mlr_pipeops_torch_callbacks](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_optimizer](#), [model_descriptor_union\(\)](#)

Other Graph Network: [TorchIngressToken\(\)](#), [mlr_learners_torch_model](#), [mlr_pipeops_module](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_num](#), [model_descriptor_to_learner\(\)](#), [model_descriptor_to_module\(\)](#), [model_descriptor_union\(\)](#), [nn_graph\(\)](#)

model_descriptor_to_learner

Create a Torch Learner from a ModelDescriptor

Description

First a [nn_graph](#) is created using [model_descriptor_to_module](#) and then a learner is created from this module and the remaining information from the model descriptor, which must include the optimizer and loss function and optionally callbacks.

Usage

```
model_descriptor_to_learner(model_descriptor)
```

Arguments

model_descriptor
 ([ModelDescriptor](#))
 The model descriptor.

Value

[Learner](#)

See Also

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr_learners_torch_model](#), [mlr_pipeops_module](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [model_descriptor_to_module\(\)](#), [model_descriptor_union\(\)](#), [nn_graph\(\)](#)

model_descriptor_to_module

Create a nn_graph from ModelDescriptor

Description

Creates the [nn_graph](#) from a [ModelDescriptor](#). Mostly for internal use, since the [ModelDescriptor](#) is in most circumstances harder to use than just creating [nn_graph](#) directly.

Usage

```
model_descriptor_to_module(  
  model_descriptor,  
  output_pointers = NULL,  
  list_output = FALSE  
)
```

Arguments

model_descriptor	(ModelDescriptor) Model Descriptor. pointer is ignored, instead output_pointer values are used. \$graph member is modified by-reference.
output_pointers	(list of character) Collection of pointers that indicate what part of the model_descriptor\$graph is being used for output. Entries have the format of ModelDescriptor\$pointer.
list_output	(logical(1)) Whether output should be a list of tensors. If FALSE, then length(output_pointers) must be 1.

Value

nn_graph

See Also

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr_learners_torch_model](#), [mlr_pipeops_module](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [model_descriptor_to_learner\(\)](#), [model_descriptor_union\(\)](#), [nn_graph\(\)](#)

model_descriptor_union

Union of ModelDescriptors

Description

This is a mostly internal function that is used in [PipeOpTorchs](#) with multiple input channels.

It creates the union of multiple [ModelDescriptors](#):

- graphs are combined (if they are not identical to begin with). The first entry's graph is modified by reference.
- PipeOps with the same ID must be identical. No new input edges may be added to PipeOps.
- Drops pointer / pointer_shape entries.
- The new task is the [feature union](#) of the two incoming tasks.
- The optimizer and loss of both [ModelDescriptors](#) must be identical.
- Ingress tokens and callbacks are merged, where objects with the same "id" must be identical.

Usage

```
model_descriptor_union(md1, md2)
```

Arguments

md1 (ModelDescriptor) The first [ModelDescriptor](#).
 md2 (ModelDescriptor) The second [ModelDescriptor](#).

Details

The requirement that no new input edges may be added to PipeOps is not theoretically necessary, but since we assume that ModelDescriptor is being built from beginning to end (i.e. PipeOps never get new ancestors) we can make this assumption and simplify things. Otherwise we'd need to treat "..."-inputs special.)

Value

[ModelDescriptor](#)

See Also

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr_learners_torch_model](#), [mlr_pipeops_module](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [model_descriptor_to_learner\(\)](#), [model_descriptor_to_module\(\)](#), [nn_graph\(\)](#)

Other Model Configuration: [ModelDescriptor\(\)](#), [mlr_pipeops_torch_callbacks](#), [mlr_pipeops_torch_loss](#), [mlr_pipeops_torch_optimizer](#)

 nn_graph

Graph Network

Description

Represents a neural network using a [Graph](#) that usually contains mostly [PipeOpModules](#).

Usage

```
nn_graph(graph, shapes_in, output_map = graph$output$name, list_output = FALSE)
```

Arguments

graph ([Graph](#))
 The [Graph](#) to wrap. Is **not** cloned.

shapes_in (named integer)
 Shape info of tensors that go into graph. Names must be graph\$input\$name, possibly in different order.

output_map (character)
 Which of graph's outputs to use. Must be a subset of graph\$output\$name.

list_output (logical(1))
 Whether output should be a list of tensors. If FALSE (default), then length(output_map) must be 1.

Value[nn_graph](#)**See Also**

Other Graph Network: [ModelDescriptor\(\)](#), [TorchIngressToken\(\)](#), [mlr_learners_torch_model](#), [mlr_pipeops_module](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_ltnsr](#), [mlr_pipeops_torch_ingress_num](#), [model_descriptor_to_learner\(\)](#), [model_descriptor_to_module\(\)](#), [model_descriptor_union\(\)](#)

Examples

```
graph = mlr3pipelines::Graph$new()
graph$add_pipeop(po("module_1", module = nn_linear(10, 20)), clone = FALSE)
graph$add_pipeop(po("module_2", module = nn_relu()), clone = FALSE)
graph$add_pipeop(po("module_3", module = nn_linear(20, 1)), clone = FALSE)
graph$add_edge("module_1", "module_2")
graph$add_edge("module_2", "module_3")

network = nn_graph(graph, shapes_in = list(module_1.input = c(NA, 10)))

x = torch_randn(16, 10)

network(module_1.input = x)
```

`nn_merge_cat`*Concatenates multiple tensors*

Description

Concatenates multiple tensors on a given dimension. No broadcasting rules are applied here, you must reshape the tensors before to have the same shape.

Usage

```
nn_merge_cat(dim = -1)
```

Arguments

`dim` `(integer(1))`
The dimension for the concatenation.

nn_merge_prod	<i>Product of multiple tensors</i>
---------------	------------------------------------

Description

Calculates the product of all input tensors.

Usage

```
nn_merge_prod()
```

nn_merge_sum	<i>Sum of multiple tensors</i>
--------------	--------------------------------

Description

Calculates the sum of all input tensors.

Usage

```
nn_merge_sum()
```

nn_reshape	<i>Reshape</i>
------------	----------------

Description

Reshape a tensor to the given shape.

Usage

```
nn_reshape(shape)
```

Arguments

shape	(integer()) The desired output shape.
-------	--

`nn_squeeze`*Squeeze*

Description

Squeezes a tensor by calling `torch::torch_squeeze()` with the given dimension `dim`.

Usage

```
nn_squeeze(dim)
```

Arguments

<code>dim</code>	<code>(integer())</code> The dimension to squeeze.
------------------	---

`nn_unsqueeze`*Unsqueeze*

Description

Unsquizes a tensor by calling `torch::torch_unsqueeze()` with the given dimension `dim`.

Usage

```
nn_unsqueeze(dim)
```

Arguments

<code>dim</code>	<code>(integer(1))</code> The dimension to unsqueeze.
------------------	--

pipeop_preproc_torch *Create Torch Preprocessing PipeOps*

Description

Function to create objects of class [PipeOpTaskPreprocTorch](#) in a more convenient way. Start by reading the documentation of [PipeOpTaskPreprocTorch](#).

Usage

```
pipeop_preproc_torch(
  id,
  fn,
  shapes_out = NULL,
  param_set = NULL,
  packages = character(0),
  rowwise = FALSE,
  parent_env = parent.frame(),
  stages_init = NULL,
  tags = NULL
)
```

Arguments

id	(character(1)) The id for of the new object.
fn	(function) The preprocessing function.
shapes_out	(function or NULL or "infer") The private .shapes_out(shapes_in, param_vals, task) method of PipeOpTaskPreprocTorch (see section Inheriting). Special values are NULL and infer: If NULL, the output shapes are unknown. If "infer", the output shape function is inferred and calculates the output shapes as follows: For an input shape of (NA, ...) a meta-tensor of shape (1, ...) is created and the preprocessing function is applied. Afterwards the batch dimension (1) is replaced with NA and the shape is returned. If the first dimension is not NA, the output shape of applying the preprocessing function is returned. Method "infer" should be correct in most cases, but might fail in some edge cases.
param_set	(ParamSet or NULL) The parameter set. If this is left as NULL (default) the parameter set is inferred in the following way: All parameters but the first and . . . of fn are set as untyped parameters with tags 'train' and those that have no default value are tagged as 'required' as well. Default values are not annotated.
packages	(character()) The R packages this object depends on.

rowwise	(logical(1)) Whether the preprocessing is applied row-wise.
parent_env	(environment) The parent environment for the R6 class.
stages_init	(character(1)) Initial value for the stages parameter. If NULL (default), will be set to "both" in case the id starts with "trafo" and to "train" if it starts with "augment". Otherwise it must be specified.
tags	(character()) Tags for the pipeop

Value

An [R6Class](#) instance inheriting from [PipeOpTaskPreprocTorch](#)

Examples

```
PipeOpPreprocExample = pipeop_preproc_torch("preproc_example", function(x, a) x + a)
po_example = PipeOpPreprocExample$new()
po_example$param_set
```

task_dataset	<i>Create a Dataset from a Task</i>
--------------	-------------------------------------

Description

Creates a torch [dataset](#) from an mlr3 [Task](#). The resulting dataset's `$.get_batch()` method returns a list with elements `x`, `y` and `index`:

- `x` is a list with tensors, whose content is defined by the parameter `feature_ingress_tokens`.
- `y` is the target variable and its content is defined by the parameter `target_batchgetter`.
- `.index` is the index of the batch in the task's data.

The data is returned on the device specified by the parameter `device`.

Usage

```
task_dataset(task, feature_ingress_tokens, target_batchgetter = NULL, device)
```

Arguments

task	(Task) The task for which to build the dataset .
feature_ingress_tokens	(named <code>list()</code> of TorchIngressToken) Each ingress token defines one item in the <code>\$x</code> value of a batch with corresponding names.

```
target_batchgetter
    (function(data, device))
    A function taking in arguments data, which is a data.table containing only
    the target variable, and device. It must return the target as a torch tensor on the
    selected device.

device
    (character())
    The device, e.g. "cuda" or "cpu".
```

Value

[torch::dataset](#)

Examples

```
task = tsk("iris")
sepal_ingress = TorchIngressToken(
  features = c("Sepal.Length", "Sepal.Width"),
  batchgetter = batchgetter_num,
  shape = c(NA, 2)
)
petal_ingress = TorchIngressToken(
  features = c("Petal.Length", "Petal.Width"),
  batchgetter = batchgetter_num,
  shape = c(NA, 2)
)
ingress_tokens = list(sepal = sepal_ingress, petal = petal_ingress)

target_batchgetter = function(data, device) {
  torch_tensor(data = data[[1L]], dtype = torch_float32(), device)$unsqueeze(2)
}
dataset = task_dataset(task, ingress_tokens, target_batchgetter, "cpu")
batch = dataset$getbatch(1:10)
batch
```

TorchCallback

Torch Callback

Description

This wraps a [CallbackSet](#) and annotates it with metadata, most importantly a [ParamSet](#). The callback is created for the given parameter values by calling the `$generate()` method.

This class is usually used to configure the callback of a torch learner, e.g. when constructing a learner of in a [ModelDescriptor](#).

For a list of available callbacks, see [mlr3torch_callbacks](#). To conveniently retrieve a [TorchCallback](#), use `t_clbk()`.

Parameters

Defined by the constructor argument `param_set`. If no parameter set is provided during construction, the parameter set is constructed by creating a parameter for each argument of the wrapped loss function, where the parameters are then of type `ParamUty`.

Super class

`mlr3torch::TorchDescriptor` -> `TorchCallback`

Methods**Public methods:**

- `TorchCallback$new()`
- `TorchCallback$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
TorchCallback$new(
  callback_generator,
  param_set = NULL,
  id = NULL,
  label = NULL,
  packages = NULL,
  man = NULL
)
```

Arguments:

`callback_generator` (`R6ClassGenerator`)

The class generator for the callback that is being wrapped.

`param_set` (`ParamSet` or `NULL`)

The parameter set. If `NULL` (default) it is inferred from `callback_generator`.

`id` (`character(1)`)

The id for of the new object.

`label` (`character(1)`)

Label for the new instance.

`packages` (`character()`)

The R packages this object depends on.

`man` (`character(1)`)

String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TorchCallback$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Callback: [as_torch_callback\(\)](#), [as_torch_callbacks\(\)](#), [callback_set\(\)](#), [mlr3torch_callbacks](#), [mlr_callback_set](#), [mlr_callback_set.checkpoint](#), [mlr_callback_set.progress](#), [mlr_context_torch](#), [t_clbk\(\)](#), [torch_callback\(\)](#)

Other Torch Descriptor: [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as_torch_callbacks\(\)](#), [as_torch_loss\(\)](#), [as_torch_optimizer\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_clbk\(\)](#), [t_loss\(\)](#), [t_opt\(\)](#)

Examples

```
# Create a new torch callback from an existing callback set
torch_callback = TorchCallback$new(CallbackSetCheckpoint)
# The parameters are inferred
torch_callback$param_set

# Retrieve a torch callback from the dictionary
torch_callback = t_clbk("checkpoint",
  path = tempfile(), freq = 1
)
torch_callback
torch_callback$label
torch_callback$id

# open the help page of the wrapped callback set
# torch_callback$help()

# Create the callback set
callback = torch_callback$generate()
callback
# is the same as
CallbackSetCheckpoint$new(
  path = tempfile(), freq = 1
)

# Use in a learner
learner = lrn("regr.mlp", callbacks = t_clbk("checkpoint"))
# the parameters of the callback are added to the learner's parameter set
learner$param_set
```

TorchDescriptor

Base Class for Torch Descriptors

Description

Abstract Base Class from which [TorchLoss](#), [TorchOptimizer](#), and [TorchCallback](#) inherit. This class wraps a generator (R6Class Generator or the torch version of such a generator) and annotates it with metadata such as a [ParamSet](#), a label, an ID, packages, or a manual page.

The parameters are the construction arguments of the wrapped generator and the parameter \$values are passed to the generator when calling the public method \$generate().

Parameters

Defined by the constructor argument `param_set`. All parameters are tagged with "train", but this is done automatically during initialize.

Public fields

`label` (character(1))
Label for this object. Can be used in tables, plot and text output instead of the ID.

`param_set` ([ParamSet](#))
Set of hyperparameters.

`packages` (character(1))
Set of required packages. These packages are loaded, but not attached.

`id` (character(1))
Identifier of the object. Used in tables, plot and text output.

`generator` The wrapped generator that is described.

`man` (character(1))
String in the format `[pkg]::[topic]` pointing to a manual page for this object.

Active bindings

`phash` (character(1))
Hash (unique identifier) for this partial object, excluding some components which are varied systematically (e.g. the parameter values).

Methods

Public methods:

- [TorchDescriptor\\$new\(\)](#)
- [TorchDescriptor\\$print\(\)](#)
- [TorchDescriptor\\$generate\(\)](#)
- [TorchDescriptor\\$help\(\)](#)
- [TorchDescriptor\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
TorchDescriptor$new(  
  generator,  
  id = NULL,  
  param_set = NULL,  
  packages = NULL,  
  label = NULL,  
  man = NULL  
)
```

Arguments:

`generator` The wrapped generator that is described.

`id` (character(1))
The id for of the new object.

`param_set` ([ParamSet](#))
The parameter set.

`packages` (character())
The R packages this object depends on.

`label` (character(1))
Label for the new instance.

`man` (character(1))
String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

Method `print()`: Prints the object

Usage:

```
TorchDescriptor$print(...)
```

Arguments:

... any

Method `generate()`: Calls the generator with the given parameter values.

Usage:

```
TorchDescriptor$generate()
```

Method `help()`: Displays the help file of the wrapped object.

Usage:

```
TorchDescriptor$help()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TorchDescriptor$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Torch Descriptor: [TorchCallback](#), [TorchLoss](#), [TorchOptimizer](#), [as_torch_callbacks\(\)](#), [as_torch_loss\(\)](#), [as_torch_optimizer\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_clbk\(\)](#), [t_loss\(\)](#), [t_opt\(\)](#)

TorchIngressToken *Torch Ingress Token*

Description

This function creates an S3 class of class "TorchIngressToken", which is an internal data structure. It contains the (meta-)information of how a batch is generated from a [Task](#) and fed into an entry point of the neural network. It is stored as the `ingress` field in a [ModelDescriptor](#).

Usage

```
TorchIngressToken(features, batchgetter, shape)
```

Arguments

<code>features</code>	(character) Features on which the batchgetter will operate.
<code>batchgetter</code>	(function) Function with two arguments: <code>data</code> and <code>device</code> . This function is given the output of <code>Task\$data(rows = batch_indices, cols = features)</code> and it should produce a tensor of shape <code>shape_out</code> .
<code>shape</code>	(integer) Shape that batchgetter will produce. Batch-dimension should be included as <code>NA</code> .

Value

TorchIngressToken object.

See Also

Other Graph Network: [ModelDescriptor\(\)](#), [mlr_learners_torch_model](#), [mlr_pipeops_module](#), [mlr_pipeops_torch](#), [mlr_pipeops_torch_ingress](#), [mlr_pipeops_torch_ingress_categ](#), [mlr_pipeops_torch_ingress_num](#), [model_descriptor_to_learner\(\)](#), [model_descriptor_to_module\(\)](#), [model_descriptor_union\(\)](#), [nn_graph\(\)](#)

Examples

```
# Define a task for which we want to define an ingress token
task = tsk("iris")

# We create an ingress token for two feature Sepal.Length and Petal.Length:
# We have to specify the features, the batchgetter and the shape
features = c("Sepal.Length", "Petal.Length")
# As a batchgetter we use batchgetter_num

batch_dt = task$data(rows = 1:10, cols =features)
batch_dt
```

```

batch_tensor = batchgetter_num(batch_dt, "cpu")
batch_tensor

# The shape is unknown in the first dimension (batch dimension)

ingress_token = TorchIngressToken(
  features = features,
  batchgetter = batchgetter_num,
  shape = c(NA, 2)
)
ingress_token

```

TorchLoss

Torch Loss

Description

This wraps a `torch::nn_loss` and annotates it with metadata, most importantly a [ParamSet](#). The loss function is created for the given parameter values by calling the `$generate()` method.

This class is usually used to configure the loss function of a torch learner, e.g. when constructing a learner or in a [ModelDescriptor](#).

For a list of available losses, see [mlr3torch_losses](#). Items from this dictionary can be retrieved using `t_loss()`.

Parameters

Defined by the constructor argument `param_set`. If no parameter set is provided during construction, the parameter set is constructed by creating a parameter for each argument of the wrapped loss function, where the parameters are then of type `ParamUty`.

Super class

[mlr3torch::TorchDescriptor](#) -> TorchLoss

Public fields

`task_types` (`character()`)
The task types this loss supports.

Methods

Public methods:

- [TorchLoss\\$new\(\)](#)
- [TorchLoss\\$print\(\)](#)
- [TorchLoss\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
TorchLoss$new(
  torch_loss,
  task_types = NULL,
  param_set = NULL,
  id = NULL,
  label = NULL,
  packages = NULL,
  man = NULL
)
```

Arguments:

`torch_loss` (`nn_loss`)
The loss module.

`task_types` (`character()`)
The task types supported by this loss.

`param_set` (`ParamSet` or `NULL`)
The parameter set. If `NULL` (default) it is inferred from `torch_loss`.

`id` (`character(1)`)
The id for of the new object.

`label` (`character(1)`)
Label for the new instance.

`packages` (`character()`)
The R packages this object depends on.

`man` (`character(1)`)
String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

Method `print()`: Prints the object

Usage:

```
TorchLoss$print(...)
```

Arguments:

... any

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TorchLoss$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

See Also

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchOptimizer](#), [as_torch_callbacks\(\)](#), [as_torch_loss\(\)](#), [as_torch_optimizer\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_clbk\(\)](#), [t_loss\(\)](#), [t_opt\(\)](#)

Examples

```

# Create a new torch loss
torch_loss = TorchLoss$new(torch_loss = nn_mse_loss, task_types = "regr")
torch_loss
# the parameters are inferred
torch_loss$param_set

# Retrieve a loss from the dictionary:
torch_loss = t_loss("mse", reduction = "mean")
# is the same as
torch_loss
torch_loss$param_set
torch_loss$label
torch_loss$task_types
torch_loss$id

# Create the loss function
loss_fn = torch_loss$generate()
loss_fn
# Is the same as
nn_mse_loss(reduction = "mean")

# open the help page of the wrapped loss function
# torch_loss$help()

# Use in a learner
learner = lrn("regr.mlp", loss = t_loss("mse"))
# The parameters of the loss are added to the learner's parameter set
learner$param_set

```

TorchOptimizer

Torch Optimizer

Description

This wraps a `torch::torch_optimizer_generator` and annotates it with metadata, most importantly a [ParamSet](#). The optimizer is created for the given parameter values by calling the `$generate()` method.

This class is usually used to configure the optimizer of a torch learner, e.g. when constructing a learner or in a [ModelDescriptor](#).

For a list of available optimizers, see [mlr3torch_optimizers](#). Items from this dictionary can be retrieved using `t_opt()`.

Parameters

Defined by the constructor argument `param_set`. If no parameter set is provided during construction, the parameter set is constructed by creating a parameter for each argument of the wrapped loss function, where the parameters are then of type [ParamUty](#).

Super class

`mlr3torch::TorchDescriptor` -> TorchOptimizer

Methods**Public methods:**

- `TorchOptimizer$new()`
- `TorchOptimizer$generate()`
- `TorchOptimizer$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
TorchOptimizer$new(
  torch_optimizer,
  param_set = NULL,
  id = NULL,
  label = NULL,
  packages = NULL,
  man = NULL
)
```

Arguments:

`torch_optimizer` (`torch_optimizer_generator`)

The torch optimizer.

`param_set` (`ParamSet` or `NULL`)

The parameter set. If `NULL` (default) it is inferred from `torch_optimizer`.

`id` (`character(1)`)

The id for of the new object.

`label` (`character(1)`)

Label for the new instance.

`packages` (`character()`)

The R packages this object depends on.

`man` (`character(1)`)

String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

Method `generate()`: Instantiates the optimizer.

Usage:

```
TorchOptimizer$generate(params)
```

Arguments:

`params` (`named list()` of `torch_tensors`)

The parameters of the network.

Returns: `torch_optimizer`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TorchOptimizer$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

See Also

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [as_torch_callbacks\(\)](#), [as_torch_loss\(\)](#), [as_torch_optimizer\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_clbk\(\)](#), [t_loss\(\)](#), [t_opt\(\)](#)

Examples

```
# Create a new torch loss
torch_opt = TorchOptimizer$new(optim_adam, label = "adam")
torch_opt
# If the param set is not specified, parameters are inferred but are of class ParamUty
torch_opt$param_set

# open the help page of the wrapped optimizer
# torch_opt$help()

# Retrieve an optimizer from the dictionary
torch_opt = t_opt("sgd", lr = 0.1)
torch_opt
torch_opt$param_set
torch_opt$label
torch_opt$id

# Create the optimizer for a network
net = nn_linear(10, 1)
opt = torch_opt$generate(net$parameters)

# is the same as
optim_sgd(net$parameters, lr = 0.1)

# Use in a learner
learner = lrn("regr.mlp", optimizer = t_opt("sgd"))
# The parameters of the optimizer are added to the learner's parameter set
learner$param_set
```

torch_callback

Create a Callback Descriptor

Description

Convenience function to create a custom [TorchCallback](#). All arguments that are available in [callback_set\(\)](#) are also available here. For more information on how to correctly implement a new callback, see [CallbackSet](#).

Usage

```

torch_callback(
    id,
    classname = paste0("CallbackSet", capitalize(id)),
    param_set = NULL,
    packages = NULL,
    label = capitalize(id),
    man = NULL,
    on_begin = NULL,
    on_end = NULL,
    on_exit = NULL,
    on_epoch_begin = NULL,
    on_before_valid = NULL,
    on_epoch_end = NULL,
    on_batch_begin = NULL,
    on_batch_end = NULL,
    on_after_backward = NULL,
    on_batch_valid_begin = NULL,
    on_batch_valid_end = NULL,
    on_valid_end = NULL,
    state_dict = NULL,
    load_state_dict = NULL,
    initialize = NULL,
    public = NULL,
    private = NULL,
    active = NULL,
    parent_env = parent.frame(),
    inherit = CallbackSet,
    lock_objects = FALSE
)

```

Arguments

id	(character(1)) ,	The id for the torch callback.
classname	(character(1))	The class name.
param_set	(ParamSet)	The parameter set, if not present it is inferred from the <code>\$initialize()</code> method.
packages	(character())	The packages the callback depends on. Default is <code>NULL</code> .
label	(character(1))	The label for the torch callback. Defaults to the capitalized id.
man	(character(1))	String in the format <code>[pkg]::[topic]</code> pointing to a manual page for this object.

The referenced help package can be opened via method `$help()`. The default is `NULL`.

`on_begin`, `on_end`, `on_epoch_begin`, `on_before_valid`,
`on_epoch_end`, `on_batch_begin`, `on_batch_end`, `on_after_backward`,
`on_batch_valid_begin`, `on_batch_valid_end`, `on_valid_end`, `on_exit`
(function)
Function to execute at the given stage, see section *Stages*.

`state_dict` (function())
The function that retrieves the state dict from the callback. This is what will be available in the learner after training.

`load_state_dict`
(function(`state_dict`))
Function that loads a callback state.

`initialize` (function())
The initialization method of the callback.

`public`, `private`, `active`
(list())
Additional public, private, and active fields to add to the callback.

`parent_env` (environment())
The parent environment for the [R6Class](#).

`inherit` (R6ClassGenerator)
From which class to inherit. This class must either be [CallbackSet](#) (default) or inherit from it.

`lock_objects` (logical(1))
Whether to lock the objects of the resulting [R6Class](#). If `FALSE` (default), values can be freely assigned to `self` without declaring them in the class definition.

Value

[TorchCallback](#)

Internals

It first creates an R6 class inheriting from [CallbackSet](#) (using `callback_set()`) and then wraps this generator in a [TorchCallback](#) that can be passed to a torch learner.

Stages

- `begin` :: Run before the training loop begins.
- `epoch_begin` :: Run he beginning of each epoch.
- `batch_begin` :: Run before the forward call.
- `after_backward` :: Run after the backward call.
- `batch_end` :: Run after the optimizer step.
- `batch_valid_begin` :: Run before the forward call in the validation loop.
- `batch_valid_end` :: Run after the forward call in the validation loop.

- `valid_end` :: Run at the end of validation.
- `epoch_end` :: Run at the end of each epoch.
- `end` :: Run after last epoch.
- `exit` :: Run at last, using `on.exit()`.

See Also

Other Callback: [TorchCallback](#), [as_torch_callback\(\)](#), [as_torch_callbacks\(\)](#), [callback_set\(\)](#), [mlr3torch_callbacks](#), [mlr_callback_set](#), [mlr_callback_set.checkpoint](#), [mlr_callback_set.progress](#), [mlr_context_torch](#), [t_clbk\(\)](#)

Examples

```
custom_tcb = torch_callback("custom",
  initialize = function(name) {
    self$name = name
  },
  on_begin = function() {
    cat("Hello", self$name, ", we will train for ", self$ctx$total_epochs, "epochs.\n")
  },
  on_end = function() {
    cat("Training is done.")
  }
)

learner = lrn("classif.torch.featureless",
  batch_size = 16,
  epochs = 1,
  callbacks = custom_tcb,
  cb.custom.name = "Marie",
  device = "cpu"
)
task = tsk("iris")
learner$train(task)
```

t_clbk

Sugar Function for Torch Callback

Description

Retrieves one or more [TorchCallbacks](#) from [mlr3torch_callbacks](#). Works like [mlr3::lrn\(\)](#) and [mlr3::lrns\(\)](#).

Usage

```
t_clbk(.key, ...)
```

```
t_clbks(.keys)
```

Arguments

.key	(character(1)) The key of the torch callback.
...	(any) See description of dictionary_sugar_get() .
.keys	(character()) The keys of the callbacks.

Value

[TorchCallback](#)
list() of [TorchCallbacks](#)

See Also

Other Callback: [TorchCallback](#), [as_torch_callback\(\)](#), [as_torch_callbacks\(\)](#), [callback_set\(\)](#), [mlr3torch_callbacks](#), [mlr_callback_set](#), [mlr_callback_set.checkpoint](#), [mlr_callback_set.progress](#), [mlr_context_torch](#), [torch_callback\(\)](#)

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as_torch_callbacks\(\)](#), [as_torch_loss\(\)](#), [as_torch_optimizer\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_loss\(\)](#), [t_opt\(\)](#)

Examples

```
t_clbk("progress")
```

t_loss	<i>Loss Function Quick Access</i>
--------	-----------------------------------

Description

Retrieve one or more [TorchLosses](#) from [mlr3torch_losses](#). Works like [mlr3::lrn\(\)](#) and [mlr3::lrns\(\)](#).

Usage

```
t_loss(.key, ...)
```

```
t_losses(.keys, ...)
```

Arguments

.key	(character(1)) Key of the object to retrieve.
...	(any) See description of dictionary_sugar_get .
.keys	(character()) The keys of the losses.

Value

A [TorchLoss](#)

See Also

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as_torch_callbacks\(\)](#), [as_torch_loss\(\)](#), [as_torch_optimizer\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_clbk\(\)](#), [t_opt\(\)](#)

Examples

```
t_loss("mse", reduction = "mean")
# get the dictionary
t_loss()
```

```
t_losses(c("mse", "l1"))
# get the dictionary
t_losses()
```

t_opt

Optimizers Quick Access

Description

Retrieves one or more [TorchOptimizers](#) from [mlr3torch_optimizers](#). Works like [mlr3::lrn\(\)](#) and [mlr3::lrns\(\)](#).

Usage

```
t_opt(.key, ...)
t_opts(.keys, ...)
```

Arguments

.key	(character(1)) Key of the object to retrieve.
...	(any) See description of dictionary_sugar_get .
.keys	(character()) The keys of the optimizers.

Value

A [TorchOptimizer](#)

See Also

Other Torch Descriptor: [TorchCallback](#), [TorchDescriptor](#), [TorchLoss](#), [TorchOptimizer](#), [as_torch_callbacks\(\)](#), [as_torch_loss\(\)](#), [as_torch_optimizer\(\)](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#), [t_clbk\(\)](#), [t_loss\(\)](#)

Other Dictionary: [mlr3torch_callbacks](#), [mlr3torch_losses](#), [mlr3torch_optimizers](#)

Examples

```
t_opt("adam", lr = 0.1)
# get the dictionary
t_opt()
```

```
t_opts(c("adam", "sgd"))
# get the dictionary
t_opts()
```

Index

- * **Callback**
 - as_torch_callback, 8
 - as_torch_callbacks, 9
 - callback_set, 12
 - mlr3torch_callbacks, 19
 - mlr_callback_set, 25
 - mlr_callback_set.checkpoint, 28
 - mlr_callback_set.progress, 30
 - mlr_context_torch, 32
 - t_clbk, 223
 - torch_callback, 220
 - TorchCallback, 210
- * **Dictionary**
 - mlr3torch_callbacks, 19
 - mlr3torch_losses, 20
 - mlr3torch_optimizers, 21
 - t_opt, 225
- * **Graph Network**
 - mlr_learners_torch_model, 51
 - mlr_pipeops_module, 54
 - mlr_pipeops_torch, 171
 - mlr_pipeops_torch_ingress, 178
 - mlr_pipeops_torch_ingress_categ, 180
 - mlr_pipeops_torch_ingress_ltnsr, 182
 - mlr_pipeops_torch_ingress_num, 185
 - model_descriptor_to_learner, 202
 - model_descriptor_to_module, 202
 - model_descriptor_union, 203
 - ModelDescriptor, 200
 - nn_graph, 204
 - TorchIngressToken, 215
- * **Learner**
 - mlr_learners.mlp, 34
 - mlr_learners.tab_resnet, 37
 - mlr_learners.torch_featureless, 41
 - mlr_learners_torch, 43
 - mlr_learners_torch_image, 50
 - mlr_learners_torch_model, 51
- * **Model Configuration**
 - mlr_pipeops_torch_callbacks, 177
 - mlr_pipeops_torch_loss, 187
 - mlr_pipeops_torch_optimizer, 196
 - model_descriptor_union, 203
 - ModelDescriptor, 200
- * **PipeOps**
 - mlr_pipeops_nn_avg_pool1d, 57
 - mlr_pipeops_nn_avg_pool2d, 59
 - mlr_pipeops_nn_avg_pool3d, 61
 - mlr_pipeops_nn_batch_norm1d, 63
 - mlr_pipeops_nn_batch_norm2d, 65
 - mlr_pipeops_nn_batch_norm3d, 67
 - mlr_pipeops_nn_block, 69
 - mlr_pipeops_nn_celu, 71
 - mlr_pipeops_nn_conv1d, 73
 - mlr_pipeops_nn_conv2d, 75
 - mlr_pipeops_nn_conv3d, 77
 - mlr_pipeops_nn_conv_transpose1d, 79
 - mlr_pipeops_nn_conv_transpose2d, 81
 - mlr_pipeops_nn_conv_transpose3d, 84
 - mlr_pipeops_nn_dropout, 86
 - mlr_pipeops_nn_elu, 88
 - mlr_pipeops_nn_flatten, 90
 - mlr_pipeops_nn_gelu, 91
 - mlr_pipeops_nn_glu, 93
 - mlr_pipeops_nn_hardshrink, 95
 - mlr_pipeops_nn_hardsigmoid, 97
 - mlr_pipeops_nn_hardtanh, 98
 - mlr_pipeops_nn_head, 100
 - mlr_pipeops_nn_layer_norm, 102
 - mlr_pipeops_nn_leaky_relu, 104
 - mlr_pipeops_nn_linear, 106
 - mlr_pipeops_nn_log_sigmoid, 107
 - mlr_pipeops_nn_max_pool1d, 109

- mlr_pipeops_nn_max_pool2d, 111
- mlr_pipeops_nn_max_pool3d, 114
- mlr_pipeops_nn_merge, 116
- mlr_pipeops_nn_merge_cat, 118
- mlr_pipeops_nn_merge_prod, 120
- mlr_pipeops_nn_merge_sum, 122
- mlr_pipeops_nn_prelu, 124
- mlr_pipeops_nn_relu, 126
- mlr_pipeops_nn_relu6, 128
- mlr_pipeops_nn_reshape, 129
- mlr_pipeops_nn_rrelu, 131
- mlr_pipeops_nn_selu, 133
- mlr_pipeops_nn_sigmoid, 135
- mlr_pipeops_nn_softmax, 137
- mlr_pipeops_nn_softplus, 138
- mlr_pipeops_nn_softshrink, 140
- mlr_pipeops_nn_softsign, 142
- mlr_pipeops_nn_squeeze, 144
- mlr_pipeops_nn_tanh, 147
- mlr_pipeops_nn_tanhshrink, 148
- mlr_pipeops_nn_threshold, 150
- mlr_pipeops_torch_ingress, 178
- mlr_pipeops_torch_ingress_categ, 180
- mlr_pipeops_torch_ingress_ltnsr, 182
- mlr_pipeops_torch_ingress_num, 185
- mlr_pipeops_torch_loss, 187
- mlr_pipeops_torch_model, 189
- mlr_pipeops_torch_model_classif, 192
- mlr_pipeops_torch_model_regr, 194
- * **PipeOp**
 - mlr_pipeops_module, 54
 - mlr_pipeops_torch_callbacks, 177
 - mlr_pipeops_torch_optimizer, 196
- * **Torch Descriptor**
 - as_torch_callbacks, 9
 - as_torch_loss, 10
 - as_torch_optimizer, 10
 - mlr3torch_losses, 20
 - mlr3torch_optimizers, 21
 - t_clbk, 223
 - t_loss, 224
 - t_opt, 225
 - TorchCallback, 210
 - TorchDescriptor, 212
 - TorchLoss, 216
 - TorchOptimizer, 218
- * **datasets**
 - mlr3torch_callbacks, 19
 - mlr3torch_losses, 20
 - mlr3torch_optimizers, 21
 - ..., 170
- as.data.table, 19–21
- as_data_descriptor, 6
- as_data_descriptor(), 14
- as_lazy_tensor, 7
- as_torch_callback, 8, 9, 14, 19, 27, 29, 31, 34, 212, 223, 224
- as_torch_callbacks, 9, 9, 10, 11, 14, 19–21, 27, 29, 31, 34, 212, 214, 217, 220, 223–226
- as_torch_callbacks(), 178
- as_torch_loss, 9, 10, 11, 20, 21, 212, 214, 217, 220, 224–226
- as_torch_loss(), 188
- as_torch_optimizer, 9, 10, 10, 20, 21, 212, 214, 217, 220, 224–226
- as_torch_optimizer(), 196
- assert_lazy_tensor, 6
- auto_device, 11
- batchgetter_categ, 11
- batchgetter_categ(), 181
- batchgetter_num, 12
- batchgetter_num(), 185
- callback_set, 9, 12, 19, 27, 29, 31, 34, 212, 223, 224
- callback_set(), 26, 220, 222
- callbacks, 44
- CallbackSet, 12, 14, 25, 32, 201, 210, 220, 222
- CallbackSet (mlr_callback_set), 25
- CallbackSetCheckpoint (mlr_callback_set.checkpoint), 28
- CallbackSetHistory (mlr_callback_set.history), 29
- CallbackSetProgress (mlr_callback_set.progress), 30
- ContextTorch, 25, 26
- ContextTorch (mlr_context_torch), 32
- data.table, 19–21

- data.table::data.table(), 23, 24
- DataBackend, 198, 199
- DataBackendLazy, 198, 199
- DataBackendLazy (mlr_backends_lazy), 21
- DataDescriptor, 6, 14, 17, 18
- dataset, 49, 209
- datasets::iris, 197
- dictionary_sugar_get, 224, 225
- dictionary_sugar_get(), 224
- feature union, 171, 203
- Graph, 14–16, 18, 69, 70, 171, 172, 200, 201, 204
- graph, 172
- is_lazy_tensor, 17
- lazy_tensor, 7, 14, 17, 18, 19, 22, 34, 50, 54, 152, 182
- lazy_tensor(), 18
- Learner, 32–34, 37, 41, 202
- LearnerTorch, 26, 27, 32, 35, 37, 41, 50, 51, 192, 194
- LearnerTorch (mlr_learners_torch), 43
- LearnerTorchFeatureless (mlr_learners.torch_featureless), 41
- LearnerTorchImage, 39
- LearnerTorchImage (mlr_learners_torch_image), 50
- LearnerTorchMLP (mlr_learners.mlp), 34
- LearnerTorchModel, 189, 191, 192, 194
- LearnerTorchModel (mlr_learners_torch_model), 51
- LearnerTorchTabResNet (mlr_learners.tab_resnet), 37
- LearnerTorchVision (mlr_learners.torchvision), 39
- loss, 44
- lrn(), 34, 37, 41
- materialize, 18
- materialize(), 14
- Measure, 32–34, 44, 189
- mlr3::as_prediction_data(), 46
- mlr3::col_info(), 22
- mlr3::DataBackend, 22
- mlr3::Learner, 35, 37, 39, 41, 46, 50, 52
- mlr3::lrn(), 223–225
- mlr3::lrns(), 223–225
- mlr3::Task, 43, 152
- mlr3::TaskClassif, 197
- mlr3misc::Dictionary, 19
- mlr3pipelines::Graph, 14, 54
- mlr3pipelines::PipeOp, 54, 58, 60, 62, 64, 66, 68, 69, 71, 74, 76, 78, 80, 82, 85, 86, 88, 90, 92, 94, 95, 97, 99, 101, 103, 104, 106, 108, 110, 112, 114, 116, 118, 120, 122, 125, 126, 128, 130, 132, 134, 135, 137, 139, 141, 142, 144, 145, 147, 149, 151, 153, 172, 177, 179, 181, 183, 185, 187, 191, 192, 194, 196
- mlr3pipelines::PipeOpLearner, 191, 192, 194
- mlr3pipelines::PipeOpTaskPreproc, 153
- mlr3torch (mlr3torch-package), 5
- mlr3torch-package, 5
- mlr3torch::CallbackSet, 28–30
- mlr3torch::LearnerTorch, 35, 37, 39, 41, 50, 52
- mlr3torch::LearnerTorchImage, 39
- mlr3torch::PipeOpTorch, 58, 60, 62, 64, 66, 68, 69, 71, 74, 76, 78, 80, 82, 85, 86, 88, 90, 92, 94, 95, 97, 99, 101, 103, 104, 106, 108, 110, 112, 114, 116, 118, 120, 122, 125, 126, 128, 130, 132, 134, 135, 137, 139, 141, 142, 144, 145, 147, 149, 151
- mlr3torch::PipeOpTorchIngress, 181, 183, 185
- mlr3torch::PipeOpTorchMerge, 118, 120, 122
- mlr3torch::PipeOpTorchModel, 192, 194
- mlr3torch::TorchDescriptor, 211, 216, 219
- mlr3torch_callbacks, 9, 14, 19, 20, 21, 27, 29, 31, 34, 210, 212, 223, 224, 226
- mlr3torch_losses, 9–11, 19, 20, 21, 212, 214, 216, 217, 220, 224–226
- mlr3torch_optimizers, 9–11, 19, 20, 21, 212, 214, 217, 218, 220, 224–226
- mlr_backends_lazy, 21
- mlr_callback_set, 9, 14, 19, 25, 29, 31, 34, 212, 223, 224
- mlr_callback_set.checkpoint, 9, 14, 19,

- 27, 28, 31, 34, 212, 223, 224
- `mlr_callback_set.history`, 29
- `mlr_callback_set.progress`, 9, 14, 19, 27, 29, 30, 34, 212, 223, 224
- `mlr_context_torch`, 9, 14, 19, 27, 29, 31, 32, 212, 223, 224
- `mlr_learners.mlp`, 34, 38, 42, 49, 51, 53
- `mlr_learners.tab_resnet`, 36, 37, 42, 49, 51, 53
- `mlr_learners.torch_featureless`, 36, 38, 41, 49, 51, 53
- `mlr_learners.torchvision`, 39
- `mlr_learners_torch`, 36, 38, 42, 43, 51, 53
- `mlr_learners_torch_image`, 36, 38, 42, 49, 50, 53
- `mlr_learners_torch_model`, 36, 38, 42, 49, 51, 51, 55, 174, 180, 182, 184, 186, 201–205, 215
- `mlr_pipeops_module`, 53, 54, 174, 178, 180, 182, 184, 186, 197, 201–205, 215
- `mlr_pipeops_nn_avg_pool1d`, 57, 60, 62, 64, 66, 68, 70, 72, 74, 76, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 132, 134, 136, 138, 140, 141, 143, 146, 148, 150, 151, 180, 182, 184, 186, 188, 191, 193, 195
- `mlr_pipeops_nn_avg_pool2d`, 58, 59, 62, 64, 66, 68, 70, 72, 74, 76, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 132, 134, 136, 138, 140, 141, 143, 146, 148, 150, 151, 180, 182, 184, 186, 188, 191, 193, 195
- `mlr_pipeops_nn_avg_pool3d`, 58, 60, 61, 64, 66, 68, 70, 72, 74, 76, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 132, 134, 136, 138, 140, 141, 143, 146, 148, 150, 151, 180, 182, 184, 186, 188, 191, 193, 195
- `mlr_pipeops_nn_batch_norm1d`, 58, 60, 62, 63, 66, 68, 70, 72, 74, 76, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 132, 134, 136, 138, 140, 141, 143, 146, 148, 150, 151, 180, 182, 184, 186, 188, 191, 193, 195
- `mlr_pipeops_nn_batch_norm2d`, 58, 60, 62, 64, 65, 68, 70, 72, 74, 76, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 132, 134, 136, 138, 140, 141, 143, 146, 148, 150, 151, 180, 182, 184, 186, 188, 191, 193, 195
- `mlr_pipeops_nn_batch_norm3d`, 58, 60, 62, 64, 66, 67, 70, 72, 74, 76, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 132, 134, 136, 138, 140, 141, 143, 146, 148, 150, 151, 180, 182, 184, 186, 188, 191, 193, 195
- `mlr_pipeops_nn_block`, 58, 60, 62, 64, 66, 68, 69, 72, 74, 76, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 132, 134, 136, 138, 140, 141, 143, 146, 148, 150, 151, 180, 182, 184, 186, 188, 191, 193, 195
- `mlr_pipeops_nn_celu`, 58, 60, 62, 64, 66, 68, 70, 71, 74, 76, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 132, 134, 136, 138, 140, 141, 143, 146, 148, 150, 151, 180, 182, 184, 186, 188, 191, 193, 195
- `mlr_pipeops_nn_conv1d`, 58, 60, 62, 64, 66, 68, 70, 72, 73, 76, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117, 119, 121, 123, 125, 127, 129, 131, 132, 134, 136, 138, 140, 141, 143, 146, 148, 150, 151, 180, 182, 184, 186, 188, 191, 193, 195
- `mlr_pipeops_nn_conv2d`, 58, 60, 62, 64, 66, 68, 70, 72, 74, 75, 79, 81, 83, 85, 87, 89, 91, 93, 94, 96, 98, 100, 101, 103, 105, 107, 109, 111, 113, 115, 117,

- 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 144, 148, 150, 152, 180, 182, 184, 186, 188, 192, 193, 195
- mlr_pipeops_nn_tanh, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 147, 150, 152, 180, 182, 184, 186, 188, 192, 193, 195
- mlr_pipeops_nn_tanhshrink, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 148, 148, 152, 180, 182, 184, 186, 188, 192, 193, 195
- mlr_pipeops_nn_threshold, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 150, 150, 180, 182, 184, 186, 188, 192, 193, 195
- mlr_pipeops_preproc_torch, 152
- mlr_pipeops_preproc_torch.augment_center_crop, 157
- mlr_pipeops_preproc_torch.augment_color_jitter, 157
- mlr_pipeops_preproc_torch.augment_crop, 158
- mlr_pipeops_preproc_torch.augment_hflip, 159
- mlr_pipeops_preproc_torch.augment_random_affine, 159
- mlr_pipeops_preproc_torch.augment_random_choice, 160
- mlr_pipeops_preproc_torch.augment_random_crop, 160
- mlr_pipeops_preproc_torch.augment_random_horizontal_flip, 161
- mlr_pipeops_preproc_torch.augment_random_order, 162
- mlr_pipeops_preproc_torch.augment_random_resized_crop, 162
- mlr_pipeops_preproc_torch.augment_random_vertical_flip, 163
- mlr_pipeops_preproc_torch.augment_resized_crop, 163
- mlr_pipeops_preproc_torch.augment_rotate, 164
- mlr_pipeops_preproc_torch.augment_vflip, 165
- mlr_pipeops_preproc_torch.trafo_adjust_brightness, 165
- mlr_pipeops_preproc_torch.trafo_adjust_gamma, 166
- mlr_pipeops_preproc_torch.trafo_adjust_hue, 166
- mlr_pipeops_preproc_torch.trafo_adjust_saturation, 167
- mlr_pipeops_preproc_torch.trafo_grayscale, 167
- mlr_pipeops_preproc_torch.trafo_nop, 168
- mlr_pipeops_preproc_torch.trafo_normalize, 168
- mlr_pipeops_preproc_torch.trafo_pad, 169
- mlr_pipeops_preproc_torch.trafo_reshape, 169
- mlr_pipeops_preproc_torch.trafo_resize, 170
- mlr_pipeops_preproc_torch.trafo_rgb_to_grayscale, 170
- mlr_pipeops_torch, 53, 55, 171, 180, 182, 184, 186, 201–205, 215
- mlr_pipeops_torch_callbacks, 55, 177, 188, 197, 201, 204
- mlr_pipeops_torch_ingress, 53, 55, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 150, 152, 174, 178, 182, 184, 186, 188, 192, 193, 195, 201–205, 215
- mlr_pipeops_torch_ingress_categ, 53, 55,

- 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 150, 152, 174, 180, 180, 184, 186, 188, 192, 193, 195, 201–205, 215
- `mlr_pipeops_torch_ingress_ltnsr`, 53, 55, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 150, 152, 174, 180, 182, 182, 186, 188, 192, 193, 195, 201–205, 215
- `mlr_pipeops_torch_ingress_num`, 53, 55, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 150, 152, 174, 180, 182, 184, 185, 188, 192, 193, 195, 201–205, 215
- `mlr_pipeops_torch_loss`, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 150, 152, 178, 180, 182, 184, 186, 187, 192, 193, 195, 197, 201, 204
- `mlr_pipeops_torch_model`, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 150, 152, 180, 182, 184, 186, 188, 189, 193, 195
- `mlr_pipeops_torch_model_classif`, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 150, 152, 180, 182, 184, 186, 188, 188, 192, 192, 195
- `mlr_pipeops_torch_model_regr`, 58, 60, 62, 64, 66, 68, 70, 72, 74, 77, 79, 81, 83, 85, 87, 89, 91, 93, 95, 96, 98, 100, 102, 103, 105, 107, 109, 111, 113, 115, 118, 119, 121, 123–125, 127, 129, 131, 133, 134, 136, 138, 140, 142, 143, 146, 148, 150, 152, 180, 182, 184, 186, 188, 192, 193, 194
- `mlr_reflections$learner_predict_types`, 48, 51
- `mlr_reflections$learner_properties`, 48, 51
- `mlr_reflections$task_feature_types`, 48, 180
- `mlr_tasks_lazy_iris`, 197
- `mlr_tasks_mnist`, 198
- `mlr_tasks_tiny_imagenet`, 199
- model descriptor union, 172
- `model_descriptor_to_learner`, 53, 55, 174, 180, 182, 184, 186, 201, 202, 203–205, 215
- `model_descriptor_to_learner()`, 191, 192, 194
- `model_descriptor_to_module`, 53, 55, 174, 180, 182, 184, 186, 200–202, 202, 204, 205, 215
- `model_descriptor_union`, 53, 55, 172, 174, 178, 180, 182, 184, 186, 188, 197, 201–203, 203, 205, 215
- `ModelDescriptor`, 53–55, 153, 171, 172, 174, 177, 178, 180, 182, 184, 186–189, 191, 192, 194, 196, 197, 200, 202–205, 210, 215, 216, 218
- module, 55
- network, 44
- `nn_avg_pool1d()`, 57
- `nn_avg_pool2d()`, 59
- `nn_avg_pool3d()`, 61
- `nn_conv_transpose1d`, 80
- `nn_conv_transpose2d`, 82
- `nn_conv_transpose3d`, 84

- nn_graph, [53](#), [55](#), [174](#), [180](#), [182](#), [184](#), [186](#),
[200–204](#), [204](#), [205](#), [215](#)
- nn_linear, [171](#)
- nn_merge_cat, [205](#)
- nn_merge_cat(), [118](#)
- nn_merge_prod, [206](#)
- nn_merge_prod(), [120](#)
- nn_merge_sum, [206](#)
- nn_merge_sum(), [122](#)
- nn_module, [46](#), [52](#), [54](#), [55](#), [171](#), [172](#)
- nn_module(), [47](#), [51](#)
- nn_relu, [35](#)
- nn_reshape, [206](#)
- nn_reshape(), [130](#)
- nn_sequential, [90](#)
- nn_squeeze, [207](#)
- nn_squeeze(), [144](#)
- nn_unsqueeze, [207](#)
- nn_unsqueeze(), [144](#)

- optimizer, [44](#)

- ParamSet, [46–48](#), [50](#), [117](#), [154](#), [172](#), [173](#), [179](#),
[208](#), [210](#), [212–214](#), [216–218](#)
- ParamUty, [218](#)
- PipeOp, [18](#), [100](#), [171](#), [173](#)
- pipeop_preproc_torch, [152](#), [208](#)
- PipeOpModule, [14](#), [153](#), [171–173](#), [201](#), [204](#)
- PipeOpModule (mlr_pipeops_module), [54](#)
- PipeOpNOP, [171](#), [201](#)
- PipeOpPreprocTorchAugmentCenterCrop
(mlr_pipeops_preproc_torch.augment_center_crop),
[157](#)
- PipeOpPreprocTorchAugmentColorJitter
(mlr_pipeops_preproc_torch.augment_color_jitter),
[157](#)
- PipeOpPreprocTorchAugmentCrop
(mlr_pipeops_preproc_torch.augment_crop),
[158](#)
- PipeOpPreprocTorchAugmentHflip
(mlr_pipeops_preproc_torch.augment_hflip),
[159](#)
- PipeOpPreprocTorchAugmentRandomAffine
(mlr_pipeops_preproc_torch.augment_random_affine),
[159](#)
- PipeOpPreprocTorchAugmentRandomChoice
(mlr_pipeops_preproc_torch.augment_random_choice),
[160](#)
- PipeOpPreprocTorchAugmentRandomCrop
(mlr_pipeops_preproc_torch.augment_random_crop),
[160](#)
- PipeOpPreprocTorchAugmentRandomHorizontalFlip
(mlr_pipeops_preproc_torch.augment_random_horizonta),
[161](#)
- PipeOpPreprocTorchAugmentRandomOrder
(mlr_pipeops_preproc_torch.augment_random_order),
[162](#)
- PipeOpPreprocTorchAugmentRandomResizedCrop
(mlr_pipeops_preproc_torch.augment_random_resized_c),
[162](#)
- PipeOpPreprocTorchAugmentRandomVerticalFlip
(mlr_pipeops_preproc_torch.augment_random_vertical),
[163](#)
- PipeOpPreprocTorchAugmentResizedCrop
(mlr_pipeops_preproc_torch.augment_resized_crop),
[163](#)
- PipeOpPreprocTorchAugmentRotate
(mlr_pipeops_preproc_torch.augment_rotate),
[164](#)
- PipeOpPreprocTorchAugmentVflip
(mlr_pipeops_preproc_torch.augment_vflip),
[165](#)
- PipeOpPreprocTorchTrafoAdjustBrightness
(mlr_pipeops_preproc_torch.trafo_adjust_brightness),
[165](#)
- PipeOpPreprocTorchTrafoAdjustGamma
(mlr_pipeops_preproc_torch.trafo_adjust_gamma),
[166](#)
- PipeOpPreprocTorchTrafoAdjustHue
(mlr_pipeops_preproc_torch.trafo_adjust_hue),
[166](#)
- PipeOpPreprocTorchTrafoAdjustSaturation
(mlr_pipeops_preproc_torch.trafo_adjust_saturation),
[167](#)
- PipeOpPreprocTorchTrafoGrayscale
(mlr_pipeops_preproc_torch.trafo_grayscale),
[167](#)
- PipeOpPreprocTorchTrafoNop
(mlr_pipeops_preproc_torch.trafo_nop),
[168](#)
- PipeOpPreprocTorchTrafoNormalize
(mlr_pipeops_preproc_torch.trafo_normalize),
[168](#)
- PipeOpPreprocTorchTrafoPad
(mlr_pipeops_preproc_torch.trafo_pad),
[169](#)

- PipeOpPreprocTorchTrafoReshape
(mlr_pipeops_preproc_torch.trafo_reshape),
[169](#)
- PipeOpPreprocTorchTrafoResize
(mlr_pipeops_preproc_torch.trafo_resize),
[170](#)
- PipeOpPreprocTorchTrafoRgbToGrayscale
(mlr_pipeops_preproc_torch.trafo_rgb_to_grayscale),
[170](#)
- PipeOpTaskPreproc, [152](#), [153](#)
- PipeOpTaskPreprocSimple, [153](#)
- PipeOpTaskPreprocTorch, [157–170](#), [208](#),
[209](#)
- PipeOpTaskPreprocTorch
(mlr_pipeops_preproc_torch),
[152](#)
- PipeOpTorch, [54](#), [57](#), [59](#), [61](#), [63](#), [65](#), [67](#), [70](#),
[71](#), [73](#), [75](#), [77](#), [79](#), [82](#), [84](#), [86](#), [88](#), [90](#),
[92](#), [93](#), [95](#), [97](#), [100](#), [102](#), [104](#), [106](#),
[108](#), [109](#), [112](#), [114](#), [116](#), [118](#), [120](#),
[122](#), [124](#), [126](#), [128](#), [130](#), [131](#), [133](#),
[135](#), [137](#), [139](#), [140](#), [142](#), [144](#), [147](#),
[148](#), [150](#), [172](#), [179](#), [181](#), [183](#), [185](#),
[187](#), [200](#), [203](#)
- PipeOpTorch (mlr_pipeops_torch), [171](#)
- PipeOpTorchAvgPool1D
(mlr_pipeops_nn_avg_pool1d), [57](#)
- PipeOpTorchAvgPool2D
(mlr_pipeops_nn_avg_pool2d), [59](#)
- PipeOpTorchAvgPool3D
(mlr_pipeops_nn_avg_pool3d), [61](#)
- PipeOpTorchBatchNorm1D
(mlr_pipeops_nn_batch_norm1d),
[63](#)
- PipeOpTorchBatchNorm2D
(mlr_pipeops_nn_batch_norm2d),
[65](#)
- PipeOpTorchBatchNorm3D
(mlr_pipeops_nn_batch_norm3d),
[67](#)
- PipeOpTorchBlock
(mlr_pipeops_nn_block), [69](#)
- PipeOpTorchCallbacks, [200](#)
- PipeOpTorchCallbacks
(mlr_pipeops_torch_callbacks),
[177](#)
- PipeOpTorchCELU (mlr_pipeops_nn_celu),
[71](#)
- PipeOpTorchConv1D
(mlr_pipeops_nn_conv1d), [73](#)
- PipeOpTorchConv2D
(mlr_pipeops_nn_conv2d), [75](#)
- PipeOpTorchConv3D
(mlr_pipeops_nn_conv3d), [77](#)
- PipeOpTorchConvTranspose1D
(mlr_pipeops_nn_conv_transpose1d),
[79](#)
- PipeOpTorchConvTranspose2D
(mlr_pipeops_nn_conv_transpose2d),
[81](#)
- PipeOpTorchConvTranspose3D
(mlr_pipeops_nn_conv_transpose3d),
[84](#)
- PipeOpTorchDropout
(mlr_pipeops_nn_dropout), [86](#)
- PipeOpTorchELU (mlr_pipeops_nn_elu), [88](#)
- PipeOpTorchFlatten
(mlr_pipeops_nn_flatten), [90](#)
- PipeOpTorchGELU (mlr_pipeops_nn_gelu),
[91](#)
- PipeOpTorchGLU (mlr_pipeops_nn_glu), [93](#)
- PipeOpTorchHardShrink
(mlr_pipeops_nn_hardshrink), [95](#)
- PipeOpTorchHardSigmoid
(mlr_pipeops_nn_hardsigmoid),
[97](#)
- PipeOpTorchHardTanh
(mlr_pipeops_nn_hardtanh), [98](#)
- PipeOpTorchHead, [171](#), [174](#)
- PipeOpTorchHead (mlr_pipeops_nn_head),
[100](#)
- PipeOpTorchIngress, [54](#), [172](#), [200](#)
- PipeOpTorchIngress
(mlr_pipeops_torch_ingress),
[178](#)
- PipeOpTorchIngressCategorical, [178](#)
- PipeOpTorchIngressCategorical
(mlr_pipeops_torch_ingress_categ),
[180](#)
- PipeOpTorchIngressLazyTensor, [178](#)
- PipeOpTorchIngressLazyTensor
(mlr_pipeops_torch_ingress_ltnsr),
[182](#)
- PipeOpTorchIngressNumeric, [178](#)
- PipeOpTorchIngressNumeric
(mlr_pipeops_torch_ingress_num),

- 185
- PipeOpTorchLayerNorm
(mlr_pipeops_nn_layer_norm),
102
- PipeOpTorchLeakyReLU
(mlr_pipeops_nn_leaky_relu),
104
- PipeOpTorchLinear
(mlr_pipeops_nn_linear), 106
- PipeOpTorchLogSigmoid
(mlr_pipeops_nn_log_sigmoid),
107
- PipeOpTorchLoss, 200
- PipeOpTorchLoss
(mlr_pipeops_torch_loss), 187
- PipeOpTorchMaxPool1D
(mlr_pipeops_nn_max_pool1d),
109
- PipeOpTorchMaxPool2D
(mlr_pipeops_nn_max_pool2d),
111
- PipeOpTorchMaxPool3D
(mlr_pipeops_nn_max_pool3d),
114
- PipeOpTorchMerge
(mlr_pipeops_nn_merge), 116
- PipeOpTorchMergeCat, 116
- PipeOpTorchMergeCat
(mlr_pipeops_nn_merge_cat), 118
- PipeOpTorchMergeProd, 116
- PipeOpTorchMergeProd
(mlr_pipeops_nn_merge_prod),
120
- PipeOpTorchMergeSum, 116
- PipeOpTorchMergeSum
(mlr_pipeops_nn_merge_sum), 122
- PipeOpTorchModel, 153
- PipeOpTorchModel
(mlr_pipeops_torch_model), 189
- PipeOpTorchModelClassif
(mlr_pipeops_torch_model_classif),
192
- PipeOpTorchModelRegr
(mlr_pipeops_torch_model_regr),
194
- PipeOpTorchOptimizer, 200
- PipeOpTorchOptimizer
(mlr_pipeops_torch_optimizer),
196
- PipeOpTorchPReLU
(mlr_pipeops_nn_prelu), 124
- PipeOpTorchReLU (mlr_pipeops_nn_relu),
126
- PipeOpTorchReLU6
(mlr_pipeops_nn_relu6), 128
- PipeOpTorchReshape
(mlr_pipeops_nn_reshape), 129
- PipeOpTorchRRReLU
(mlr_pipeops_nn_rrelu), 131
- PipeOpTorchSELU (mlr_pipeops_nn_selu),
133
- PipeOpTorchSigmoid
(mlr_pipeops_nn_sigmoid), 135
- PipeOpTorchSoftmax
(mlr_pipeops_nn_softmax), 137
- PipeOpTorchSoftPlus
(mlr_pipeops_nn_softplus), 138
- PipeOpTorchSoftShrink
(mlr_pipeops_nn_softshrink),
140
- PipeOpTorchSoftSign
(mlr_pipeops_nn_softsign), 142
- PipeOpTorchSqueeze
(mlr_pipeops_nn_squeeze), 144
- PipeOpTorchTanh (mlr_pipeops_nn_tanh),
147
- PipeOpTorchTanhShrink
(mlr_pipeops_nn_tanhshrink),
148
- PipeOpTorchThreshold
(mlr_pipeops_nn_threshold), 150
- PipeOpTorchUnsqueeze
(mlr_pipeops_nn_unsqueeze), 144
- R6, 15, 23, 28, 33, 35, 38, 40, 41, 47, 50, 52,
55, 58, 60, 62, 64, 66, 68, 70, 72, 74,
76, 78, 80, 83, 85, 87, 88, 90, 92, 94,
96, 97, 99, 101, 103, 105, 106, 108,
110, 112, 115, 117, 119, 121, 123,
125, 127, 128, 130, 132, 134, 136,
137, 139, 141, 143, 145, 147, 149,
151, 154, 173, 177, 179, 181, 183,
186, 187, 191, 192, 194, 196, 211,
213, 216, 219
- R6::R6Class, 197
- R6Class, 13, 14, 157–170, 209, 222

- t_clbk, [9–11](#), [14](#), [19–21](#), [27](#), [29](#), [31](#), [34](#), [212](#), [214](#), [217](#), [220](#), [223](#), [223](#), [225](#), [226](#)
- t_clbk(), [19](#), [210](#)
- t_clbks(t_clbk), [223](#)
- t_loss, [9–11](#), [20](#), [21](#), [212](#), [214](#), [217](#), [220](#), [224](#), [224](#), [226](#)
- t_loss(), [20](#), [216](#)
- t_losses(t_loss), [224](#)
- t_opt, [9–11](#), [19–21](#), [212](#), [214](#), [217](#), [220](#), [224](#), [225](#), [225](#)
- t_opt(), [218](#)
- t_opts(t_opt), [225](#)
- Task, [32](#), [33](#), [39](#), [46](#), [49](#), [155](#), [171](#), [172](#), [174](#), [177](#), [196](#), [201](#), [209](#), [215](#)
- task, [198](#), [199](#)
- task_dataset, [209](#)
- task_dataset(), [153](#)
- tensor, [55](#), [210](#)
- tensors, [171](#)
- torch::data_loader, [32](#), [33](#), [46](#)
- torch::dataset, [14](#), [15](#), [46](#), [210](#)
- torch::nn_batch_norm1d(), [63](#)
- torch::nn_batch_norm2d(), [65](#)
- torch::nn_batch_norm3d(), [67](#)
- torch::nn_celu(), [71](#)
- torch::nn_conv1d(), [73](#)
- torch::nn_conv2d(), [75](#)
- torch::nn_conv3d(), [77](#)
- torch::nn_dropout(), [86](#)
- torch::nn_elu(), [88](#)
- torch::nn_flatten(), [90](#)
- torch::nn_gelu(), [92](#)
- torch::nn_glu(), [94](#)
- torch::nn_hardshrink(), [95](#)
- torch::nn_hardsigmoid(), [97](#)
- torch::nn_hardswish(), [104](#)
- torch::nn_hardtanh(), [99](#)
- torch::nn_layer_norm(), [103](#)
- torch::nn_linear(), [101](#), [106](#)
- torch::nn_log_sigmoid(), [108](#)
- torch::nn_max_pool1d(), [110](#)
- torch::nn_max_pool2d(), [112](#)
- torch::nn_max_pool3d(), [114](#)
- torch::nn_module, [32](#), [34](#), [46](#)
- torch::nn_prelu(), [125](#)
- torch::nn_relu(), [126](#)
- torch::nn_relu6(), [128](#)
- torch::nn_rrelu(), [132](#)
- torch::nn_selu(), [134](#)
- torch::nn_sigmoid(), [135](#)
- torch::nn_softmax(), [137](#)
- torch::nn_softplus(), [139](#)
- torch::nn_softshrink(), [141](#)
- torch::nn_softsign(), [142](#)
- torch::nn_tanh(), [147](#)
- torch::nn_tanhshrink(), [149](#)
- torch::nn_threshold(), [151](#)
- torch::optimizer, [32](#), [34](#)
- torch::sampler, [45](#), [190](#)
- torch::torch_reshape(), [130](#)
- torch::torch_squeeze(), [144](#), [207](#)
- torch::torch_unsqueeze(), [144](#), [207](#)
- torch_callback, [9](#), [14](#), [19](#), [27](#), [29](#), [31](#), [34](#), [212](#), [220](#), [224](#)
- torch_callback(), [12](#), [26](#)
- torch_tensor, [15](#), [46](#), [154](#), [219](#)
- TorchCallback, [8–12](#), [14](#), [19–21](#), [25–27](#), [29](#), [31](#), [34](#), [36](#), [38](#), [40](#), [42](#), [47](#), [48](#), [51](#), [52](#), [178](#), [210](#), [210](#), [212](#), [214](#), [217](#), [220](#), [222–226](#)
- TorchDescriptor, [9–11](#), [20](#), [21](#), [212](#), [212](#), [217](#), [220](#), [224–226](#)
- TorchIngressToken, [53](#), [55](#), [174](#), [179](#), [180](#), [182](#), [184](#), [186](#), [201–205](#), [209](#), [215](#)
- TorchIngressToken(), [52](#)
- TorchLoss, [9–11](#), [20](#), [21](#), [36](#), [38](#), [40](#), [42](#), [47](#), [48](#), [51](#), [52](#), [188](#), [201](#), [212](#), [214](#), [216](#), [220](#), [224–226](#)
- TorchOptimizer, [9–11](#), [20](#), [21](#), [36](#), [38](#), [40](#), [42](#), [47](#), [48](#), [51](#), [52](#), [196](#), [201](#), [212](#), [214](#), [217](#), [218](#), [224–226](#)
- torchvision::tiny_imagenet_dataset(), [199](#)
- torchvision::transform_adjust_brightness, [165](#)
- torchvision::transform_adjust_gamma, [166](#)
- torchvision::transform_adjust_hue, [166](#)
- torchvision::transform_adjust_saturation, [167](#)
- torchvision::transform_center_crop, [157](#)
- torchvision::transform_color_jitter, [157](#)
- torchvision::transform_crop, [158](#)
- torchvision::transform_grayscale, [167](#)

`torchvision::transform_hflip`, [159](#)
`torchvision::transform_normalize`, [168](#)
`torchvision::transform_pad`, [169](#)
`torchvision::transform_random_affine`,
[159](#)
`torchvision::transform_random_choice`,
[160](#)
`torchvision::transform_random_crop`,
[160](#)
`torchvision::transform_random_horizontal_flip`,
[161](#)
`torchvision::transform_random_order`,
[162](#)
`torchvision::transform_random_resized_crop`,
[162](#)
`torchvision::transform_random_vertical_flip`,
[163](#)
`torchvision::transform_resize`, [170](#)
`torchvision::transform_resized_crop`,
[163](#)
`torchvision::transform_rgb_to_grayscale`,
[170](#)
`torchvision::transform_rotate`, [164](#)
`torchvision::transform_vflip`, [165](#)